				AMENDE	FOR D REPORT							
			1. WELL NAME and NUMBER 5-31D-36 BTR									
2. TYPE (OF WORK	DRILL NEW WE	3. FIELD OR WILDCA	T CEDAR	RIM							
									TIZATION A		NT NAM	E
6. NAME	OF OPERATO	R	Oil Well	BILL BARRE	TT COPP			7. OPERATOR PHONE	303 312-	9164		
8. ADDRE	SS OF OPERA				0, Denver, CO, 80202			9. OPERATOR E-MAII			nm.	
	RAL LEASE NU	JMBER	1000 10111 0110	010 200	11. MINERAL OWNERS			12. SURFACE OWNER	SHIP			
		1420H626405	12 = 'fee')		FEDERAL IND	IAN 📵 STATE 🔵) FEE ()	FEDERAL INI	DIAN ()	STATE (E (<u>)</u>
		FACE OWNER (if I		Robert B	. Giase			16. SURFACE OWNE	415-435-	4739		
				et. Apt 11	04, San Francisco, CA 9	4109					,	
	N ALLOTTEE 2 = 'INDIAN')	OR TRIBE NAME			18. INTEND TO COMMI MULTIPLE FORMATION		FROM	19. SLANT				
<u> </u>					YES (Submit C	ommingling Application	on) NO 📵	VERTICAL DIF	RECTIONAL	📵 но	ORIZONT	AL 🔵
20. LOC	ATION OF WE	LL		FC	OTAGES	QTR-QTR	SECTION	TOWNSHIP	RAN	IGE	МЕ	RIDIAN
LOCATI	ON AT SURFA	CE		1982 FI	NL 632 FWL	SWNW	31	3.0 S	6.0	W		U
Top of U	Uppermost Pr	oducing Zone		1978 FI	NL 810 FWL	SWNW	31	3.0 S	6.0	W		U
At Tota				1980 Fi	NL 810 FWL	SWNW	31	3.0 S	6.0	W		U
21. COUI	NTY	DUCHESNE			22. DISTANCE TO NEA	REST LEASE LINE (Fe	eet)	23. NUMBER OF ACRES IN DRILLING UNIT 640				
					25. DISTANCE TO NEAL (Applied For Drilling of		POOL	26. PROPOSED DEPTH MD: 9473 TVD: 9468				
27. ELEVATION - GROUND LEVEL 28. BOND NUMBER							29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE 43-180					
27. ELEV	ATION - GRO	JND LEVEL 6613			28. BOND NUMBER	LPM8874725			OVAL NUM	BER IF AP	PLICABL	.E
27. ELEV	ATION - GROU					LPM8874725	rmation		OVAL NUM	BER IF AP	PLICABL	.E
27. ELEV	Hole Size		Length	Weigh	Hole, Casing,		rmation		OVAL NUM	BER IF AP	PLICABL	.E Weight
		6613	Length 0 - 80	Weigh 65.0	Hole, Casing,	and Cement Info	rmation	WATER RIGHTS APPR	OVAL NUM	BER IF AP		
String	Hole Size	6613 Casing Size		_	Hole, Casing,	and Cement Info		WATER RIGHTS APPR	43-18	Sacks	Yield	Weight
String Cond	Hole Size	Casing Size	0 - 80	65.0	Hole, Casing, t Grade & Thread Unknown	and Cement Info Max Mud Wt. 8.8	Halliburto	Cement Unknown	AOVAL NUM 43-18	Sacks	Yield 0.0	Weight 0.0
String Cond	Hole Size	Casing Size	0 - 80	65.0	Hole, Casing, t Grade & Thread Unknown	and Cement Info Max Mud Wt. 8.8	Halliburto	Cement Unknown	AOVAL NUM 43-18	Sacks 0 400	Yield 0.0 3.16	Weight 0.0 11.0
String Cond Surf	Hole Size 26 12.25	6613 Casing Size 16 9.625	0 - 80	65.0 36.0	Hole, Casing, Grade & Thread Unknown J-55 ST&C	and Cement Info Max Mud Wt. 8.8 8.8	Halliburto	Cement Unknown on Light , Type Unkr	AOVAL NUM 43-18	Sacks 0 400 210	Yield 0.0 3.16 1.36	Weight 0.0 11.0 14.8
String Cond Surf	Hole Size 26 12.25	6613 Casing Size 16 9.625	0 - 80	65.0 36.0	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C	and Cement Info Max Mud Wt. 8.8 8.8	Halliburto	Cement Unknown on Light , Type Unkr	AOVAL NUM 43-18	Sacks 0 400 210 650	Yield 0.0 3.16 1.36 2.31	0.0 11.0 14.8 11.0
String Cond Surf	26 12.25 8.75	6613 Casing Size 16 9.625 5.5	0 - 80 0 - 2700 0 - 9473	65.0 36.0 17.0	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C	and Cement Info Max Mud Wt. 8.8 8.8 9.7	Halliburton	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown	43-18	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	0.0 11.0 14.8 11.0
String Cond Surf	Hole Size 26 12.25 8.75	6613 Casing Size 16 9.625 5.5	0 - 80 0 - 2700 0 - 9473	65.0 36.0 17.0	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C A** CHED IN ACCORDAN	and Cement Info Max Mud Wt. 8.8 8.8 9.7 FTACHMENTS CE WITH THE UTA	Halliburton	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown	43-18	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	0.0 11.0 14.8 11.0
String Cond Surf Prod	Hole Size 26 12.25 8.75	Casing Size 16 9.625 5.5	0 - 80 0 - 2700 0 - 9473	65.0 36.0 17.0	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C A** CHED IN ACCORDAN	and Cement Info Max Mud Wt. 8.8 8.8 9.7 FTACHMENTS CE WITH THE UTA	Halliburton Halliburton HOIL AND GAS	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown	nown known	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	0.0 11.0 14.8 11.0
String Cond Surf Prod	Hole Size 26 12.25 8.75 VE	Casing Size 16 9.625 5.5 ERIFY THE FOL	0 - 80 0 - 2700 0 - 9473 LOWING AR	65.0 36.0 17.0 E ATTAC	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C ACHED IN ACCORDAN	and Cement Info Max Mud Wt. 8.8 8.8 9.7 FTACHMENTS CE WITH THE UTA FORM	Halliburton Halliburton HOIL AND GAS	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown	nown known	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	0.0 11.0 14.8 11.0
String Cond Surf Prod	Hole Size 26 12.25 8.75 VE	Casing Size 16 9.625 5.5 ERIFY THE FOL MAP PREPARED I	0 - 80 0 - 2700 0 - 9473 LOWING AR	65.0 36.0 17.0 E ATTAC	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C ACHED IN ACCORDAN R OR ENGINEER T (IF FEE SURFACE)	AND CEMENT INFO Max Mud Wt. 8.8 8.8 9.7 FORM FORM TOPO	Halliburton Halliburton HALLIBURTON HOIL AND GAS PLETE DRILLING P	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown CONSERVATION G LAN S OTHER THAN THE LI	nown known	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	Weight 0.0 11.0 14.8 11.0
String Cond Surf Prod	Hole Size 26 12.25 8.75 VELL PLAT OR FFIDAVIT OF S RECTIONAL S	Casing Size 16 9.625 5.5 ERIFY THE FOL MAP PREPARED I	0 - 80 0 - 2700 0 - 9473 LOWING AR	65.0 36.0 17.0 E ATTAC SURVEYO GREEMEN LY OR HC	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C A** CHED IN ACCORDAN R OR ENGINEER T (IF FEE SURFACE) PRIZONTALLY DRILLED)	AND CEMENT INFO Max Mud Wt. 8.8 8.8 9.7 FORM FORM TOPO	Halliburton Halliburton Halliburton HALLIBURTON HOIL AND GAS PLETE DRILLING P 5. IF OPERATOR I GRAPHICAL MAP PHONE 303	Cement Unknown on Light , Type Unkr Premium , Type Un Unknown Unknown CONSERVATION G LAN S OTHER THAN THE LI	ASE OWN	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	Weight 0.0 11.0 14.8 11.0
String Cond Surf Prod I A I NAME V SIGNATI	Hole Size 26 12.25 8.75 VELL PLAT OR FFIDAVIT OF S RECTIONAL S	Casing Size 16 9.625 5.5 ERIFY THE FOL MAP PREPARED I TATUS OF SURFA SURVEY PLAN (IF acher	0 - 80 0 - 2700 0 - 9473 LOWING AR	E ATTAC SURVEYO GREEMEN LY OR HC	Hole, Casing, Grade & Thread Unknown J-55 ST&C P-110 LT&C CHED IN ACCORDAN R OR ENGINEER T (IF FEE SURFACE) DRIZONTALLY DRILLED) LE Senior Permit Analyst	AND CEMENT INFO Max Mud Wt. 8.8 8.8 9.7 FORM FORM TOPO	Halliburton Halliburton Halliburton HALLIBURTON HOIL AND GAS PLETE DRILLING P 5. IF OPERATOR I GRAPHICAL MAP PHONE 303	Cement Unknown On Light , Type Unkr Premium , Type Unknown Unknown Unknown CONSERVATION G LAN S OTHER THAN THE LI	ASE OWN	Sacks 0 400 210 650 910	Yield 0.0 3.16 1.36 2.31	Weight 0.0 11.0 14.8 11.0

DRILLING PLAN

BILL BARRETT CORPORATION

5-31D-36 BTR Well Pad

Lot 2 (SW NW), 1982' FNL and 632' FWL, Section 31, T3S-R6W, USB&M (surface hole) Lot 2 (SW NW), 1980' FNL and 810' FWL, Section 31, T3S-R6W, USB&M (bottom hole) Duchesne County, Utah

1 - 2. <u>Estimated Tops of Geological Markers and Formations Expected to Contain Water, Oil and Gas and Other Minerals</u>

Formation	Depth – MD	Depth – TVD
Lower Green River*	4,951'	4,948'
Douglas Creek	5,787'	5,783'
Black Shale	6,603'	6,598'
Castle Peak	6,738'	6,733'
Uteland Butte	7,103'	7,098'
Wasatch*	7,508'	7,503'
TD	9,473'	9,468'

^{*}PROSPECTIVE PAY

To operate most efficiently in this manner.

The Wasatch and the Lower Green River are primary objectives for oil/gas.

Base of Useable Water = 1,128'

3. BOP and Pressure Containment Data

Depth Intervals	ervals BOP Equipment								
0-2,700	No pressure control required								
2,700' – TD	11" 5000# Ram Type BOP								
	11" 5000# Annular BOP								
- Drilling spool to a	accommodate choke and kill lines;								
- Ancillary equipme	ent and choke manifold rated at 5,000 psi. All BOP and BOPE tests will be in								
accordance with the	he requirements of onshore Order No. 2;								
- The BLM and the	- The BLM and the State of Utah Division of Oil, Gas and Mining will be notified 24 hours in								
advance of all BC	advance of all BOP pressure tests.								
- BOP hand wheels	may be underneath the sub-structure of the rig if the drilling rig used is set up								

4. <u>Casing Program</u>

<u>Hole</u> <u>Size</u>	SETTING DEPTH (FROM) (TO)		Casing Size	Casing Weight	Casing Grade	Thread	Condition
26"	Surface	80'	16"	65#			
12 1/4"	Surface	2,700'	9 5/8"	36#	J or K 55	BT&C	New
8 3/4"	Surface	TD	5 ½"	17#	P-110	LT&C	New
NOTE:	In addition	. 8 ¾" hole	size may cha	ange to 7 7/8	" at the poin	t the bit is cl	nanged out.

RECEIVED: December 28, 2011

Bill Barrett Corporation Drilling Program #5-31D-36 BTR Duchesne County, Utah

5. <u>Cementing Program</u>

Casing	Cementing
16" Conductor Casing	Grout
9 5/8" Surface Casing	Lead with approximately 400 sx Halliburton Light Premium with additives mixed at 11.0 ppg (yield = 3.16 ft ³ /sx) circulated to surface with 75% excess. Top of lead estimated at surface.
	Tail with approximately 210 sx Halliburton Premium cement with additives mixed at 14.8 ppg (yield = 1.36 ft ³ /sx), calculated hole volume with 75% excess. Top of tail estimated at 2,200'.
5 ½" Production Casing	Lead with approximately 650 sx Tuned Light cement with additives, mixed at 11.0 ppg (yield = 2.31 ft ³ /sx,) . Top of lead estimated at 2,200°.
	<i>Tail</i> with approximately 910 sx Halliburton Econocem cement with additives mixed at 13.5 ppg (yield = 1.42 ft ³ /sx). Top of tail estimated at 6.103 .

6. <u>Mud Program</u>

<u>Interval</u>	<u>Weight</u>	Viscosity	Fluid Loss (API filtrate)	<u>Remarks</u>
0'-80'	8.3 - 8.8	26 - 36	NC	Freshwater Spud Mud Fluid
				System
80' - 2,700'	8.3 - 8.8	26 - 36	NC	Freshwater Spud Mud Fluid
				System
2,700' – TD	8.6 - 9.7	42-52	20 cc or less	DAP Polymer Fluid System

Note: Sufficient mud materials to maintain mud properties, control lost circulation and to contain "kicks" will be available at wellsite. BBC may require minor amounts of diesel to be added to its fluid system in order to reduce torque and drag.

7. <u>Testing, Logging and Core Programs</u>

Cores	None anticipated
Testing	None anticipated; drill stem tests may be run on shows of interest;
Sampling	30' to 50' samples; surface casing to TD. Preserve samples all show intervals;
Surveys	MWD as needed to land wellbore;
Logging	DIL-GR-SP, FDC-CNL-GR-CALIPER-Pe-Microlog, Sonic-GR (all TD to surface).
	FMI & Sonic Scanner to be run at geologist's discretion.

Bill Barrett Corporation Drilling Program #5-31D-36 BTR Duchesne County, Utah

8. Anticipated Abnormal Pressures or Temperatures

No abnormal pressures or temperatures or other hazards are anticipated.

Maximum anticipated bottom hole pressure equals approximately 4776 psi* and maximum anticipated surface pressure equals approximately 2693 psi** (bottom hole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

*Max Mud Wt x 0.052 x TD = A (bottom hole pressure)

**Maximum surface pressure = A - (0.22 x TD)

9. Auxiliary Equipment

- a) Upper kelly cock; lower Kelly cock will be installed while drilling
- b) Inside BOP or stab-in valve (available on rig floor)
- c) Safety valve(s) and subs to fit all string connections in use
- d) Mud monitoring will be visually observed

10. Location and Type of Water Supply

Water for the drilling and completion will be trucked from the Duchesne City Culinary Water Dock located in Sec. 1, T4S, R5W.

11. <u>Drilling Schedule</u>

Location Construction: June 2012 Spud: June 2012

Duration: 15 days drilling time


45 days completion time

RECEIVED: December 28, 2011



LAKE CANYON & BLACK TAIL RIDGE CEMENT VOLUMES

Well Name: 5-31D-36 BTR Surface Hole Data: Calculated Data: Total Depth: 2,700' Lead Volume: 1205.8 Top of Cement: 0' Lead Fill: 2,200' Tail Volume: OD of Hole: 12.250" 274.0 500' OD of Casing: Tail Fill: 9.625 **Cement Data:** Calculated # of Sacks: ft³/sk Lead Yield: 3.16 # SK's Lead: % Excess: 75% Top of Lead: 0' Tail Yield: ft°/sk # SK's Tail: 1.36 % Excess: 75% Top of Tail: 2,200'



5-31D-36 BTR Proposed Cementing Program

Job Recommendation		Sur	face Casing
Lead Cement - (2200' - 0')			
Halliburton Light Premium	Fluid Weight:	11.0	lbm/gal
5.0 lbm/sk Silicalite Compacted	Slurry Yield:	3.16	ft ³ /sk
0.25 lbm/sk Kwik Seal	Total Mixing Fluid:	19.48	Gal/sk
0.125 lbm/sk Poly-E-Flake	Top of Fluid:	0'	
2.0% Bentonite	Calculated Fill:	2,200'	
	Volume:	214.74	bbl
	Proposed Sacks:	400	sks
Tail Cement - (TD - 2200')			
Premium Cement	Fluid Weight:	14.8	lbm/gal
2.0% Calcium Chloride	Slurry Yield:	1.36	ft ³ /sk
	Total Mixing Fluid:	6.37	Gal/sk
	Top of Fluid:	2,200'	
	Calculated Fill:	500'	
	Volume:	48.80	bbl
	Proposed Sacks:	210	sks

Job Recommendation		Produc	tion Casing
Lead Cement - (6103' - 2200')			
Tuned Light TM System	Fluid Weight:	11.0	lbm/gal
	Slurry Yield:	2.31	ft ³ /sk
	Total Mixing Fluid:	10.65	Gal/sk
	Top of Fluid:	2,200'	
	Calculated Fill:	3,903'	
	Volume:		bbl
	Proposed Sacks:	650	sks
Tail Cement - (9473' - 6103')			
Econocem TM System	Fluid Weight:	13.5	lbm/gal
0.125 lbm/sk Poly-E-Flake	Slurry Yield:	1.42	ft ³ /sk
1.0 lbm/sk Granulite TR 1/4	Total Mixing Fluid:	6.61	Gal/sk
	Top of Fluid:	6,103'	
	Calculated Fill:	3,370'	
	Volume:	227.42	bbl
	Proposed Sacks:	910	sks

RECEIVED: December 28, 2011

PRESSURE CONTROL EQUIPMENT – Schematic Attached

A. Type: Eleven (11) Inch Double Gate Hydraulic BOP with Eleven (11) Inch Annular Preventer. The blow out preventer will be equipped as follows:

- 1. One (1) blind ram (above).
- 2. One (1) pipe ram (below).
- 3. Drilling spool with two (2) side outlets (choke side 3-inch minimum, kill side 2-inch minimum).
- 4. 3-inch diameter choke line.
- 5. Two (2) choke line valves (3-inch minimum).
- 6. Kill line (2-inch minimum).
- 7. Two (2) chokes with one (1) remotely controlled from the rig floor.
- 8. Two (2) kill line valves, and a check valve (2-inch minimum).
- 9. Upper and lower kelly cock valves with handles available.
- 10. Safety valve(s) & subs to fit all drill string connections in use.
- 11. Inside BOP or float sub available.
- 12. Pressure gauge on choke manifold.
- 13. Fill-up line above the uppermost preventer.

B. Pressure Rating: 5,000 psi

C. Testing Procedure:

Annular Preventer

At a minimum, the Annular Preventer will be pressure tested to 50% of the rated working pressure for a period of ten (10) minutes or until provisions of the test are met, whichever is longer.

At a minimum the above pressure test will be performed:

- 1. When the annular preventer is initially installed;
- 2. Whenever any seal subject to test pressure is broken;
- 3. Following related repairs; and
- 4. At thirty (30) day intervals.

In addition, the Annular Preventer will be functionally operated at least weekly.

Blow-Out Preventer

At a minimum, the BOP, choke manifold, and related equipment will be pressure tested to the approved working pressure of the BOP stack (if isolated from the surface casing by a test plug) or to 70% of the internal yieldstrength of the surface casing (if the BOP is not isolated from the casing by a test plug). Pressure will be

maintained for a period of at least ten (10) minutes or until the requirmentsof the test are met, whichever is longer.

At a minimum, the above pressure test will be performed:

- 1. When the BOP is initially installed;
- 2. Whenever any seal subject to test pressure is broken;
- 3. Following related repairs; and
- 4. At thirty (30) day intervals.

In addition the pipe and blind rams will be activated each trip, but not more than once each day. All BOP drills and tests will be recorded in the IADC driller's log.

D. Choke Manifold Equipment:

All choke lines will be straight lines unless turns use tee blocks or are targeted with running tees, and will be anchored to prevent whip and vibration.

E. Accumulator:

The accumulator will have sufficient capacity to open the hydraulically-controlled choke line valve (if so equipped), close all rams plus the annular preventer, and retain a minimum of 200 psi above precharge on the closing manifold without the use of closing unit pumps. The fluid reservoir capacity will be double the usable fluid volume of the accumulator system capacity and the fluid level of the reservoir will be maintained at the manufacturer's recommendations.

The BOP system will have two (2) independent power sources to close the preventers. Nitrogen bottles (3 minimum) will be one (1) of these independent power sources and will maintain a charge equal to the manufacturer's specifications.

The accumulator precharge pressure test will be conducted prior to connecting the closing unit to the BOP stack and at least once every six (6) months thereafter. The accumulator pressure will be corrected if the measured precharge pressure is found to be above or below the maximum or minimum limits specified in the *Onshore Oil & Gas Order Number 2*.


A manual locking device (i.e. hand wheels) or automatic locking device will be installed on all systems of 2M or greater. A valve will be installed in the closing line as close as possible to the annular preventer to act as a locking device. This valve will be maintained in the open position and will be closed only when the power source for the accumulator is inoperative.


Remote controls shall be readily accessible to the driller. Remote controls for all 3M or greater systems will be capable of closing all preventers. Remote controls for 5M or greater systems will be capable of both opening and closing all preventers. Master controls will be at the accumulator and will be capable of opening and closing all preventers and the choke line valve (if so equipped).


F. Miscellaneous Information:


The Blow-Out Preventer and related pressure control equipment will be installed, tested and maintained in compliance with the specifications in and requirements of *Onshore Oil & Gas Order Number 2*. The hydraulic BOP closing unit will be located at least twenty-five (25) feet from the well head but readily accessible to the driller. Exact locations and configurations of the hydraulic BOP closing unit will depend upon the particular rig contracted to drill this hole.

A flare line will be installed after the choke manifold, extending 125 feet (minimum) from the center of the drill hole to a separate flare pit.









API Well Number: 43013511460000

Bill Barrett Corporation

COMPANY DETAILS: BILL BARRETT CORP

Calculation Method: Minimum Curvature

Error System: ISCWSA

-3750

-1250

0

Vertical Section at 88.71° (2500 ft/in)

1250

2500

3750

5000

Scan Method: Closest Approach 3D Error Surface: Elliptical Conic Warning Method: Error Ratio SITE DETAILS: 5-31D-36 BTR


Blacktail Ridge

Site Centre Latitude: 40° 10′ 41.401 N

Longitude: 110° 36' 43.099 W

Positional Uncertainity: 0.0 Convergence: 0.57 Local North: True

WELLBORE TARGET DETAILS (LAT/LONG)											
Name	TVD	+N/-S	+E/-W	Latitude	Longitude	Shape					
5-31D 3PT MKR	6208.0	4.0	178.5	40° 10' 41.441 N	110° 36' 40.799 W	Rectangle (Sides: L200.0 W200.0)					
5-31D PBHL	9468.0	4.0	178.5	40° 10' 41.441 N	110° 36' 40.799 W	Rectangle (Sides: L200.0 W200.0)					



Model: IGRF2010

BILL BARRETT CORP

DUCHESNE COUNTY, UT (NAD 27) 5-31D-36 BTR 5-31D-36 BTR

5-31D-36 BTR

Plan: Design #1

Standard Planning Report

13 December, 2011

Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-31D-36 BTR

 Well:
 5-31D-36 BTR

 Wellbore:
 5-31D-36 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-31D-36 BTR

KB @ 6629.0ft (Original Well Elev) KB @ 6629.0ft (Original Well Elev)

True

Minimum Curvature

65.78

52.206

Project DUCHESNE COUNTY, UT (NAD 27)

IGRF2010

Map System: US State Plane 1927 (Exact solution)

Geo Datum: NAD 1927 (NADCON CONUS)

Map Zone: Utah Central 4302

System Datum:

Ground Level

Site 5-31D-36 BTR

Northing: 673,174.73 ft Site Position: Latitude: 40° 10' 41.401 N From: Lat/Long Easting: 2,248,126.59 ft Longitude: 110° 36' 43.099 W **Position Uncertainty:** 0.0 ft Slot Radius: **Grid Convergence:** 0.57 °

osition uncertainty: 0.0 it slot Radius: Grid Convergence: 0.57

Well 5-31D-36 BTR

Well Position +N/-S 0.0 ft Northing: 673,174.73 ft Latitude: 40° 10' 41.401 N +E/-W 0.0 ft Easting: 2,248,126.60 ft Longitude: 110° 36' 43.099 W **Position Uncertainty** 0.0 ft Wellhead Elevation: ft **Ground Level:** 6,613.0 ft

Wellbore 5-31D-36 BTR

Magnetics Model Name Sample Date Declination Dip Angle Field Strength

(°) (°) (nT)

11.49

12/13/2011

Design #1 Design **Audit Notes:** Version: Phase: PLAN Tie On Depth: 0.0 Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (ft) (ft) (ft) (°) 0.0 0.0 0.0 88.71

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,906.4	3.10	88.71	2,906.3	0.1	5.6	1.50	1.50	0.00	88.71	
6,006.3	3.10	88.71	6,001.7	3.9	173.0	0.00	0.00	0.00	0.00	
6,212.7	0.00	0.00	6,208.0	4.0	178.5	1.50	-1.50	0.00	180.00	5-31D 3PT MKR
9,472.7	0.00	0.00	9,468.0	4.0	178.5	0.00	0.00	0.00	0.00	5-31D PBHL

Planning Report

Database: Compass

Company: BILL BARRETT CORP

 Project:
 DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-31D-36 BTR

 Well:
 5-31D-36 BTR

 Wellbore:
 5-31D-36 BTR

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-31D-36 BTR

KB @ 6629.0ft (Original Well Elev) KB @ 6629.0ft (Original Well Elev)

True

Minimum Curvature

Design:	Design #1								
Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0 1,300.0	0.00	0.00	1,200.0 1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00 0.00	0.00 0.00	1,400.0	0.0 0.0	0.0 0.0	0.0 0.0	0.00 0.00	0.00 0.00	0.00 0.00
1,500.0 1,600.0	0.00 0.00	0.00 0.00	1,500.0 1,600.0	0.0 0.0	0.0 0.0	0.0 0.0	0.00 0.00	0.00 0.00	0.00 0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00
2,800.0	1.50	88.71	2,800.0	0.0	1.3	1.3	1.50	1.50	0.00
2,900.0	3.00	88.71	2,899.9	0.1	5.2	5.2	1.50	1.50	0.00
2,906.4	3.10	88.71	2,906.3	0.1	5.6	5.6	1.50	1.50	0.00
2,998.2	3.10	88.71	2,998.0	0.2	10.5	10.5	0.00	0.00	0.00
Green River									
3,000.0	3.10	88.71	2,999.8	0.2	10.6	10.6	0.00	0.00	0.00
3,100.0 3,200.0	3.10 3.10	88.71 88.71	3,099.6 3,199.5	0.4 0.5	16.0 21.4	16.0 21.4	0.00 0.00	0.00 0.00	0.00 0.00
3,300.0	3.10	88.71	3,299.3	0.6	26.8	26.8	0.00	0.00	0.00
3,400.0	3.10	88.71	3,399.2	0.7	32.2	32.2	0.00	0.00	0.00
3,500.0 3,504.0	3.10 3.10	88.71 88.71	3,499.0 3,503.0	0.8 0.9	37.6 37.8	37.6 37.9	0.00 0.00	0.00 0.00	0.00 0.00
, ,	3.10	00.71	3,303.0	0.9	37.0	37.9	0.00	0.00	0.00
Mahogany 3,600.0	3.10	88.71	3,598.9	1.0	43.0	43.0	0.00	0.00	0.00
3,700.0	3.10	88.71	3,698.7	1.1	48.4	48.4	0.00	0.00	0.00
3,800.0 3,900.0	3.10 3.10	88.71 88.71	3,798.6 3,898.4	1.2 1.3	53.8 59.2	53.8 59.2	0.00 0.00	0.00 0.00	0.00 0.00
4,000.0	3.10	88.71	3,998.3	1.5	64.6	64.6	0.00	0.00	0.00
4,100.0	3.10	88.71	4,098.2	1.6	70.0	70.0	0.00	0.00	0.00
4,200.0	3.10	88.71	4,198.0	1.7	75.4	75.4	0.00	0.00	0.00
4,200.0	3.10	88.71	4,196.0	1.7	80.8	80.8	0.00	0.00	0.00
4,400.0	3.10	88.71	4,397.7	1.9	86.2	86.2	0.00	0.00	0.00
4,500.0	3.10	88.71	4,497.6	2.1	91.6	91.6	0.00	0.00	0.00
4,600.0	3.10	88.71	4,597.4	2.2	97.0	97.0	0.00	0.00	0.00
4,700.0	3.10	88.71	4,697.3	2.3	102.4	102.4	0.00	0.00	0.00
4,800.0	3.10	88.71	4,797.1	2.4	107.8	107.8	0.00	0.00	0.00
			· · · · · · · · · · · · · · · · · · ·						

Planning Report

Database: Compass

Company: BILL BARRETT CORP

Project: DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-31D-36 BTR

 Well:
 5-31D-36 BTR

 Wellbore:
 5-31D-36 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well 5-31D-36 BTR

KB @ 6629.0ft (Original Well Elev) KB @ 6629.0ft (Original Well Elev)

True

Minimum Curvature

•	Design #1								
ed Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,900.0		88.71	4,897.0	2.5	113.2	113.2	0.00	0.00	0.00
4,951.1 TGR3	3.10	88.71	4,948.0	2.6	116.0	116.0	0.00	0.00	0.00
5,000.0	3.10	88.71	4,996.8	2.7	118.6	118.7	0.00	0.00	0.00
5,100.0	3.10	88.71	5,096.7	2.8	124.0	124.1	0.00	0.00	0.00
5,200.0		88.71	5,196.6	2.9	129.4	129.5	0.00	0.00	0.00
5,300.0		88.71	5,296.4	3.0	134.8	134.9	0.00	0.00	0.00
5,400.0 5,500.0		88.71 88.71	5,396.3 5,496.1	3.2 3.3	140.2 145.6	140.3 145.7	0.00 0.00	0.00 0.00	0.00 0.00
5,600.0 5,700.0		88.71 88.71	5,596.0 5,695.8	3.4 3.5	151.0 156.4	151.1 156.5	0.00 0.00	0.00 0.00	0.00 0.00
5,787.3		88.71	5,783.0	3.6	161.1	161.2	0.00	0.00	0.00
Douglas C									
5,800.0		88.71	5,795.7	3.6	161.8	161.9	0.00	0.00	0.00
5,900.0	3.10	88.71	5,895.5	3.8	167.2	167.3	0.00	0.00	0.00
6,000.0		88.71	5,995.4	3.9	172.6	172.7	0.00	0.00	0.00
6,006.3		88.71	6,001.7	3.9	173.0	173.0	0.00	0.00	0.00
6,100.0 6,200.0		88.71 88.71	6,095.3 6,195.3	4.0 4.0	176.9 178.5	176.9 178.6	1.50 1.50	-1.50 -1.50	0.00 0.00
6,200.0		0.00	6,195.3 6,208.0	4.0	178.5	178.6	1.50	-1.50 -1.50	-697.12
	- 5-31D 3PT MKR	0.00	-,200.0						302
6,300.0	0.00	0.00	6,295.3	4.0	178.5	178.6	0.00	0.00	0.00
6,400.0		0.00	6,395.3	4.0	178.5	178.6	0.00	0.00	0.00
6,500.0	0.00	0.00	6,495.3	4.0	178.5	178.6	0.00	0.00	0.00
6,600.0		0.00	6,595.3	4.0	178.5	178.6	0.00	0.00	0.00
6,602.7		0.00	6,598.0	4.0	178.5	178.6	0.00	0.00	0.00
Black Sha									
6,700.0 6,737.7		0.00 0.00	6,695.3 6,733.0	4.0 4.0	178.5 178.5	178.6 178.6	0.00 0.00	0.00 0.00	0.00 0.00
Castle Pea		0.00	0,700.0	4.0	170.0	170.0	0.00	0.00	0.00
6,800.0		0.00	6,795.3	4.0	178.5	178.6	0.00	0.00	0.00
6,900.0		0.00	6,895.3	4.0	178.5	178.6	0.00	0.00	0.00
7,000.0	0.00	0.00	6,995.3	4.0	178.5	178.6	0.00	0.00	0.00
7,100.0		0.00	7,095.3	4.0	178.5	178.6	0.00	0.00	0.00
7,102.7		0.00	7,098.0	4.0	178.5	178.6	0.00	0.00	0.00
Uteland B: 7,162.7		0.00	7,158.0	4.0	178.5	178.6	0.00	0.00	0.00
CR 1	0.00	0.00	7,100.0	٠.٠	170.5	170.0	0.00	0.00	0.00
7,200.0	0.00	0.00	7,195.3	4.0	178.5	178.6	0.00	0.00	0.00
7,300.0	0.00	0.00	7,295.3	4.0	178.5	178.6	0.00	0.00	0.00
7,400.0		0.00	7,395.3	4.0	178.5	178.6	0.00	0.00	0.00
7,500.0		0.00	7,495.3	4.0	178.5	178.6	0.00	0.00	0.00
7,507.7	0.00	0.00	7,503.0	4.0	178.5	178.6	0.00	0.00	0.00
Wasatch 7,600.0	0.00	0.00	7,595.3	4.0	178.5	178.6	0.00	0.00	0.00
7,600.0		0.00	7,638.0	4.0	178.5	178.6	0.00	0.00	0.00
CR 2	3.1.0		,						
7,700.0	0.00	0.00	7,695.3	4.0	178.5	178.6	0.00	0.00	0.00
7,700.0		0.00	7,795.3	4.0	178.5	178.6	0.00	0.00	0.00
7,900.0		0.00	7,895.3	4.0	178.5	178.6	0.00	0.00	0.00
7,932.7	0.00	0.00	7,928.0	4.0	178.5	178.6	0.00	0.00	0.00
CR 3									
8,000.0	0.00	0.00	7,995.3	4.0	178.5	178.6	0.00	0.00	0.00

Planning Report

Database: Compass

Company: BILL BARRETT CORP

Project: DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-31D-36 BTR

 Well:
 5-31D-36 BTR

 Wellbore:
 5-31D-36 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-31D-36 BTR

KB @ 6629.0ft (Original Well Elev) KB @ 6629.0ft (Original Well Elev)

True

Minimum Curvature

lanned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
8,100.0 8,200.0 8,247.7	0.00 0.00 0.00	0.00 0.00 0.00	8,095.3 8,195.3 8,243.0	4.0 4.0 4.0	178.5 178.5 178.5	178.6 178.6 178.6	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
CR 4 8,300.0 8,400.0	0.00 0.00	0.00 0.00	8,295.3 8,395.3	4.0 4.0	178.5 178.5	178.6 178.6	0.00 0.00	0.00 0.00	0.00 0.00
8,500.0 8,552.7	0.00 0.00	0.00 0.00	8,495.3 8,548.0	4.0 4.0	178.5 178.5	178.6 178.6	0.00 0.00	0.00 0.00	0.00 0.00
CR 4A 8,600.0 8,642.7	0.00 0.00	0.00 0.00	8,595.3 8,638.0	4.0 4.0	178.5 178.5	178.6 178.6	0.00 0.00	0.00 0.00	0.00 0.00
CR 5 8,652.7	0.00	0.00	8,648.0	4.0	178.5	178.6	0.00	0.00	0.00
8,700.0 8,800.0 8,900.0 9,000.0 9,100.0	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	8,695.3 8,795.3 8,895.3 8,995.3 9,095.3	4.0 4.0 4.0 4.0 4.0	178.5 178.5 178.5 178.5 178.5	178.6 178.6 178.6 178.6 178.6	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
9,172.7 CR 7	0.00	0.00	9,168.0	4.0	178.5	178.6	0.00	0.00	0.00
9,200.0 9,300.0 9,400.0 9,472.7	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	9,195.3 9,295.3 9,395.3 9,468.0	4.0 4.0 4.0 4.0	178.5 178.5 178.5 178.5	178.6 178.6 178.6 178.6	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00
5-31D PBHL									

ations						
	Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
	2,998.2	2,998.0	Green River		0.00	
	3,504.0	3,503.0	Mahogany		0.00	
	4,951.1	4,948.0	TGR3		0.00	
	5,787.3	5,783.0	Douglas Creek		0.00	
	6,212.7	6,208.0	3PT MKR		0.00	
	6,602.7	6,598.0	Black Shale Facies		0.00	
	6,737.7	6,733.0	Castle Peak		0.00	
	7,102.7	7,098.0	Uteland Butte		0.00	
	7,162.7	7,158.0	CR 1		0.00	
	7,507.7	7,503.0	Wasatch		0.00	
	7,642.7	7,638.0	CR 2		0.00	
	7,932.7	7,928.0	CR 3		0.00	
	8,247.7	8,243.0	CR 4		0.00	
	8,552.7	8,548.0	CR 4A		0.00	
	8,642.7	8,638.0	CR 5		0.00	
	8,652.7	8,648.0	CR 6		0.00	
	9,172.7	9,168.0	CR 7		0.00	

Bill Barrett Corp

Planning Report

Database: Compass

Company: BILL BARRETT CORP

Project: DUCHESNE COUNTY, UT (NAD 27)

 Site:
 5-31D-36 BTR

 Well:
 5-31D-36 BTR

 Wellbore:
 5-31D-36 BTR

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 5-31D-36 BTR

KB @ 6629.0ft (Original Well Elev) KB @ 6629.0ft (Original Well Elev)

True

Minimum Curvature

12/13/2011 12:28:35PM Page 6 COMPASS 2003.21 Build 25

RECEIVED: December 28, 2011

SURFACE DAMAGE AND RIGHT-OF-WAY SETTLEMENT AGREEMENT

This Agreement, made and entered into this the <u>22nd</u> day of <u>February</u>, 2011, by and between <u>Robert B. Giase</u>, 2190 <u>Washington Street</u>, <u>Apt. 1104</u>, <u>San Francisco</u>, <u>CA 94109-2814</u> ("Surface Owner") and <u>Bill Barrett Corporation</u>, 1099 18th Street, <u>Suite 2300</u>, <u>Denver CO 80202</u>, ("BBC").

WITNESSETH THAT:

WHEREAS, BBC owns undivided interests in certain oil and gas leases ("leases") covering and affecting All of Section 31, Township 3 South, Range 6 West, USM, of <u>Duchesne</u> County, Utah; and,

WHEREAS, such leases grant to BBC the right and privilege of ingress, egress, exploring, drilling, mining, operating for, producing and owning oil and gas and all other products produced therewith, together with the right to make surveys on said lands, lay pipelines, construct roads and bridges, dig canals, build power stations, telephone lines, employee houses and other structures on said lands, necessary or useful in BBC's operations; and,

WHEREAS, BBC, pursuant to its rights under the Leases, intends to drill the #5-31-36 BTR wells at a legal drill-site location in the SW1/4NW1/4 of Section 31 Township 3 South, Range 6 West, USM, Duchesne County, Utah; and,

Any topsoil which is removed by BBC on Surface Owner's land will be stockpiled at the drillsite and will be redistributed on the drillsite upon completion of all operations, and the land reseeded with grasses and/or native plants by BBC upon written request by Surface Owner. All mud pits will be filled and material and debris will be removed from the drillsite upon completion of operations. BBC shall remove from the lands covered hereby, at any time during the term hereof or within six (6) months after the plugging and abandonment of the well drilled pursuant to this Agreement, any or all structures, pipes, equipment and other facilities placed on, over, under, through and across any lands covered hereby, excepting fences, culverts, and other land improvements required by the Surface Owner, and title thereto shall be vested in BBC at all times, and shall in no event be considered or construed as fixtures thereto.

BBC shall maintain all roads used pursuant to this Agreement and shall install culverts where necessary to insure adequate drainage from all roads.

BBC shall repair any fences and gates damaged by them during the course of their operations on the lands subject to this Agreement.

Surface Owner and their heirs or assigns shall have full access and use of the road built pursuant to this Agreement.


This Agreement shall inure to the benefit of the parties hereto, their heirs, successors and assigns and shall be a burden running with the land.


This Agreement may be executed in any number of counterparts and all such counterparts shall be deemed to constitute a single Agreement and the execution of one counterpart by any party hereto shall have the same force and effect as if said party had signed all other counterparts.


IN WITNESS WHEREOF, the parties have executed this Surface Damage Settlement Agreement effective as of the <u>22nd</u> day of <u>February</u>, <u>2011</u>.

SURFACE OWNER:	BILL BARRETT CORPORATION
By: Robert B. Giase	By: Lilia to Lum As Agent for Bill Barrett Corporation
STATE OF CALIFORNIA)	
COUNTY OF Marin	
Giase known to me to be the person	, 2011, personally appeared before me Robert B. on whose name is subscribed to the foregoing that he executed the same for the purpose and
	Notary Public Residing at: Tiburon, CA
My Commission Expires: 6/22/2013	JORDAN ROBERT TWITCHELL Commission # 1855263 Notary Public - California Marin County My Comm. Expires Jun 22, 2013
STATE OF UTAH)	
COUNTY OF SALT LAKE)	
Clint W. Turner , who, being b	that said instrument was signed in behalf of said of its Board of Directors and said
	Notary Public
	Residing at:

My Commission Expires: 10 - 24-2014







STATE OF UTAH COUNTY OF DUCHESNE

SURFACE LAND USE AGREEMENT

KNOW ALL MEN BY THESE PRESENTS, THAT:

WHEREAS, Bandanna Ranch, LLC, whose mailing address is 556 Confluence Avenue, Murray, Utah 84123 (hereinafter referred to as GRANTOR, whether one or more), is the owner of the surface of the following described property located in Duchesne County, Utah, to-wit:

TOWNSHIP 3 SOUTH, RANGE 7 WEST, USM

Section 36: SEI/4NEI/4 See Exhibit "A" Well No. 5-31-36-BTR

WHEREAS, Bill Barrett Corporation., whose address is 1099 18th Street, Suite 2300, Denver, CO 80202, (hereinafter referred to as GRANTEE), desires to obtain rights to construct a road and appurtenances thereto on a portion of said property.

WHEREAS, Grantee has agreed to reimburse Grantor for actual damages and injuries to all crops, timber, fences and other improvements located on the surface which results from grantee's operations hereunder, provided that Grantee shall not be held liable or responsible for acts of providence or occurrences beyond Grantee's control, such payment to be made upon commencement of operations to construct the road and pipeline or pipelines; so,

Grantee shall repair or replace any fences damaged by them, their employees or contractors with a new fence that will be exactly the same type of fence that is damaged.

Upon abandonment of the facilities Grantee shall restore such facilities to as near its original condition as possible and shall furnish a recordable document evidencing such abandonment to Grantor, or Grantor's successors in interest, and all rights that Grantee has under the terms of this Agreement shall be terminated.

The making, execution and delivery of this document by Grantor has been induced by no representations, statements, warranties, or other agreements other than those herein expressed. This agreement embodies the entire understanding of the parties, and this instrument may be amended or modified only by subsequent written agreement of the parties.

This agreement shall inure to the benefit of the parties hereto, their heirs, successors, and assigns and shall be a burden running with the land.

IN WITNESS WHEREOF, this Surface Land Use Agreement is executed as of the dates of the respective acknowledgments of the parties hereto, but is effective as of the 16th of November, 2011.

GRANTOR:

By: Y

PAT FORD

BRIDGING 111.

GRANTEE:

BILL BARRETT CORPORATION

Clint W. Turner, as Agent for Bill Barrett Corporation

ACKNOWLEDGMENTS

STATE OF UTAH	
COUNTY OF SALT LAKE	
Por this 1st day of Decen	uly sworn, did say that he is the Hest. for Bandanna
Ranch, LLC and that said instrument was signed in its Board of Directors and saidexecuted the same.	behalf of said corporation by authority of a resolution of acknowledged to me that said corporation
My Commission Expires: 12/10///	Softmof Western Notary Public Tarment on Valle
STATE OF UTAH	Notary Public STEFANI H MESTUZZI # 572368 Commission Expires December 10, 2011 Stute Of Utah
Clint W. Turner, who, being by me duly sworn, did	, 2011, personally appeared before me d say that he is the Agent for Bill Barrett Corporation and corporation by authority of a resolution of its Board of to me that said corporation executed the same.
My Commission Expires: 9-8-15	Notaty Public Residing at: West Torday 117

STATE OF UTAH COUNTY OF DUCHESNE

SURFACE LAND USE AGREEMENT

KNOW ALL MEN BY THESE PRESENTS, THAT:

WHEREAS, Raymond Campione, 9610 E. Eddystone Court, Chandler, AZ 85248-7112 (hereinafter referred to as GRANTOR), whether one or more), is the owner of the surface of the following described property located in Duchesne County, Utah, to-wit:

TOWNSHIP 3 SOUTH, RANGE 6 WEST, USM

Section 31: E1/2E1/2W1/2NW1/4 Less State Highway

See Exhibit "A"

WHEREAS, Bill Barrett Corporation., whose address is 1099 18th Street, Suite 2300, Denver, CO 80202 (hereinafter referred to as GRANTEE) desires to construct a pipeline or pipelines and appurtenances thereto for the transportation of natural gas, water, saltwater and other substances on a portion of said property.

WHEREAS, Grantee has agreed to reimburse Grantor for actual damages and injuries to all crops, timber, fences and other improvements located on the surface which results from grantee's operations hereunder, provided that Grantee shall not be held liable or responsible for acts of providence or occurrences beyond Grantee's control, such payment to be made upon commencement of operations to construct the road and pipeline or pipelines; so,

Grantee shall repair or replace any fences damaged by them, their employees or contractors with a new fence that will be exactly the same type of fence that is damaged. Grantee shall also reseed the pipeline damaged area with native grasses.

Upon abandonment of the facilities Grantee shall restore such facilities to as near its original condition as possible and shall furnish a recordable document evidencing such abandonment to Grantor, or Grantor's successors in interest, and all rights that Grantee has under the terms of this Agreement shall be terminated.

The making, execution and delivery of this document by Grantor has been induced by no representations, statements, warranties, or other agreements other than those herein expressed. This agreement embodies the entire understanding of the parties, and this instrument may be amended or modified only by subsequent written agreement of the parties.

This agreement shall inure to the benefit of the parties hereto, their heirs, successors, and assigns and shall be a burden running with the land.

IN WITNESS WHEREOF, this Surface Land Use Agreement is executed as of the dates of the respective acknowledgments of the parties hereto, but is effective as of the 22nd day of February, 2011.

GRANTOR:

Raymond Campione

Date: 3-22-2011

GRANTEE:

BILL BARRETT CORPORATION

Clint W. Turner, as Agent for Bill Barrett Corporation

ACKNOWLEDGMENT

STATE OF ARIZONA COUNTY OF

On the 22 day of March, 2011, personally appeared before me Raymond Campione Known to me to be the person whose name is subscribed to the foregoing instrument and acknowledged to me that he executed the same for the purpose and consideration therein expressed.

My Commission Expires: 10-31-2014

Notary Public Residing at:

JACQUELINE MIONI-MOORE
NOTARY PUBLIC - ARIZONA
MARICOPA COUNTY
My Commission Expires
October 31, 2014


ACKNOWLEDGMENT


STATE OF UTAH COUNTY OF SALT LAKE


On this day of April, 2011, personally appeared before me Clint W. Turner, who, being by me duly sworn, did say that he is the Agent for Bill Barrett Corporation and that said instrument was signed in behalf of said corporation by authority of a resolution of its Board of Directors and said Clint W. Turner acknowledged to me that said corporation executed the same.

My Commission Expires: 10 - 24-2014

DANIEL WILLIAM COSTLEY NOTARY PUBLIC-STATE OF UTAH COMMISSION# 600945 COMM. EXP. 10-24-2014 Notary Public Residing at: Willie Contly







STATE OF UTAH COUNTY OF DUCHESNE

SURFACE LAND USE AGREEMENT

KNOW ALL MEN BY THESE PRESENTS, THAT:

WHEREAS, Norris Northrup and Janice Northrup, 6145 West 13900 South, Herriman, UT 84096-3866 (hereinafter referred to as GRANTOR), whether one or more), is the owner of the surface of the following described property located in Duchesne County, Utah, to-wit:

TOWNSHIP 3 SOUTH, RANGE 6 WEST, USM

Section 31: Beginning at the North quarter corner of said Section; the South 0°08'58" East a distance of 1,248.38 feet along the North South Quarter Section line to the North right of way line of US 40; the Northwesterly a distance of 781.83 feet along said North right of way line to a right of way marker; thence North 86°39'56" West a distance of 533.92 feet along said North North right of way line to the West line of the E1/2W1/2 of said Section; thence North 0°07'10" West a distance of 1,145.19 feet along said West line to the North line of said Section; thence North 89°37'23" East a distance of 1,311.42 feet to the point of beginning.

See Exhibit "A"

WHEREAS, Bill Barrett Corporation., whose address is 1099 18th Street, Suite 2300, Denver, CO 80202 (hereinafter referred to as GRANTEE) desires to construct a pipeline or pipelines and appurtenances thereto for the transportation of natural gas, water, saltwater and other substances on a portion of said property.

WHEREAS, Grantee has agreed to reimburse Grantor for actual damages and injuries to all crops, timber, fences and other improvements located on the surface which results from grantee's operations hereunder, provided that Grantee shall not be held liable or responsible for acts of providence or occurrences beyond Grantee's control, such payment to be made upon commencement of operations to construct the road and pipeline or pipelines; so,

Grantee shall repair or replace any fences damaged by them, their employees or contractors with a new fence that will be exactly the same type of fence that is damaged. Grantee shall also reseed the pipeline damaged area with native grasses.

Upon abandonment of the facilities Grantee shall restore such facilities to as near its original condition as possible and shall furnish a recordable document evidencing such abandonment to Grantor, or Grantor's successors in interest, and all rights that Grantee has under the terms of this Agreement shall be terminated.

The making, execution and delivery of this document by Grantor has been induced by no representations, statements, warranties, or other agreements other than those herein expressed. This agreement embodies the entire understanding of the parties, and this instrument may be amended or modified only by subsequent written agreement of the parties.

This agreement shall inure to the benefit of the parties hereto, their heirs, successors, and assigns and shall be a burden running with the land.

IN WITNESS WHEREOF, this Surface Land Use Agreement is executed as of the dates of the respective acknowledgments of the parties hereto, but is effective as of the 22nd day of February, 2011.

By: Norris Northrup

By: Janjee Northrup

Date: $\frac{3}{1} - \frac{1}{1} - \frac{1}{1}$

GRANTEE:

BILL BARRETT CORPORATION

By: Clint W. Turner, as Agent for Bill Barrett Corporation


ACKNOWLEDGMENT

STATE OF UTAH COUNTY OF SALT LAKE

On the _l _day of _Max_____, 2011, personally appeared before me <u>Norris Northrup and Janice Northrup</u> known to me to be the persons whose names are subscribed to the foregoing instrument and acknowledged to me that they executed the same for the purpose and consideration therein expressed.

My Commission Expires: 11/10/2011

Notary Public Residing at:



Willia Coultry

ACKNOWLEDGMENT


STATE OF UTAH COUNTY OF SALT LAKE


On this 17 day of March, 2011, personally appeared before me Clint W. Turner, who, being by me duly sworn, did say that he is the Agent for Bill Barrett Corporation and that said instrument was signed in behalf of said corporation by authority of a resolution of its Board of Directors and said Clint W. Turner acknowledged to me that said corporation executed the same.


My Commission Expires: 10 - 24 - 2014

DANIEL WILLIAM COSTLEY NOTARY PUBLIC-STATE OF UTAH COMMISSION# 600945 COMM. EXP. 10-24-2014

Notary Public Residing at:







SURFACE USE PLAN

BILL BARRETT CORPORATION

5-31D-36 BTR Well Pad

Lot 2 (SW NW), 1982' FNL and 632' FWL, Section 31, T3S-R6W, USB&M (surface hole) Lot 2 (SW NW), 1980' FNL and 810' FWL, Section 31, T3S-R6W, USB&M (bottom hole) Duchesne County, Utah

The onsite inspection for this pad occurred on October 28, 2011. Site-specific notes, conditions and plat changes requested at the onsite are reflected within this APD and summarized below.

- a. Relocate production equipment on cut near the access road while maximizing interim reclamation:
- b. Insert an 18-inch culvert as the access road enters the pad area;
- c. Salvage woody material for use in reclamation;

The excavation contractor would be provided with an approved copy of the surface use plan of operations before initiating construction.

1. Existing Roads:

- a. The proposed well site is located approximately 12.0 miles west of Duchesne, Utah. Maps and directions reflecting the route to the proposed well site are included (see Topographic maps A and B).
- b. The Utah Department of Transportation maintained Highway 40 would be utilized for 11.8 miles to the existing Duchesne County maintained CR-382 Road that would be utilized for 0.1 miles and provides access to the planned new access road.
- c. Project roads would require routine year-round maintenance to provide year-round access. Maintenance would include inspections, reduction of ruts and holes, maintenance to keep water off the road, replacement of surfacing materials, and clearing of sediment blocking ditches and culverts. Should snow removal become necessary, roads would be cleared with a motor grader and snow would be stored along the down gradient side to prohibit runoff onto the road. Aggregate would be used as necessary to maintain a solid running surface and minimize dust generation.
- d. Vehicle operators would obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions. Travel would be limited to the existing access roads and proposed access road.
- e. The use of roads under State and Duchesne County Road Department maintenance are necessary to access the project area with no improvements proposed. A Duchesne County road encroachment and UDOT pipeline crossing approvals are required.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

f. All existing roads would be maintained and kept in good repair during all phases of operation.

2. Planned Access Road:

- a. Approximately 438 feet of new access road trending east is planned from the existing Duchesne County maintained CR 382 Road across entirely private surface (see Topographic Map B).
- b. The planned access road would be constructed to a 30-foot ROW width with an 18-foot travel surface. See section 12.d. below for disturbance estimates.
- c. New road construction and improvements of existing roads would typically require the use of motor graders, crawler tractors, 10-yard end dump trucks, and water trucks. The standard methodology for building new roads involves the use of a crawler tractor or track hoe to windrow the vegetation to one side of the road corridor, remove topsoil to the opposing side of the corridor, and rough-in the roadway. This is followed by a grader or bulldozer to establish barrow ditches and crown the road surface. Where culverts are required, a track hoe or backhoe would trench the road and install the culverts. Some hand labor would be required when installing and armoring culverts. Road base or gravel in some instances would be necessary and would be hauled in and a grader used to smooth the running surface.
- d. The proposed road would be constructed to facilitate drainage, control erosion and minimize visual impacts by following natural contours where practical. No unnecessary side-casting of material would occur on steep slopes.
- e. A maximum grade of 10% would be maintained throughout the project with minimum cuts and fills, as necessary, to access the well.
- f. Excess rock from construction of the pad may be used for surfacing of the access road if necessary. Any additional aggregate necessary would be obtained from private or State of Utah lands in conformance with applicable regulations. Aggregate would be of sufficient size, type, and amount to allow all weather access and alleviate dust.
- g. Where topsoil removal is necessary, it would be windrowed (i.e. stockpiled/accumulated along the edge of the ROW and in a low row/pile parallel with the ROW) and re-spread over the disturbed area after construction and backfilling are completed. Vegetation removed from the disturbed area would also be re-spread to provide protection, nutrient recycling, and a seed source for reclamation.
- h. Turnouts are not proposed.
- i. One 18-inch culvert as the access road enters the pad area and no low-water crossings are anticipated.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

Adequate drainage structures, where necessary, would be incorporated into the remainder of the road to prevent soil erosion and accommodate all-weather traffic.

- j. No gates or cattle guards are anticipated at this time.
- k. Surface disturbance and vehicular travel would be limited to the approved location access road. Adequate signs would be posted, as necessary, to warn the public of project related traffic.
- All access roads and surface disturbing activities would conform to the
 appropriate standard, **no higher than necessary**, to accommodate their intended
 function adequately as outlined in the Bureau of Land Management and Forest
 Service publication: <u>Surface Operating Standards for Oil and Gas Exploration</u>
 and <u>Development</u>, Fourth Edition Revised 2007.
- m. The operator would be responsible for all maintenance needs of the new access road.

3. Location of Existing Wells (see One-Mile Radius Map):

a. Following is a list of wells with surface hole locations within a one-mile radius of the proposed pad:

i.	water wells	none
ii.	injection wells	none
iii.	disposal wells	none
iv.	drilling wells	one
v.	temp shut-in wells	none
vi.	producing wells	one
vii.	abandoned wells	one

4. <u>Location of Production Facilities</u>

- a. Surface facilities would consist of a wellhead, separator, gas meter, combustor, (1) 500 gal methanol tank, (1) 500 glycol tank, (3) 500 bbl oil tanks, (1) 500 bbl water tank, (1) 500 bbl test tank, (1) 1000 gal propane tank, a pumping unit or Roto-flex unit or ESP or gas lift unit, electrical or with a natural gas or diesel fired motor, solar panels, solar chemical and methanol pumps and one trace pump. See attached proposed facility diagram.
- b. Most wells would be fitted with a pump jack or Roto-flex unit or ESP or gas lift to assist liquid production. The prime mover for pump jacks or Roto-flex units would be small (100 horsepower or less), electric motor or natural gas or diesel fired internal combustion engines. If a gas lift is installed, it would be set on a 10 ft x 25 ft pad and the prime mover would be a natural gas-fired internal

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

combustion engine rated at 200 horsepower or less or an electric compressor of similar horsepower powered by electricity.

- c. The tank battery would be surrounded by a secondary containment berm of sufficient capacity to contain 1.1 times the entire capacity of the largest single tank and sufficient freeboard to contain precipitation. All loading lines and valves would be placed inside the berm surrounding the tank battery or would utilize catchment basins to contain spills. All liquid hydrocarbon production and measurement shall conform to the provisions of 43 CFR 3162.7-2 and Onshore Oil and Gas Order No. 4 for the measurement of oil.
- d. Gas meter run(s) would be constructed and located on lease within 500 feet of the wellheads. Meter runs would be housed and/or fenced. As practicably feasible, meters would be equipped with remote telemetry monitoring systems. All gas production and measurement shall comply with the provisions of 43 CFR 3162.7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3.
- e. A combustor may be installed at this location for control of associated condensate tank emissions. A combustor ranges from 24 inches to 48 inches wide and is approximately 27 ft tall. Combustor placement would be on existing disturbance.
- f. Approximately 3,550 feet of pipeline corridor (see Topographic Map C) containing up to three lines (one gas pipeline up to 8 inch in diameter, one water line up to 4 inch in diameter and one residue line up to 4 inch in diameter) is proposed trending west, north then east to the existing 14-30-36 BTR pipeline corridor. Pipelines would be constructed of steel, polyethylene or fiberglass crossing entirely private surface.
- g. The new segment of gas pipeline would be surface laid within a 30 foot wide pipeline corridor adjacent to the proposed access road. See 12.d below for disturbance estimates.
- h. Construction of the ROW would temporarily utilize the 30 foot disturbed width for the road for a total disturbed width of 60 foot for the road and pipeline corridors. The use of the proposed well site and access roads would facilitate the staging of the pipeline construction.
- i. Pipeline construction methods and practices would be planned and conducted by BBC with the objective of enhancing reclamation and fostering the reestablishment of the native plant community.
- j. All permanent above-ground structures would be painted a flat, non-reflective color, such as Beetle Green, to match the standard environmental colors. All facilities would be painted the designated color at the time of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

- k. Site security guidelines identified in 43 CFR 3162.7-5 and Onshore Oil and Gas Order No. 3 would be adhered to. Any modifications to proposed facilities would be reflected in the site security diagram submitted.
- 1. The site would require periodic maintenance to ensure that drainages are kept open and free of debris, and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.

5. <u>Location and Type of Water Supply:</u>

a. Water for the drilling and completion would be trucked from any of the following locations:

Water Right No. and Application or Change No.	Applicant	Allocation	Date	Point of Diversion	Source
43-180	Duchesne City Water Service District	5 cfs	8/13/2004	Knight Diversion Dam	Duchesne River
43-1202, Change a13837	Myton City	5.49 cfr and 3967 acre feet	3/21/1986	Knight Diversion Dam	Duchesne River
43-10444, Appln A57477	Duchesne County Upper Country Water	2 cfs	1994	Ditch at Source	Cow Canyon Spring
43-10446, Appln F57432	Duchesne County Upper Country Water	1.58 cfs	1994	Ditch at Source	Cow Canyon Spring
43-1273, Appln A17462	J.J.N.P. Company	7 cfs	1946	Strawberry River	Strawberry River
43-1273, Appln t36590	J.J.N.P. Company	4 cfs	6/03/2010	Strawberry River	Strawberry River
43-2505, Appln t37379	McKinnon Ranch Properties, LC	1.3 cfs	4/28/2011	Pumped from Sec, 17, T4SR6W	Water Canyon Lake
43-12415, Change A17215a	Peatross Ranch, LLC	1.89 cfs	09/2011	Dugout Pond	Strawberry River

- b. No new water well is proposed with this application.
- c. Should additional water sources be pursued they would be properly permitted through the State of Utah Division of Water Rights.
- d. Water use would vary in accordance with the formations to be drilled but would be up to approximately 5.41 acre feet for drilling and completion operations.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

6. <u>Source of Construction Material:</u>

- a. The use of materials would conform to 43 CFR 3610.2-3.
- b. No construction materials would be removed from the lease or EDA area.
- c. If any additional gravel is required, it would be obtained from a local supplier having a permitted source of materials within the general area.

7. <u>Methods of Handling Waste Disposal:</u>

- a. All wastes associated with this application would be contained and disposed of utilizing approved facilities.
- b. The reserve pit would be constructed so as not to leak, break or allow any discharge.
- c. The reserve would be lined with a 12 mil (minimum) thickness polyethylene nylon reinforced liner material. The liner(s) would overlay straw, dirt and/or bentonite if rock is encountered during excavation. The liner would overlap the pit walls and be covered with dirt and/or rocks to hold them in place. No trash, scrap pipe, or other materials that could puncture the liner would be discarded in the pit. A minimum of two feet of free board would be maintained between the maximum fluid level and the top of the reserve pit at all times.
- d. To deter livestock from entering the pit, the three sides exterior to the location would be fenced before drilling starts. Following the conclusion of drilling and completion activities, the fourth side would also be fenced.
- e. Drill cuttings would be contained in the pit and buried on-site for a period not to exceed six months, weather permitting
- f. Produced fluids from the well other than water would be decanted into steel test tank(s) until such time as construction of production facilities is completed. Any oil that may be accumulated would be transferred to a permanent production tank. Produced water may be used in further drilling and completion activities, evaporated in the pit, or would be hauled to one of the state-approved disposal facilities below:

Disposal Facilities

- 1. RNI Industries, Inc. Pleasant Valley Disposal Pits, Sec. 25, 26, 35 & 36, T4S-R3W
- 2. Pro Water LLC Blue Bench 13-1 Disposal Well (43-013-30971) NENE, Sec. 13, T3S-R5W
- 3. RN Industries, Inc. Bluebell Disposal Ponds, Sec. 2, 4 & 9, T2S-R2W
- 4. Water Disposal, Inc. Harmston 1-32-A1 Disposal Well (43-013-30224),

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

Disposal Facilities

UTR #00707, Sec. 32, T1S-R1W

- 5. Unified Water Pits Sec. 31, T2S-R4W
- 6. Iowa Tank Line Pits 8500 BLM Fence Road, Pleasant Valley
- g. Any salts and/or chemicals, which are an integral part of the drilling system, would be disposed of in the same manner as the drilling fluid.
- h. Any spills of oil, condensate, produced or frac water, drilling fluids, or other potentially deleterious substances would be recovered and either returned to its origin or disposed of at an approved disposal site, most likely in Duchesne, Utah.
- i. Chemicals on the EPA's Consolidated List of Chemicals subject to reporting under Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) may be used or stored in quantities over reportable quantities. In the course of drilling, BBC could potentially store and use diesel fuel, sand (silica), hydrochloric acid, and CO₂ gas, all described as hazardous substances in 40 CFR Part 302, Section 302.4, in quantities exceeding 10,000 pounds. In addition, natural gas condensate and crude oil and methanol may be stored or used in reportable quantities. Small quantities of retail products (paint/spray paints, solvents {e.g., WD-40}, and lubrication oil) containing non-reportable volumes of hazardous substances may be stored and used on site at any time. No extremely hazardous substances, as defined in 40 CFR 355, would be used, produced, stored, transported or disposed of in association with the drilling, testing or completion of the wells.
- j. Portable toilets and trash containers would be located onsite during drilling and completion operations. A commercial supplier would install and maintain portable toilets and equipment and would be responsible for removing sanitary waste. Sanitary waste facilities (i.e. toilet holding tanks) would be regularly pumped and their contents disposed of at approved sewage disposal facilities in Duchesne, and/or Uintah Counties, in accordance with applicable rules and regulations regarding sewage treatment and disposal. Accumulated trash and nonflammable waste materials would be hauled to an approved landfill once a week or as often as necessary. All debris and waste materials not contained in the trash containers would be cleaned up, removed from the construction ROW, well pad, or worker housing location, and disposed of at an approved landfill. Trash would be cleaned up everyday.
- k. Sanitary waste equipment and trash bins would be removed from the Project Area upon completion of access road or pipeline construction; following drilling and completion operations at an individual well pad; when worker housing is no longer needed; or as required.
- 1. A flare pit may be constructed a minimum of 110' from the wellhead(s) and may be used during completion work. In the event a flare pit proves to be unworkable, a temporary flare stack or open top tank would be installed. BBC

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

would flow back as much fluid and gas as possible into pressurized vessels, separating the fluids from the gas. In some instances, due to the completion fluids utilized within the Project Area, it is not feasible to direct the flow stream from the wellbore through pressurized vessels. In such instances BBC proposes to direct the flow to the open top tanks until flow through the pressurized vessels is feasible. At which point the fluid would either be returned to the reserve pit or placed into a tank(s). The gas would be directed to the flare pit, flare stack (each with a constant source of ignition), or may be directed into the sales pipeline.

m. Hydrocarbons would be removed from the reserve pit would as soon as practical. In the event immediate removal is not practical, the reserve pit would be flagged overhead or covered with wire or plastic mesh to protect migrating birds.

8. <u>Ancillary Facilities:</u>

- a. Garbage containers and portable toilets would be located on the well pad.
- b. On well pads where active drilling and completion is occurring, temporary housing would be provided on location for the well pad supervisor, geologist, tool pusher, and others that are required to be on location at all times. The well pad could include up to five single wide mobile homes or fifth wheel campers/trailers.
- c. A surface powerline corridor 4,688 feet in length is proposed for installation by third-party installer within a 150 foot wide powerline corridor adjacent to the proposed access road. See 12.d below for disturbance estimates. The powerline crosses entirely private surface.

9. Well Site Layout:

- a. The well would be properly identified in accordance with 43 CFR 3162.6.
- b. The pad layout, cross section diagrams and rig layout are enclosed (see Figures 1 and 2).
- c. The pad and road designs are consistent with industry specifications.
- d. The pad has been staked at its maximum size of 400 feet x 285 feet with an inboard reserve pit size of 200 feet x 100 feet x 8 feet deep. See section 12.d below for disturbance estimates.
- e. Within the approved well pad location, a crawler tractor would strip whatever topsoil is present and stockpile it along the edge of the well pad for use during reclamation. Vegetation would be distributed along the sides of the well pad.
- f. Fill from pit excavation would be stockpiled along the edge of the pit and the adjacent edge of the well pad.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

- g. Use of erosion control measures, including proper grading to minimize slopes, diversion terraces and ditches, mulching, terracing, riprap, fiber matting, temporary sediment traps, and broad-based drainage dips or low water crossings would be employed by BBC as necessary and appropriate to minimize erosion and surface runoff during well pad construction and operation. Cut and fill slopes would be constructed such that stability would be maintained for the life of the activity.
- h. All cut and fill slopes would be such that stability can be maintained for the life of the activity.
- i. Diversion ditches would be constructed, if necessary, around the well site to prevent surface waters from entering the well site area.
- j. Water application may be implemented if necessary to minimize the amount of fugitive dust.
- k. All surface disturbing activities would be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.

10. Plan for Restoration of the Surface:

- a. A site specific reclamation plan would be submitted, if requested, within 90 days of location construction to the surface managing agency or the fee landowners.
- b. Site reclamation would be accomplished for portions of the well pad not required for the continued operation of the well on this pad within six months of completion, weather permitting.
- c. The operator would control noxious weeds along access road use authorizations and well site by spraying or mechanical removal, according to the Utah Noxious Weed Act and as set forth in the approved surface damage agreements.
- d. Rat and mouse holes would be filled and compacted from bottom to top immediately upon release of the drilling rig from location. Upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1. The reserve pit would be allowed to dry prior to the commencement of backfilling work. No attempts would be made to backfill the reserve pit until it is free of standing water. Once dry, the liner would be torn and perforated before backfilling.
- e. The reserve pit and that portion of the location not needed for production facilities/operations would be recontoured to the approximate natural contours. Areas not used for production purposes would be backfilled and blended into the surrounding terrain, reseeded and erosion control measures installed. Mulching, erosion control measures and fertilization may be required to achieve acceptable stabilization. Back slopes and fore slopes would be reduced as practical and

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

scarified with the contour. The reserved topsoil would be evenly distributed over the slopes and scarified along the contour. Slopes would be seeded with the Ute Tribe specified seed mix.

f. Topsoil salvaged from the drill site and stored for more than one year would be placed at the location indicated on the well site layout drawing and graded to a depth optimum to maintain topsoil viability, seeded with the Ute Tribe prescribed seed mixture and covered with mulch for protection from wind and water erosion and to discourage the invasion of weeds.

11. <u>Surface and Mineral Ownership:</u>

- a. Surface ownership -
 - Robert B. Giase (pad area, access, pipeline and powerline segments);
 - o Fords, Inc. (access segment);
 - o Raymond Campione (pipeline and powerline segments);
 - o Norris & Janice Northrup (pipeline and powerline segments);
- b. Mineral ownership Ute Indian Tribe 988 South 7500 East; Ft. Duchesne, Utah 84026; 435-725-4982.

12. Other Information:

- a. Montgomery Archeological Consultants has conducted a Class III archeological survey. A copy of the report has been submitted under separate cover to the appropriate agencies by Montgomery as report 10-277 dated June 16, 2011.
- b. BBC would require that their personnel, contractors, and subcontractors to comply with Federal regulations intended to protect archeological and cultural resources.
- c. Project personnel and contractors would be educated on and subject to the following requirements:
 - No dogs or firearms within the Project Area.
 - No littering within the Project Area.
 - Smoking within the Project Area would only be allowed in off-operator
 active locations or in specifically designated smoking areas. All cigarette
 butts would be placed in appropriate containers and not thrown on the
 ground or out windows of vehicles; personnel and contractors would abide
 by all fire restriction orders.
 - Campfires or uncontained fires of any kind would be prohibited.
 - Portable generators used in the Project Area would have spark arrestors.

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

d. Disturbance estimates:

Approximate Acreage Disturbances

Well Pad		4.307	acres
Access	438 feet	0.302	acres
Pipeline	3550 feet	2.428	acres
Powerline	4688 feet	16.135	acres

Total 23.172 acres

Bill Barrett Corporation Surface Use Plan 5-31D-36 BTR Duchesne County, UT

OPERATOR CERTIFICATION

Certification:

I hereby certify that I, or someone under my direction supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein would be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application and that bond coverage is provided under Bill Barrett Corporations federal nationwide bond. These statements are subject to the provisions of 18 U.S.C. 1001 for the filings of false statements.

Executed this 28th day of 2011

Name: Venessa Langmacher
Position Title: Senior Permit Analyst

Address: 1099 18th Street, Suite 2300, Denver, CO 80202

Telephone: 303-312-8172


E-mail: vlangmacher@billbarrettcorp.com
Field Representative Kary Eldredge / Bill Barrett Corporation
Address: 1820 W. Highway 40, Roosevelt, UT 84066
Telephone: 435-725-3515 (office); 435-724-6789 (mobile)

E-mail: keldredge@billbarrettcorp.com

Venessa Langmacher, Senior Permit Analyst


BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. BLOWOUT PREVENTER



BILL BARRETT CORPORATION

TYPICAL 5,000 p.s.i. CHOKE MANIFOLD





December 28, 2011

Ms. Diana Mason – Petroleum Technician State of Utah Division of Oil, Gas and Mining 1594 West North Temple, Suite 1210 P. O. Box 145801 Salt Lake City, Utah 84114-5801

Re: Directional Drilling R649-3-11

Blacktail Ridge Area #5-31D-36 BTR Well

Surface: 1,982' FNL & 632' FWL, SWNW, 31-T3S-R6W, USM Bottom Hole: 1,980' FNL & 810' FWL, SWNW, 31-T3S-R6W, USM

Duchesne County, Utah

Dear Ms. Mason,

Pursuant to the filing of Bill Barrett Corporation's ("BBC") Application for Permit to Drill the above referenced well, we hereby submit this letter in accordance with Oil & Gas Conservation Rules R649-2, R649-3, R649-10 and R649-11, pertaining to the Location and Siting of Wells.


- The proposed location is within our Blacktail Ridge Area.
- BBC is permitting this well as a directional well in order to minimize surface disturbance. By locating the well at the surface location and directionally drilling from this location, BBC will be able to utilize the existing road and pipelines in the area.
- The well will be drilled under an Exploration and Development Agreement between the Ute Indian Tribe and Ute Distribution Corporation. Ute Energy, LLC owns a right to participate in this well.
- BBC certifies that it is the working interest owner of all lands within 460 feet of the proposed well location, and together with Ute Energy, LLC, we own 100% of the working interest in these lands.


Based on the information provided, BBC requests that the permit be granted pursuant to R649-3-11. Should you have any questions or need further information, please contact me at 303-312-8544.


Spricerely,


David Watts


Landman











ON-SITE PREDRILL EVALUATION

Utah Division of Oil, Gas and Mining

Operator BILL BARRETT CORP

Well Name 5-31D-36 BTR

API Number 43013511460000 APD No 5118 Field/Unit CEDAR RIM

Location: 1/4,1/4 SWNW Sec 31 Tw 3.0S Rng 6.0W 1982 FNL 632 FWL

GPS Coord (UTM) Surface Owner Robert B. Giase

Participants

Richard Powell (UDOGM), Trevor Anderson (UELS), Kary Eldredge (BBC), Don Hamilton (Starpoint)

Regional/Local Setting & Topography

This location sits approximately 500 feet south of Hwy 40. There is a slight slope toward the Hwy corridor but the sight in nearly flat. The location is approximately 12 miles west of Duchesne, Utah. There are several dwellings in the area but nothing within several hundred feet of the location.

Surface Use Plan

Current Surface Use

Wildlfe Habitat

Residential

New Road Miles Well Pad Src Const Material Surface Formation

0.08 Width 285 Length 400 Onsite UNTA

Ancillary Facilities N

Waste Management Plan Adequate? Y

Environmental Parameters

Affected Floodplains and/or Wetlands N

Flora / Fauna

Sage, grasses, scattered P-J, rabbit brush

Rabbits, elk, deer, coyote

Soil Type and Characteristics

Sandy clay loam, fractured rock pieces scattered on the surface.

Erosion Issues N

Sedimentation Issues N

Site Stability Issues N

Drainage Diverson Required? Y

Some small drainages

2/16/2012 Page 1

Berm Required? Y

Due to close proximity of Hwy 40

Erosion Sedimentation Control Required? N

Paleo Survey Run? N Paleo Potental Observed? N Cultural Survey Run? Y Cultural Resources? N

Reserve Pit

Site-Specific Factors	Site Ran	king	
Distance to Groundwater (feet)	> 200	0	
Distance to Surface Water (feet)	>1000	0	
Dist. Nearest Municipal Well (ft)	>5280	0	
Distance to Other Wells (feet)	> 1 3 2 0	0	
Native Soil Type	Mod permeability	10	
Fluid Type	Fresh Water	5	
Drill Cuttings	Normal Rock	0	
Annual Precipitation (inches)	10 to 20	5	
Affected Populations			
Presence Nearby Utility Conduits	Unknown	10	
	Final Score	30	1 Sensitivity Level

Characteristics / Requirements

Reserve pit is 200' x 100' x 8' deep. It is placed in a cut stable location. BBC typically uses either a 20 or 16 mil liner with a felt sub liner. Either will be adequate for this site.

Closed Loop Mud Required? N Liner Required? Y Liner Thickness 16 Pit Underlayment Required? Y

Other Observations / Comments

Richard Powell 1/19/2012

Evaluator Date / Time

2/16/2012 Page 2

Application for Permit to Drill Statement of Basis

Utah Division of Oil, Gas and Mining

Page 1

APD No	API Wel	llNo			5	Status	Well Type		Surf Owner	CBM
5118	4301351	1146	0000		I	LOCKED	OW		P	No
Operator	BILL BA	RRET	TT CC)RP			Surface O	wner-APD	Robert B. Gia	ase
Well Name	5-31D-3	86 BT	`R				Unit			
Field	CEDAR I	RIM					Type of W	ork	DRILL	
Location	SWNW	31	3S	6W	U	1982 FNL	632 FWL	GPS Coord		
Lucation	(TITAL)	522	0015	4.4.7	1760	ONT				

(UTM) 532981E 4447602N

Geologic Statement of Basis

The mineral rights for the proposed well are owned by the Ute Tribe. The BLM will be the agency responsible for evaluating and approving the drilling, casing and cement programs.

Brad Hill 2/8/2012
APD Evaluator Date / Time

Surface Statement of Basis

This well was previously onsited by BLM. The minerals are Indian and the surface is fee. I was unable to contact the surface owner Robert B. Giase, but there is a surface use agreement in place. According to permit contractor Don Hamilton, UDOT has approved of the access point and construction plans for the Hwy 40 access. The location is nearly flat but there are several small drainages throught the location which must be diverted around the location on both the east and west. This appears to be a good location for placement of this well.

Richard Powell 1/19/2012
Onsite Evaluator Date / Time

Conditions of Approval / Application for Permit to Drill

Conditions of hippicotton for a climit to Diffi				
Category	Condition			
Pits	A synthetic liner with a minimum thickness of 16 mils with a felt subliner shall be properly installed and maintained in the reserve pit.			
Surface	The well site shall be bermed to prevent fluids from leaving the pad.			
Surface	Drainages adjacent to the proposed pad shall be diverted around the location.			
Surface	The reserve pit shall be fenced upon completion of drilling operations.			

RECEIVED: February 16, 2012

WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED:	12/28/2011	API NO. ASSIGNED:	43013511460000

WELL NAME: 5-31D-36 BTR

OPERATOR: BILL BARRETT CORP (N2165) PHONE NUMBER: 303 312-8172

CONTACT: Venessa Langmacher

PROPOSED LOCATION: SWNW 31 030S 060W **Permit Tech Review:**

> **SURFACE: 1982 FNL 0632 FWL Engineering Review:**

> BOTTOM: 1980 FNL 0810 FWL **Geology Review:**

COUNTY: DUCHESNE

LATITUDE: 40.17815 LONGITUDE: -110.61262 UTM SURF EASTINGS: 532981.00 NORTHINGS: 4447602.00

FIELD NAME: CEDAR RIM

LEASE TYPE: 2 - Indian

LEASE NUMBER: 1420H626405 PROPOSED PRODUCING FORMATION(S): GREEN RIVER-WASATCH

SURFACE OWNER: 4 - Fee **COALBED METHANE: NO**

RECEIVED AND/OR REVIEWED: LOCATION AND SITING:

✓ PLAT R649-2-3.

Bond: INDIAN - LPM8874725 Unit:

Potash R649-3-2. General

R649-3-3. Exception Oil Shale 190-3

Oil Shale 190-13 **Drilling Unit**

Board Cause No: Cause 139-84 Water Permit: 43-180

Effective Date: 12/31/2008 **RDCC Review:**

Siting: 660' Fr Drl U Bdry & 1320' Fr Other Wells **Fee Surface Agreement**

Intent to Commingle R649-3-11. Directional Drill

Commingling Approved


Oil Shale 190-5

Comments: Presite Completed

4 - Federal Approval - dmason 5 - Statement of Basis - bhill Stipulations:

15 - Directional - dmason

API Well No: 43013511460000



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: 5-31D-36 BTR
API Well Number: 43013511460000
Lease Number: 1420H626405
Surface Owner: FEE (PRIVATE)

Approval Date: 2/16/2012

Issued to:

BILL BARRETT CORP, 1099 18th Street Ste 2300, Denver, CO 80202

Authority:

Pursuant to Utah Code Ann. 40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 139-84. The expected producing formation or pool is the GREEN RIVER-WASATCH Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Compliance with the Conditions of Approval/Application for Permit to Drill outlined in the Statement of Basis (copy attached).

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

• Within 24 hours following the spudding of the well contact Carol Daniels at 801-538-5284

API Well No: 43013511460000

(please leave a voicemail message if not available) OR

submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website

at http://oilgas.ogm.utah.gov

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) due within 5 days of spudding the well
- Monthly Status Report (Form 9) due by 5th day of the following calendar month
- Requests to Change Plans (Form 9) due prior to implementation
- Written Notice of Emergency Changes (Form 9) due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) due prior to implementation
 - Report of Water Encountered (Form 7) due within 30 days after completion
 - Well Completion Report (Form 8) due within 30 days after completion or plugging

Approved By:

For John Rogers Associate Director, Oil & Gas

RECEIVED

Form 3160-3 (August 2007)

RECEIVED MAY 1 5 2012 CORM APPROVED

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

DEC 2 8 2811

OMB No. 1004-0136 DIV. OF OIL, GAS & MINING July 31, 2010

	0.2, 0.10 0.111111
5.	Lease Serial No.
	1420H626405

APPLICATION FOR PERMIT TO DRILL OR REEN 1

APPLICATION FOR PERMIT	TO DRILL OR REEN ES	6. If Indian, Allottee or Tribe UINTAH AND OURA	
1a. Type of Work: DRILL REENTER		7. If Unit or CA Agreement,	Name and No.
1b. Type of Well: ☑ Oil Well ☐ Gas Well ☐ Otl 2. Name of Operator Contact: BILL BARRETT CORPORATION E-Mail: vlangma	ner ☐ Single Zone ☑ Multiple Zone VENESSA LANGMACHER acher@billbarrettcorp.com	8. Lease Name and Well No. 5-31D-36 BTR 9. API Well No.	
3a. Address 1099 18TH STREET SUITE 2300 DENVER, CO 80202	3b. Phone No. (include area code) Ph: 303-312-8172 Fx: 303-291-0420	10. Field and Pool, or Explor CEDAR RIM	ratory
4. Location of Well (Report location clearly and in accorded At surface Lot 2 1982FNL 632FWL 40 At proposed prod. zone Lot 2 1980FNL 810FWL 40	0.178122 N Lat, 110.612683 W Lon	11. Sec., T., R., M., or Blk. a Sec 31 T3S R6W Me SME: FEE	
14. Distance in miles and direction from nearest town or post 12.0 MILES WEST OF DUCHESNE, UT	office*	12. County or Parish DUCHESNE	13. State UT
 Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 810' (BTM. HOLE) 	16. No. of Acres in Lease 630.08	17. Spacing Unit dedicated t	o this well
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 2916 	19. Proposed Depth 9473 MD 9468 TVD	20. BLM/BIA Bond No. on 1 WYB000040	ile
21. Elevations (Show whether DF, KB, RT, GL, etc. 6613 GL	22. Approximate date work will start 06/01/2012	23. Estimated duration 60 DAYS (D&C)	
	24. Attachments		
The following, completed in accordance with the requirements o 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest Syst SUPO shall be filed with the appropriate Forest Service Off	4. Bond to cover the operation Item 20 above). em Lands, the 5. Operator certification	this form: ns unless covered by an existing formation and/or plans as may be	,
25. Signature (Electronic Submission)	Name (Printed/Typed) VENESSA LANGMACHER Ph: 303-312	<u>?</u> -8172	Date 12/28/2011
Title SENIOR PERMIT ANALYST			
Approved by (Signature)	Name (Printed/Typed) Jerry Kenczka		APR 1 9 2012
Assistant Field Manager	Office VERNAL FIELD OFFICE	-	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #126851 verified by the BLM Well Information System For BILL BARRETT CORPORATION, sent to the Vernal Committed to AFMSS for processing by ROBIN R. HANSEN on 01/04/2012 (12RBH

NOTICE OF APPROVAL

CONDITIONS OF APPROVAL ATTACHED

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

12TJL0036AE

NOS 10/24/2011



UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT VERNAL FIELD OFFICE** 170 South 500 East

VERNAL, UT 84078

(435) 781-4400



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company:

Bill Barrett Corporation

Well No: API No:

5-31D-36 BTR 43-013-51146

Location:

Lot 2,Sec.31,T3S R6W

Lease No:

14-20-H62-6405

Agreement:

N/A

OFFICE NUMBER:

(435) 781-4400

OFFICE FAX NUMBER: (435) 781-3420

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.

NOTIFICATION REQUIREMENTS

Construction Activity (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	_	The Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist shall be notified at least 48 hours in advance of any construction activity. The Ute Tribal office is open Monday through Thursday.
Construction Completion (Notify Ute Tribe Energy & Minerals Dept. and BLM Environmental Scientist)	-	Upon completion of the pertinent APD/ROW construction, notify the Ute Tribe Energy & Minerals Dept. for a Tribal Technician to verify the Affidavit of Completion. Notify the BLM Environmental Scientist prior to moving on the drilling rig.
Spud Notice (Notify BLM Petroleum Engineer)	-	Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify BLM Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to running casing and cementing all casing strings to: blm.ut vn opreport@blm.gov
BOP & Related Equipment Tests (Notify BLM Supv. Petroleum Tech.)	-	Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify BLM Petroleum Engineer)	-	Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

Page 2 of 7 Well: 5-31D-36 BTR 4/17/2012

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

Site Specific COA's:

- Any deviation of submitted APD's, which includes BBCs surface use plan, and ROW
 applications the operator will notify the BLM in writing and will receive written authorization of
 any such change with appropriate authorization.
- The operator will implement "Safety and Emergency Plan." The operator's safety director will ensure its compliance.
- All operator employees and/or authorized personnel (sub-contractors) in the field will have approved applicable APD's, COAs, and ROW permits/authorizations on their person(s) during all phases of construction.
- All vehicular traffic, personnel movement, construction/restoration operations should be confined to the area examined and approved, and to the existing roadways and/or evaluated access routes.
- Production facilities will be painted Beetle Green to blend in with the surrounding habitat.
- Topsoil will be salvaged and used for reclamation purposes only. Topsoil should be low profile to minimize soil loss due to erosion forces like wind.
- Production equipment will be placed towards the front of the pad to maximize interim reclamation efforts.
- An 18" culvert shall be installed where the access road enters the pad area.
- Wood onsite shall be saved for reclamation purposes and for use by the private landowner.
- Site reclamation would be accomplished for portions of the well pad not needed for production, within 6 months of completion, weather permitting. This also includes any roads, and pipeline areas that have been disturbed as well. Roads and pipeline disturbances can undergo reclamation immediately after the pipeline is installed and after the roads are built. Please contact surface owner or the BLM for possible seed mixes to use in the project area. Nonnatives can be used; however lbs./ac must be kept low to minimize the chance of a monoculture.

Page 3 of 7 Well: 5-31D-36 BTR 4/17/2012

DOWNHOLE PROGRAM CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC DOWNHOLE COAs:

A CBL/GR shall be run from PBTD to the TOC on the production casing.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the
 daily drilling report. Components shall be operated and tested as required by Onshore Oil &
 Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be
 performed by a test pump with a chart recorder and NOT by the rig pumps. Test shall be
 reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- Cement baskets shall not be run on surface casing.
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water
 is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM
 Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.

Page 4 of 7 Well: 5-31D-36 BTR 4/17/2012

- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the <u>top of cement</u> and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- Please submit an electronic copy of all other logs run on this well in LAS format to BLM_UT_VN_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

Page 5 of 7 Well: 5-31D-36 BTR 4/17/2012

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- For information regarding production reporting, contact the Office of Natural Resources Revenue (ONRR) at www.ONRR.gov.
- In accordance with 43 CFR 3162.4-3, this well shall be reported on the "Monthly Report of Operations" (Oil and Gas Operations Report ((OGOR)) starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report shall be filed in duplicate, directly with the Minerals Management Service, P.O. Box 17110, Denver, Colorado 80217-0110, or call 1-800-525-7922 (303) 231-3650 for reporting information.
- Should the well be successfully completed for production, the BLM Vernal Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:
 - Operator name, address, and telephone number.
 - Well name and number.
 - Well location (¼¼, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - Unit agreement and/or participating area name and number, if applicable.
 - Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and

Page 6 of 7 Well: 5-31D-36 BTR 4/17/2012

Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field
 Office Petroleum Engineers will be provided with a date and time for the initial meter calibration
 and all future meter proving schedules. A copy of the meter calibration reports shall be
 submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API
 standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All
 measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted
 to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs
 first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be
 adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively
 sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover
 equipment shall be removed from a well to be placed in a suspended status without prior
 approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30
 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given
 before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent

Page 7 of 7 Well: 5-31D-36 BTR 4/17/2012

Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

Print Form

BLM - Vernal Field Office - Notification Form

	rator Bill Barrett Corporation			-
	nitted By <u>Venessa Langmach</u>		nber <u>303</u> -	312-8172
	Name/Number <u>5-31D-36 BTF</u> Qtr <u>swnw</u> Section <u>31</u>		s R	ange 6W
•	e Serial Number 1420H62640	-		
API	Number <u>4301351146</u>			
	d Notice – Spud is the initial pelow a casing string.	spudding o	f the we	ll, not drilling
	Date/Time <u>08/17/2012</u>	8:00	AM 📝	РМ
Casi time	ng – Please report time casins. Surface Casing Intermediate Casing Production Casing Liner Other	ng run start	ts, not ce	ementing
	Date/Time		AM 🗌	РМ
BOP	E Initial BOPE test at surface BOPE test at intermediate of 30 day BOPE test Other			RECEIVED AUG 1 5 2012 DIV. OF OIL. GAS & MINING
	Date/Time		AM 🗌	PM 🗌
Rem	arks			
	•			

Sundry Number: 29138 API Well Number: 43013511460000

	STATE OF UTAH			FORM 9
ı	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MIN	-		5.LEASE DESIGNATION AND SERIAL NUMBER: 1420H626405
SUNDR	Y NOTICES AND REPORTS	VELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	
	posals to drill new wells, significantly reenter plugged wells, or to drill horizon for such proposals.		7.UNIT or CA AGREEMENT NAME:	
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: 5-31D-36 BTR	
2. NAME OF OPERATOR: BILL BARRETT CORP				9. API NUMBER: 43013511460000
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202		ENUMBER: 2-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL				COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	IIP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W Mer	ridian: l	υ	STATE: UTAH
11. CHECI	CAPPROPRIATE BOXES TO INDICAT	TE NAT	TURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
_	ACIDIZE	☐ ALT	TER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	СНА	ANGE TUBING	CHANGE WELL NAME
SUBSEQUENT REPORT	CHANGE WELL STATUS	☐ con	MMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
Date of Work Completion:	DEEPEN	FRA	ACTURE TREAT	NEW CONSTRUCTION
	OPERATOR CHANGE	PLU	JG AND ABANDON	PLUG BACK
SPUD REPORT Date of Spud:	PRODUCTION START OR RESUME	REC	CLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
8/17/2012	REPERFORATE CURRENT FORMATION	SIDE	ETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VEN	IT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SITA	A STATUS EXTENSION	APD EXTENSION
	WILDCAT WELL DETERMINATION	ОТН	HER	OTHER:
This well was sp	COMPLETED OPERATIONS. Clearly show a pud on 8/17/2012 by Triple A	A Dril	lling at 8:00 am.	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY August 22, 2012
NAME (PLEASE PRINT) Venessa Langmacher	PHONE NUMB 303 312-8172		「ITLE Senior Permit Analyst	
SIGNATURE N/A	<u> </u>		DATE 8/22/2012	

Sundry Number: 29523 API Well Number: 43013511460000

	STATE OF UTAH		FORM 9	
ı	DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING	3	5.LEASE DESIGNATION AND SERIAL NUMBER: 1420H626405	
SUNDR	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
Do not use this form for pro current bottom-hole depth, I FOR PERMIT TO DRILL form	7.UNIT or CA AGREEMENT NAME:			
1. TYPE OF WELL Oil Well	8. WELL NAME and NUMBER: 5-31D-36 BTR			
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NUMBER: 43013511460000	
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300		ONE NUMBER: 312-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL			COUNTY: DUCHESNE	
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	IIP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W Meridian	n: U	STATE: UTAH	
11. CHECI	K APPROPRIATE BOXES TO INDICATE N	IATURE OF NOTICE, REPOR	T, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
_	ACIDIZE	ALTER CASING	CASING REPAIR	
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
SUBSEQUENT REPORT	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
Date of Work Completion:	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION	
	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
SPUD REPORT Date of Spud:	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
Date of opid.	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON	
_	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION	
8/31/2012	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
	COMPLETED OPERATIONS. Clearly show all per 2 monthly drilling activity report the control of the		epths, volumes, etc. Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY September 05, 2012	
Megan Finnegan	303 299-9949	Permit Analyst		
SIGNATURE N/A		DATE 9/4/2012		

Sundry Number: 29523 API Well Number: 43013511460000



)												
	D-36 BTF			2 10:00 -								
	1460000		State/Province JT		HESNE	Field Name Black Ta	_e ail Ridge	Well Status DRILLING		Total Depth (ftKB		imary Job Type rilling & Completion
Time Lo		I e e	I 0.1.		0-1					0		
Start Time 10:00	Dur (hr) 8.00	End Time 18:00	Code 1	RIGUP & TE	Category		Rigging o	lown from 19-9D-4	5 BTR. Movi	ng camps pir	e tubs etc.	
			<u> </u>	2 06:00 -		12 06:	00 0		0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ng campo pip	70 tubb 010.	
API/UWI	יום סניל		State/Province			TField Name		Well Status	T.	Total Depth (ftKB	\ Dri	imary Job Type
	11460000		JT		HESNE		ail Ridge	DRILLING		Total Deptil (IIIVD		rilling & Completion
Time Lo			•									
Start Time 06:00		End Time 18:00	Code 1	RIGUP & TE	Category ARDOWN			et mud tanks, matti pecause DOT did n			Entire rig se	et in. Will move derrick
	0-36 BTF			2 06:00 -	8/26/201							
API/UWI 4201351	11460000		State/Province		HESNE	Field Name	e ail Ridge	Well Status DRILLING		Total Depth (ftKB		imary Job Type rilling & Completion
Time Lo			<i>J</i> 1	IDOC	HESINE	DIACK TO	all Kluge	DRILLING			7,307.0	miling & Completion
Start Time	Dur (hr)	End Time	Code		Category					Com		
06:00		14:00	1	RIGUP & TE	ARDOWN		pad eye	and 4 cross braces	i.	•		insp. Found cracks in
14:00	16.00	06:00	8	REPAIR RIG			Set derrie for daylig		all out inspe	ctors and we	ders to repa	ir. Repair derrick. Wait
	D-36 BTF			2 06:00 -								
	1460000		State/Province JT		HESNE	Field Name Black Ta	e ail Ridge	Well Status DRILLING		Total Depth (ftKB		imary Job Type rilling & Completion
Time Lo	Dur (hr)	End Time	Code		Cotogoni					Com		
06:00		22:00	1	RIGUP & TE	Category ARDOWN		Set derric	ck on floor. Continu	ue rig up.	Com		
22:00	6.00	04:00	1	RIGUP & TE/	ARDOWN			onductor tube and r	<u> </u>	onductor pip	e and flowlin	ie
04:00	2.00	06:00	6	TRIPS			Pickup U	Iterra U716M and 8	B" sperry mo	tor.		
5-31F)-36 BTF	8/2	7/2012	2 06:00 -	8/28/201	12 06:0	00		· ·			
API/UWI	00 011		State/Province			Field Name		Well Status	T	Total Depth (ftKB) Pri	imary Job Type
4301351 Time Lo	11460000	l	JT	DUC	HESNE	Black Ta	ail Ridge	DRILLING			7,367.0 Di	rilling & Completion
Start Time	Dur (hr)	End Time	Code		Category					Com		
06:00	4.00	10:00	2	DRILL ACTU	AL		Spud we	l @ 0600hrs. Drill t	to 126'. P/U	and orient dir	equipment.	Drill to 201'.
10:00	2.50	12:30	21	Work stuck p	pe.			ple pump and work				uck pipe. Attempt to on. Pump sweeps and
12:30	0.50	13:00	7	LUBRICATE	RIG		Rig servi	ce				
13:00	17.00	06:00	2	DRILL ACTU	AL		Drlg 201- vis.	998' 797' in 17 hrs	47 fph. Sur	/ey @ 870' 1	.42* inc. 58.5	52 azi. MW9.05#/gal 42
	0-36 BTF	8/2	8/2012	2 06:00 -	8/29/201							
	11460000		State/Province		HESNE	Field Name Black Ta	e ail Ridge	Well Status DRILLING		Total Depth (ftKB		imary Job Type rilling & Completion
Time Lo	Dur (hr)	End Time	Code		Category					Com		
06:00		15:30	2	DRILL ACTU			Drlg 998- vis.	1759'. 761' in 9.5 h	nrs 80 fph. s		11.9* inc, 47	7.76* azi MW 9#/gal 43
15:30		16:00	7	LUBRICATE			Rig servi					
16:00	14.00	06:00	2	DRILL ACTU	AL		Drlg 1759 8.9#/gal	9-2521' 762' in 14 h 40 vis.	nrs 54.4 fph,	survey @ 23	89' 1.1* inc 1	72.72* azi. MW
	0-36 BTF			2 06:00 -	8/30/201							
API/UWI	11460000		State/Province		, HESNE	Field Name	e ail Ridge	Well Status DRILLING		Total Depth (ftKB		imary Job Type rilling & Completion
Time Lo			J 1	IDOC	IIESINE	DIACK T	an Nuge	PRILLING	l		1,301.0 DI	ming a completion
Start Time	Dur (hr)	End Time	Code		Category					Com		
06:00		09:00	2	DRILL ACTU			8.9#/gal			·	342, .83* inc	100.01 azi MW
09:00	1.00	10:00	5	COND MUD	& CIRC		Pump sv	veep at TD and circ	c. out. Pump	dryjob		
											,	

www.peloton.com Page 1/2 Report Printed: 9/4/2012

Sundry Number: 29523 API Well Number: 43013511460000



Time Lo	g				
Start Time	Dur (hr)	End Time	Code	Category	Com
10:00	3.00	13:00	6	TRIPS	TOH for logs. L/D 8" BHA
13:00	3.00	16:00	11	WIRELINE LOGS	Rig up HES and run Quad-Combo to 2706'. Rig down HES
16:00	13.00	05:00	12	RUN CASING & CEMENT	Rig up csg crew and run 62 jts 9 5/8" 36# J55 casing wth float equipment. Land @ 2706'. Fill csg as needed while running. Circulate while riiging HES up to cmt. Cmt as follows; Pressure test to 3000#, pump 20 bbl fresh water, 40 bbls superflush, 20 bbl water, 248 bbls (440 sks) lead cmt @ 11#/gal, 57 bbls (240 sks) tail cmt @ 14.8 #/gal, Shut down, drop plug and displace with 206 bbls mud. 26 bbls cmt to sfc. Reciprocate pipe till dropping plug. Became sticky. Final pumping pressure 480#. Stop displacement at 206 bbls. Did not bump plug. Cmt fell 40' in 20 min. Run 140' 1" and do 50 sk top job. Annulus full and holding.
05:00	1.00	06:00	13	WAIT ON CEMENT	Wait on cmt.

www.peloton.com Page 2/2 Report Printed: 9/4/2012

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES **DIVISION OF OIL, GAS AND MINING**

ENTITY ACTION FORM							
Operator:	Bill Barrett Corporation		Operator Account Number: N 2165				
Address:	1099 18th Street, Suite 2300)					
	city Denver						
	state CO	zip 80202	Phone Number: (303) 312-8	172			

18/-11 4

API Number	Well	QQ	Sec	Twp	Rng	C	ounty	
43013:51146	5-31D-36 BTR	SWNW	31	31 3S		6W Duchesne		
Action Code	Current Entity Number	New Entity Number	S	Spud Date		Entity Assignment Effective Date		
Α	new	18691	8	/17/201	2	81	28	12013
Comments: Spudd	ing Operation was co	nducted by Triple A D	Orilling @ 8:0	00 am.				

Well 2

API Number	Well I	QQ	Sec	Twp	Rng County			
Action Code	Current Entity Number	New Entity Number	Spud Date			Entity Assignment Effective Date		
comments:	<u> </u>							

Well 3

API Number	Well	QQ	Sec	Twp	Rng	County		
Action Code	Current Entity Number				te	Entity Assignment Effective Date		
omments:	<u> </u>						- 18-1	

ACTION CODES:

- A Establish new entity for new well (single well only)
- **B** Add new well to existing entity (group or unit well)
- C Re-assign well from one existing entity to another existing entity
- D Re-assign well from one existing entity to prevent the prevent to the prevent
- E Other (Explain in 'comments' section)

AUG 2 2 2012

Venessa Langmacher	
Name (Please Print)	
Venessa Langmacher	
Signature	
Sr Permit Analyst	8/22/2012
Title	Date

BLM - Vernal Field Office - Notification Form

Operator <u>Bill Barrett Corp.</u> Rig Name/# <u>Patterson Rig 506</u>
Submitted By Lawrence Lorenzen Phone Number 435-828-6095
Well Name/Number <u>5-31D-36 BTR</u>
Qtr/Qtr <u>SW/SE</u> Section <u>31</u> Township <u>3S</u> Range 6W
Lease Serial Number <u>1420H626405</u>
API Number 43-013-51146
Spud Notice – Spud is the initial spudding of the well, not drilling out below a casing string.
Date/Time AM D PM D
Casing – Please report time casing run starts, not cementing times.
 Surface Casing Intermediate Casing Production Casing Liner Other
Date/Time <u>8/29/12</u> <u>6:00</u> AM PM
BOPE Initial BOPE test at surface casing point BOPE test at intermediate casing point AUG 2 8 2012 30 day BOPE test Other RECEIVED AUG 2 8 2012 DIV. OF OIL, GAS & MININ
Date/Time <u>8/30/12</u> <u>7:00</u> AM ☐ PM ⊠

Remarks <u>Times are estimates only.</u>

BLM - Vernal Field Office - Notification Form

Operator <u>Bill Barrett Corp.</u> Rig Name/# <u>Patterson Rig 506</u>
Submitted By Pat Clark Phone Number 435-828-6095
Well Name/Number <u>5-31D-36 BTR</u>
Qtr/Qtr SW/SE Section 31 Township 3S Range 6W
Lease Serial Number 1420H626405
API Number 43-013-51146
<u>Spud Notice</u> – Spud is the initial spudding of the well, not drilling
out below a casing string.
Date/Time AM PM
<u>Casing</u> – Please report time casing run starts, not cementing
times.
Surface Casing
Intermediate Casing
Production Casing
Liner
Other
Date/Time <u>9/06/12</u> <u>23:00</u> AM PM 🔀
RECEIVED
DUPE
DODE test at intermediate easing point
BOPE test at intermediate casing point DIV. OF OIL, GAS & MINING 30 day BOPE test
Other
Date/Time AM PM

Remarks <u>Times are estimates only.</u>

Sundry Number: 30370 API Well Number: 43013511460000 FEDERAL APPROVAL OF THIS ACTION IS NECESSARY

	STATE OF UTAH				FORM 9
[DEPARTMENT OF NATURAL RESOUR DIVISION OF OIL, GAS, AND MI		3	5.LEASE I 1420H6	DESIGNATION AND SERIAL NUMBER: 26405
SUNDR	Y NOTICES AND REPORTS	ON	WELLS	6. IF INDIA	AN, ALLOTTEE OR TRIBE NAME:
	posals to drill new wells, significantly reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or	CA AGREEMENT NAME:	
1. TYPE OF WELL Oil Well			8. WELL N 5-31D-3	NAME and NUMBER: 86 BTR	
2. NAME OF OPERATOR: BILL BARRETT CORP			9. API NU I 430135	MBER: 11460000	
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202		NE NUMBER: 312-8164 Ext	9. FIELD a	and POOL or WILDCAT: RIM
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL				COUNTY: DUCHES	
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W Me	ridian	ı: U	STATE: UTAH	
11. CHECI	K APPROPRIATE BOXES TO INDICA	TE N	ATURE OF NOTICE, REPOR	T, OR 01	THER DATA
TYPE OF SUBMISSION			TYPE OF ACTION		
-	ACIDIZE		ALTER CASING		CASING REPAIR
✓ NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS		CHANGE TUBING		CHANGE WELL NAME
10/2/2012	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS		CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN		FRACTURE TREAT		NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE		PLUG AND ABANDON		PLUG BACK
	PRODUCTION START OR RESUME		RECLAMATION OF WELL SITE		RECOMPLETE DIFFERENT FORMATION
SPUD REPORT					
Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL		TEMPORARY ABANDON
	L TUBING REPAIR	~ \	/ENT OR FLARE		WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	∐ \$	SI TA STATUS EXTENSION		APD EXTENSION
	WILDCAT WELL DETERMINATION		OTHER	OTHER	R:
l .	COMPLETED OPERATIONS. Clearly show additional flaring due to pipe attached for details.				Approved by the Utah Division of II, Gas and Mining October 04, 2012
NAME (PLEASE PRINT)	PHONE NUMB	BER	TITLE Sonior Permit Applyet		
Venessa Langmacher	303 312-8172		Senior Permit Analyst		
SIGNATURE N/A			DATE 10/2/2012		

On September 27th, 2012 the BTR 5-31D-36 began initial flowback from the Wasatch Green River. Kinder Morgan was to have pipeline to location before completion. Kinder Morgan has been delayed. Pipe is run to location and in the process of being pressure tested but will not be ready for sales 10/2/2012. BBC is request an additional 30 day no more than 50 MMCF gas flaring approval before the 3000 MCF is reached.

The first three days of production have been:

9-27-12	16 BO, 0 MCF, 399 BW
9-28-12	250 BO, 396 MCF, 757 BW
9-29-12	370 BO, 659 MCF, 688 BW
9-30-12	382 BO, 814 MCF, 571 BW
10-1-12	383 BO, 887 MCF, 530 BW

Since initial completion the well has produced 2756 MCF in 5 days.

The well is in early flowback and has recovered just over 10% of load water. It is critical to continue flow testing the well to prevent any formation damage and determine oil productivity. The well has recovered 2,945 bbls of 21,143 bbls of fracture fluid. Shutting in the well so soon after the initial completion could cause a reduction in the long term ultimate recovery by dehydration of the gelled hydraulic fracture fluid still in the formation and crushing of the proppant in the hydraulic fractures. Both could result in a reduction in productivity.

Kinder Morgan should have the sales pipeline tested and the BTR 5-31D-36 to sales before 10/5/2012.

					_
	STATE OF UTAH			FORM	9
ι	DEPARTMENT OF NATURAL RESOUR DIVISION OF OIL, GAS, AND MI	-	3	5.LEASE DESIGNATION AND SERIAL NUMBER 1420H626405	R:
SUNDR	Y NOTICES AND REPORTS	ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	_
Do not use this form for pro current bottom-hole depth, I FOR PERMIT TO DRILL form	posals to drill new wells, significantly reenter plugged wells, or to drill horiz n for such proposals.	en existing wells below aterals. Use APPLICATION	7.UNIT or CA AGREEMENT NAME:	_	
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: 5-31D-36 BTR	_	
2. NAME OF OPERATOR: BILL BARRETT CORP				9. API NUMBER: 43013511460000	
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	, Denver, CO, 80202		NE NUMBER: 312-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL				COUNTY: DUCHESNE	
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	ilP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W Mo	eridian	: U	STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICA	ATE N	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUBMISSION			TYPE OF ACTION		
	ACIDIZE		ALTER CASING	CASING REPAIR	
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS		CHANGE TUBING	CHANGE WELL NAME	
	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	☐ F	RACTURE TREAT	NEW CONSTRUCTION	
	OPERATOR CHANGE	F	PLUG AND ABANDON	PLUG BACK	
SPUD REPORT	PRODUCTION START OR RESUME	☐ F	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON	
	TUBING REPAIR		/ENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF		SI TA STATUS EXTENSION	APD EXTENSION	
9/30/2012	WILDCAT WELL DETERMINATION		OTHER	OTHER:	
42 DESCRIPE PROPOSED OR	COMPLETED OPERATIONS. Clearly show				_
	012 monthly drilling activity			Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY October 05, 2012	
NAME (PLEASE PRINT) Megan Finnegan	PHONE NUM 303 299-9949	BER	TITLE Permit Analyst		
SIGNATURE N/A			DATE 10/2/2012		



API/UWI			State/Province	06:00 - 9/2/201 ce County	Field Name		Well Status	Total Depth (ftKB	
	11460000	ι	UT	DUCHESNE	Black Ta	il Ridge	COMPLETION	. `	8,860.0 Drilling & Completion
ime Lo	•	End Time	Code	Catagon				Com	
6:00		15:00	2	DRILL ACTUAL		Drlg 4322	2-4967'. 645' in 9 hrs, 71		897 3.63* inc 107.47* azi MW
						8.7#/gal 3			
5:00		15:30	7	LUBRICATE RIG		U	ce Function BOP, BOP		
5:30	14.50	06:00	2	DRILL ACTUAL			7-5718'. 761' in 14.5 hrs gal 38 vis.	52.5 fph. Survey @	5658'. 1.34* inc 240.68 azi.
	D-36 BTF			06:00 - 9/3/201			lw no.	TT	
PI/UWI 301351	11460000	1 -	State/Provinc UT	County DUCHESNE	Field Name Black Ta		Well Status COMPLETION	Total Depth (ftKB	Primary Job Type 8,860.0 Drilling & Completion
ime Lo	og			•	•		•	,	
art Time		End Time		Category		Dala: E740) COOC! Wale Odle man	Com	si da 120 asi yan 57 fab
6:00 6:00	1	16:00	2	DRILL ACTUAL LUBRICATE RIG			·		si, dp 130 psi, rop 57 fph.
5:00	1	16:30 03:00	7	DRILL ACTUAL			ce. BOP drill, Function		si, dp 130 psi, rop 55 fph. Lost 60
).30	10.50	03.00	2	DRILL ACTUAL		bbls, hole	got tight; got loose, no	diff press.	si, up 130 psi, 10p 33 ipii. Lost 60
3:00	2.50	05:30	5	COND MUD & CIRC			eep, dry job f/trip.	· · · · · · · · · · · · · · · · · · ·	
5:30	0.50	06:00	6	TRIPS		TOH.			
-31[D-36 BTF	₹ 9/3	/2012	06:00 - 9/4/201	2 06:00				
PI/UWI	11100000		State/Provinc	1 ,	Field Name		Well Status	Total Depth (ftKB	
ime Lo	11460000		UT	DUCHESNE	Black Ta	iii Riage	COMPLETION		8,860.0 Drilling & Completion
art Time		End Time	Code	Category				Com	
6:00		09:00	6	TRIPS		Finish TC blind ram		s bad(shaft probably	y broken from shock load). Function
9:00	1.00	10:00	6	TRIPS		P/u new r	nm, bit.		
0:00	4.00	14:00	6	TRIPS			pipe @ shoe.		
4:00	1.50	15:30	5	COND MUD & CIRC			ng fluid, pump lcm swee	ps.	
5:30	1.50	17:00	2	DRILL ACTUAL			' - 6258'. Wellbore seep		
7:00	0.50	17:30	7	LUBRICATE RIG		Rig servi	·		
7:30	12.50	06:00	2	DRILL ACTUAL		Drill 6858	' - 7367'. Wob 20k, rpm	46/73, spp 1650 ps	ii, dp 125 psi, rop 41 fph.
5-31[D-36 BTF	₹ 9/4	/2012	06:00 - 9/5/201	2 06:00				
PI/UWI			State/Province	1 ,	Field Name		Well Status	Total Depth (ftKB	
	11460000		UT	DUCHESNE	Black Ta	il Ridge	COMPLETION		8,860.0 Drilling & Completion
	bg	End Time	Code	Category				Com	
	Dur (hr)			DRILL ACTUAL		Drill 7367	'' - 7875'. Wob 20k, rpm		i, dp 130 psi, rop 53 fph.
art Time		15:30	2	DIVILL ACTUAL					
art Time 6:00	9.50		7	LUBRICATE RIG		Rig Servi	ce.		., ap 100 poi, 10p 00 ip.ii
art Time 6:00 5:30	9.50 0.50	15:30 16:00				Rig Servi		48/74, spp 1850 psi	i, dp 130 psi, rop 53 fph.
tart Time 6:00 5:30 6:00	9.50 0.50 14.00	15:30 16:00 06:00	7 2	LUBRICATE RIG DRILL ACTUAL		Rig Servi		48/74, spp 1850 psi	<u> </u>
6:00 5:30 6:00 5-31	9.50 0.50 14.00 D-36 BTF	15:30 16:00 06:00 R 9/5	7 2	DRILL ACTUAL 06:00 - 9/6/201	2 06:00 Field Name	Rig Servi Drill 7875	' - 8509. Wob 20k, rpm	48/74, spp 1850 psi	i, dp 130 psi, rop 53 fph. Primary Job Type
6:00 5:30 6:00 5-31 PI/UWI 30135	9.50 0.50 14.00 D-36 BTF	15:30 16:00 06:00 R 9/5	7 2 /2012	DRILL ACTUAL 06:00 - 9/6/201	2 06:00	Rig Servi Drill 7875	' - 8509. Wob 20k, rpm		i, dp 130 psi, rop 53 fph.
tart Time 6:00 5:30 6:00 5-31[PI/UWI 301352 ime Lo	9.50 0.50 14.00 D-36 BTF	15:30 16:00 06:00 R 9/5	7 2 /2012 State/Province	DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE	2 06:00 Field Name	Rig Servi Drill 7875	' - 8509. Wob 20k, rpm	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
tart Time 6:00 5:30 6:00 5-31[PI/UWI 301352 ime Lotart Time	9.50 0.50 14.00 D-36 BTF 11460000 og Dur (hr)	15:30 16:00 06:00 8 9/5	7 2 /2012 State/Province UT Code	DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 il Ridge	Well Status COMPLETION	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
tart Time 6:00 5:30 6:00 5-31 5-31 5-31 5-31 5-31 6:00	9.50 0.50 14.00 D-36 BTF 11460000 og Dur (hr) 8.00	15:30 16:00 06:00 9/5 End Time 14:00	7 2 // 2012 State/Province UT Code 2	DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 il Ridge	Well Status COMPLETION '- 8860'. TD well @ 14:	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
tart Time 6:00 5:30 6:00 6:00 5-31[PI/UWI 301352 ime Lotart Time 6:00 4:00	9.50 0.50 14.00 D-36 BTF 11460000 og 1 Dur (hr) 8.00 2.00	15:30 16:00 06:00 R 9/5 End Time 14:00 16:00	7 2 2 //2012 State/Province UT Code 2 5	LUBRICATE RIG DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST	Well Status COMPLETION	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
tart Time 6:00 5:30 6:00 5-31[FI/UWI 30135 ime Lot tart Time 6:00 4:00 6:00	9.50 0.50 14.00 D-36 BTF 11460000 og 8	15:30 16:00 06:00 R 9/5 S L End Time 14:00 16:00 17:30	7 2 2 //2012 UT Code 2 5 6	LUBRICATE RIG DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST	Well Status COMPLETION ' - 8860'. TD well @ 14: st. Hole in good shape.	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
6:00 6:00 6:00 6:00 6:00 6:00 6:00 6:00 6:00 7:30	9.50 0.50 14.00 D-36 BTF 11460000 og 8 Dur (hr) 8.00 2.00 1.50 2.00	15:30 16:00 06:00 8 9/5 \$\begin{align*} \text{End Time} \\ 14:00 \\ 16:00 \\ 17:30 \\ 19:30 \end{align*}	7 2 2 /2012 State/Province UT	Category DRILL ACTUAL COND MUD & CIRC	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC	Well Status COMPLETION '- 8860'. TD well @ 14: s. Hole in good shape. I	Total Depth (ftKB	i, dp 130 psi, rop 53 fph. Primary Job Type
art Time 6:00 5:30 6:00 6:00 6-31 E 7////////////////////////////////////	9.50 0.50 14.00 D-36 BTF 11460000 9 0 Dur (hr) 8.00 2.00 1.50 2.00 5.00	15:30 16:00 06:00 8 9/5 \$\begin{align*} \textbf{End Time} \\ 14:00 \\ 16:00 \\ 17:30 \\ 19:30 \\ 00:30 \end{align*}	7 2 // 2012 State/Province UT Code 2 5 6 5 6 6	LUBRICATE RIG DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 Ill Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo	Well Status COMPLETION '- 8860'. TD well @ 14: Is. Hole in good shape. In the status of the status	Com 00 @ 8860'. Bop Drill.	Primary Job Type 8,860.0 Drilling & Completion
tart Time 6:00 5:30 6:00 5-31 [Fi/UWI 301357 ime Lot tart Time 6:00 4:00 6:00 7:30 9:30	9.50 0.50 14.00 D-36 BTF 11460000 09 0	15:30 16:00 06:00 8 9/5 , 8 9/5 , 9 1 1 1 1 1 1 1 1 1 1	7 2 /2012 State/Province UT Code 2 5 6 5 6 111	Category DRILL ACTUAL County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS WIRELINE LOGS	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 Ill Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo	Well Status COMPLETION '- 8860'. TD well @ 14: s. Hole in good shape. I	Com 00 @ 8860'. Bop Drill.	Primary Job Type 8,860.0 Drilling & Completion
tart Time 6:00 5:30 6:00 5-31[FI/UWI 30135/ ime Lotart Time 6:00 4:00 6:00 7:30 9:30 0:30 5-31[9.50 0.50 14.00 D-36 BTF 11460000 9 0 Dur (hr) 8.00 2.00 1.50 2.00 5.00	15:30 16:00 06:00 8 9/5 , End Time 14:00 16:00 17:30 19:30 00:30 06:00 8 9/6 ,	7 2 /2012 State/Province UT Code 2 5 6 5 6 111	LUBRICATE RIG DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS WIRELINE LOGS 06:00 - 9/7/201	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo HSM. R/L	Well Status COMPLETION '- 8860'. TD well @ 14: Is. Hole in good shape. In the status of the status	Com 00 @ 8860'. Bop Drill.	Primary Job Type 8,860.0 Drilling & Completion Drilling & Completion
5:30 6:00 5:31 6:00 5:31 6:00 5-31 6:00 6:00 6:00 6:00 7:30 9:30 0:30 5-31 6:00 7:30 9:30 6:00 6:00	9.50 0.50 14.00 D-36 BTF 11460000 99 0 Dur (hr) 8.00 2.00 1.50 2.00 5.50 D-36 BTF	15:30 16:00 06:00 R 9/5, End Time 14:00 16:00 17:30 19:30 00:30 06:00 R 9/6,	7 2 2 /2012 State/Province UT	LUBRICATE RIG DRILL ACTUAL 06:00 - 9/6/201 County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS WIRELINE LOGS 06:00 - 9/7/201	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo HSM. R/L	Well Status COMPLETION ' - 8860'. TD well @ 14: is. Hole in good shape. I OH. gs. L/D Dir tools. J HES. Run quad combo	Com 00 @ 8860'. Bop Drill. D, gamma to surface	Primary Job Type 8,860.0 Drilling & Completion Drilling & Completion
API/UWI 430135 ² Fime Lo Start Time 06:00 4:00 17:30 19:30 00:30 5-31[API/UWI 430135 ² Fime Lo	9.50 0.50 14.00 D-36 BTF 11460000 09 0 Dur (hr) 8.00 2.00 1.50 2.00 5.50 D-36 BTF 11460000 09	15:30 16:00 06:00 R 9/5, End Time 14:00 16:00 17:30 19:30 00:30 06:00 R 9/6,	7 2 /2012 State/Province UT	Category DRILL ACTUAL County DUCHESNE Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS WIRELINE LOGS O6:00 - 9/7/201 COUNTY DUCHESNE	2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo HSM. R/L	Well Status COMPLETION ' - 8860'. TD well @ 14: S. Hole in good shape. In the shape of the sha	Com 00 @ 8860'. Bop Drill. Total Depth (ftKB	Primary Job Type 8,860.0 Prilling & Completion Primary Job Type Primary Job Type Primary Job Type
Start Time 06:00 5:30 6:00 5:31 6:00 5:31 6:00 6:00 6:00 6:00 6:00 7:30 9:30 00:30 5-31 PI/UWI 430135-4 PI/UWI 430135-4 PI/UWI 430135-4	9.50 0.50 14.00 D-36 BTF 11460000 9 0 Dur (hr) 8.00 2.00 1.50 5.00 5.50 D-36 BTF	15:30 16:00 06:00 R 9/5, End Time 14:00 16:00 17:30 19:30 00:30 06:00 R 9/6,	7 2 /2012 State/Province UT	Category DRILL ACTUAL COND MUD & CIRC TRIPS COND MUD & CIRC TRIPS WIRELINE LOGS O6:00 - 9/7/201 CE COUNTY COUNTY DUCHESNE	2 06:00 Field Name Black Ta 2 06:00 Field Name Black Ta	Rig Servi Drill 7875 iil Ridge Drill 8509 C&C f/ST ST 22 std C&C f/TC TOH f/Lo HSM. R/L	Well Status COMPLETION 1' - 8860'. TD well @ 14: 15. 15. 16. 17. 18. Hole in good shape. 16. 19. 19. 19. 19. 19. 19. 19. 19. 19. 19	Com 00 @ 8860'. Bop Drill. D, gamma to surface	Primary Job Type 8,860.0 Prilling & Completion Primary Job Type Primary Job Type Primary Job Type



77:00 11:30 13:30 22:30 5-31D-3 PI/UWI 4301351146 Fime Log	2.00 9.00 6.50 86 BTR	End Time 11:30 13:30 22:30	Code 6 5	Category TRIPS				Com	
77:00 1:30 3:30 22:30 5-31D-3 PIVUWI 4301351146 Fime Log	4.50 2.00 9.00 6.50 86 BTR	11:30 13:30 22:30	6						
3:30 2:30 5-31 D-3 PI/UWI 301351146 Time Log	9.00 6.50 86 BTR	22:30	5			Tih w/tric	one. Fill pipe & circ @	shoe, 6000'.	
22:30 5-31 D-3 API/UWI 1301351146 Fime Log Start Time	6.50 B6 BTR			COND MUD & CIRC		C&C to L	DDP. HSM, R/U Frank	's Westates to LDDP.	
5-31D-3 PI/UWI 1301351146 Fime Log	6 BTR	05.00	6	TRIPS		LDDP & I	BHA (tight pipe). Pull v	vear bushing.	
1301351146 Fime Log Start Time		05:00	12	RUN CASING & CEMENT	Г	R/U Frank's & run 5 1/2", 17#, P-110, Ltc csg.			
Start Time [60000	9/7	/2012	06:00 - 9/8/2012	06:00				
Time Log Start Time	30000		State/Provinc	County DUCHESNE	Field Name Black Ta		Well Status COMPLETION	Total Depth (ftKB) Primary Job Type 8,860.0 Drilling & Completion	
Start Time [<u> </u>	20020.12	- Jack Fa		22	3,555.5 Z.m.n.g & 55mp.58.5.	
06:00	Dur (hr)	End Time		Category				Com	
		09:00	12	RUN CASING & CEMENT	Γ	collar, 13 (207 total	jts csg, mj @ 8184', 1 l). P/U jt # 208, tag bott	0, LT&C Csg as follows: Float Shoe, 2 jts csg, float 7 jts csg, mj @ 7439', 32 jts csg, mj @ 6095', 143 jts cs iom @ 8860'. L/D jt # 208.	
09:00		12:00	5	COND MUD & CIRC			nt. Full returns.		
12:00	2.50	14:30	12	RUN CASING & CEMENT	Γ	10 bbl wa (625 sks) returns, 1	ater spacer, Pump 309 13.5 # tail cmt. Displa	5K. Pump 10 bbl water spacer, 40 bbls superflush 101, bbls (745 sks)11# tuned light lead cmt. Pump 158 bbls ce with 203 bbls water with Cla-web and aldacide g. Ful Final lift pressure 1700 #, bump plug 500 over. Check SM RD HES.	
14:30	3.50	18:00	21	NDBOP, Set Slips, Clean Release Rig	Pits,	cut, insta		on set slips w/ 165 k(25 k over string wt.). Made rought ts, release rig @ 18:00.	
5-31D-3	6 BTR	9/1	1/2012	2 00:00 - 9/12/20	12 06:0	00			
API/UWI	20000		State/Provinc	1 1	Field Name		Well Status	Total Depth (ftKB) Primary Job Type	
4301351146 Time Log	50000		UT	DUCHESNE	Black Ta	iii Riage	COMPLETION	8,860.0 Drilling & Completion	
	Dur (hr)	End Time	Code	Category				Com	
00:00		00:00	GOP	General Operations		HSM ANI		CELLAR. CAMERON LATE. FORGOT ABOUT JOB. . ND NIGHT CAP. NU 7" 5K X 11" 5K B-SECTION.	
5-31D-3	6 BTR	9/1	2/2012	2 06:00 - 9/13/20					
^{API/UWI} 4301351146 Time Log	00000		State/Provinc UT	County DUCHESNE	Field Name Black Ta		Well Status COMPLETION	Total Depth (ftKB) Primary Job Type 8,860.0 Drilling & Completion	
	Dur (hr)	End Time	Code	Category				Com	
06:00		07:30	GOP	General Operations			Secured.		
07:30	1.00	08:30	SRIG	Rig Up/Down		MIRU SLB W/L Crew And Equipment. Hold Safety Meeting. Rig Up Gauge Ring And Logging Tool.			
08:30	6.00	14:30	LOGG	Logging		P/U Junk Basket/Gauge Ring. RIH, Tagged Up At 8,743', Drilling Report Shows FC At 8,760', 17' Of Fill. POOH, P/U CBL Tool, Rih To PBTD, 8,743', Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-06-2012. Run Repeat Section From 8,743 - 8,400', Log Up Hole. Showed Good Bond From TD To 5280', 5280' - 4230' Ok With Ratty Spotsr, 4230-3700' Good To Ok, 3700-2100' Ok To Ratty, 2100-185' Ratty. TOC 185'. Ran With Pressure. Found Short Joints At 8,177 - 8,199, 7,432 - 7,453 And 6,088 - 6,110'. Pooh, RD Equipment, MOL.			
14:30	15.50	06:00	LOCL	Lock Wellhead & Secure		WSI And	Secured		
5-31D-3	6 BTR	9/1	3/2012	2 06:00 - 9/14/20	12 06:0	00			
API/UWI 4301351146	60000		State/Provinc	County DUCHESNE	Field Name Black Ta		Well Status COMPLETION	Total Depth (ftKB) Primary Job Type 8,860.0 Drilling & Completion	
Time Log				1	,				
Start Time 06:00	Dur (hr) 24.00	End Time 06:00	GOP	General Operations			on Crew Working On Fa ting Frac Line. n Tops.	Com acilities.	
5-31D-3	6 BTR	9/1	4/2012	2 06:00 - 9/15/20	12 06:0	00			
API/UWI			State/Province	1 1	Field Name		Well Status	Total Depth (ftKB) Primary Job Type	
4301351146	50000	Į	UT	DUCHESNE	Black Ta	ılı Ridge	COMPLETION	8,860.0 Drilling & Completion	
Time Log Start Time	Dur (hr)	End Time	Code	Category				Com	
06:00	24.00		GOP	General Operations		Finish Se	on Crew Working On Fa etting Frac Line ng Frac Line		



ว-31L	-36 BTF	R 9/1	5/2012	2 06:00 - 9/16/20	12 06:00			
PI/UWI		[5	State/Provinc	e County	Field Name	Well Status	Total Depth (ftKB)	Primary Job Type
01351 me Lo	1460000	l	UT	DUCHESNE	Black Tail Ridge	COMPLETION		8,860.0 Drilling & Completion
rt Time	Dur (hr)	End Time	Code	Category			Com	
:00	24.00	06:00	GOP	General Operations		ion Crew Working On Fa rac Line With Produced		
	-36 BTF			2 06:00 - 9/17/20				
/UWI 01351	1460000		State/Provinc UT	e County DUCHESNE	Field Name Black Tail Ridge	Well Status COMPLETION	Total Depth (ftKB)	Primary Job Type 8,860.0 Drilling & Completion
me Lo			<u>. </u>		Diagn Tall Thage	33 22		s,coord 2g a compression
art Time	Dur (hr)	End Time		Category			Com	
6:00	24.00	06:00	GOP	General Operations		illing Frac Line. 4 Additional KCL Tanks	09/18/2012 And Fill.	
-31 C	-36 BTF		1/2012 State/Province	2 06:00 - 9/22/20	12 06:00 Field Name	Well Status	Total Donth (HVP)	Primary Job Type
	1460000		UT	e County DUCHESNE	Black Tail Ridge	COMPLETION	Total Depth (ftKB)	8,860.0 Drilling & Completion
me Lo	g			•		•	•	
art Time	Dur (hr)	End Time	GOP	Category	Day 4	ion Orașu Warilin - O	Com	
6:00	24.00	06:00	GOP	General Operations	Set Fra Set Fra Finish F	ion Crew Working On Fa c Mandrel, Test c Tree, Test Casing kigging Up FlowBack, Te ot Manifold And Movers		
	-36 BTF	9/2	2/2012	2 06:00 - 9/23/20				
PI/UWI 301351	1460000		State/Provinc	e County DUCHESNE	Field Name Black Tail Ridge	Well Status COMPLETION	Total Depth (ftKB)	Primary Job Type 8,860.0 Drilling & Completion
me Lo		,	01	DOCHLONE	Diack Tall Nidge	COMPLETION		0,000.0 Drilling & Completion
art Time	Dur (hr)	End Time		Category			Com	
5:00	24.00	06:00	GOP	General Operations		CL Tanks In Frac Line. cation For Frac.		
045	AC DEF	0/0						
)-36 BTF			2 06:00 - 9/24/20		I Woll Status	Total Donth (ftKP)	I Brimany, Joh Typo
PI/UWI	1460000	[5	3/2012 State/Provinc UT		Pield Name Black Tail Ridge	Well Status COMPLETION	Total Depth (ftKB)	Primary Job Type 8,860.0 Drilling & Completion
I/UWI 801351 me Lo	1460000 g		State/Provinc UT	e County DUCHESNE	Field Name			
I/UWI 601351 me Lo art Time	1460000 g Dur (hr)	End Time	State/Provinc	e County DUCHESNE Category	Field Name Black Tail Ridge	COMPLETION	Com	
21/UWI 301351 ime Lo tart Time 6:00	1460000 g Dur (hr) 0.50		State/Provinc UT	e County DUCHESNE	Field Name Black Tail Ridge WSI An SLB Wi	d Secured. 0 Psi. On We	Com ell. n, Hold Safety Meeting	
301351 ime Lo art Time 6:00	1460000 g Dur (hr) 0.50 2.25	End Time	State/Province UT Code LOCL	County DUCHESNE Category Lock Wellhead & Secure	Field Name Black Tail Ridge WSI An SLB Wi Lubrica: RIH Wit .36" Per Density, Found A Drop Do Holes.	d Secured. 0 Psi. On We reLine Arrive On Locatio for, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short	Com cell. n, Hold Safety Meeting Gun, Rig Up To Well. I Perf. Gun Configured ms., .44 Dia. Holes. coated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012
801351 me Lo art Time 5:00 5:30	1460000 g Dur (hr) 0.50 2.25 2.00	End Time 06:30 08:45	Code LOCL SRIG	County DUCHESNE Category Lock Wellhead & Secure Rig Up/Down	Field Name Black Tail Ridge WSI An SLB Wi Lubrica RIH Wit .36" Per Density, Found A Drop Do Holes. POOH.	d Secured. 0 Psi. On We reLine Arrive On Locatio for, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short own To Depth, Perforate LayDown Gun, Verify All	Com ell. n, Hold Safety Meeting Gun, Rig Up To Well. Perf. Gun Configured ms., .44 Dia. Holes. Dated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012
801351 me Lo art Time 5:00 5:30 3:45	1460000 g Dur (hr) 0.50 2.25 2.00	End Time 06:30 08:45 10:45	Code LOCL SRIG	Category Lock Wellhead & Secure Rig Up/Down Perforating	Field Name Black Tail Ridge WSI An SLB Wi Lubrica' RIH Wii .36" Per Density, Found A Drop Do Holes. POOH.	d Secured. 0 Psi. On We reLine Arrive On Locatio tor, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short own To Depth, Perforate	Com ell. n, Hold Safety Meeting Gun, Rig Up To Well. Perf. Gun Configured ms., .44 Dia. Holes. Dated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012
801351 1 me Lo 1 art Time 1 5:00 1 5:30 1 3:45 1 5:45 1 6:00 1 6:31	1460000 g Dur (hr) 0.50 2.25 2.00	End Time 06:30 08:45 10:45 16:00 06:00	Code LOCL SRIG PFRT SRIG LOCL	County DUCHESNE Category Lock Wellhead & Secure Rig Up/Down Perforating Rig Up/Down	Field Name Black Tail Ridge WSI An SLB Wi Lubrica RIH Wit .36" Pet Density, Found A Drop Do Holes. POOH. HES Or WSI An	d Secured. 0 Psi. On We reLine Arrive On Locatio tor, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short own To Depth, Perforate LayDown Gun, Verify All Location At 11:00 Hrs. d Secured. SDFD.	Com ill. n, Hold Safety Meeting Gun, Rig Up To Well. Perf. Gun Configured ns., .44 Dia. Holes. Dated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/ Shots Fired, WSI And	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up d At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2011. CR-4 Zone, 8,391 - 8,696'. 48 d Secured.
801351 me Lo art Time 5:00 5:30 3:45 0:45 5:00 -31 D	1460000 g Dur (hr) 0.50 2.25 2.00 5.25 14.00	End Time 06:30 08:45 10:45 16:00 06:00	Code LOCL SRIG PFRT SRIG LOCL	County DUCHESNE Category Lock Wellhead & Secure Rig Up/Down Perforating Rig Up/Down Lock Wellhead & Secure 2 06:00 - 9/25/20	Field Name Black Tail Ridge WSI An SLB Wi Lubrica: RIH Wit .36" Per Density, Found A Drop Do Holes. POOH. HES Or	d Secured. 0 Psi. On We reLine Arrive On Locatio for, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short own To Depth, Perforate LayDown Gun, Verify All	Com ell. n, Hold Safety Meeting Gun, Rig Up To Well. Perf. Gun Configured ms., .44 Dia. Holes. Dated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up I At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012. CR-4 Zone, 8,391 - 8,696'. 48
87/UWI 801351 me Lo art Time 5:00 5:30 3:45 0:45 5:00 6-31 C	1460000 g	End Time 06:30 08:45 10:45 16:00 06:00 8 9/2	Code LOCL SRIG PFRT SRIG LOCL SRIG LOCL SRIG VICTORIAN CONTROL CONT	Category Lock Wellhead & Secure Rig Up/Down Perforating Rig Up/Down Lock Wellhead & Secure Rig Up/Down County Lock Wellhead & Secure County DUCHESNE	Field Name Black Tail Ridge WSI An SLB Wi Lubrica: RIH Wit .36" Pel Density, Found A Drop Do Holes. POOH. HES Or WSI An	d Secured. 0 Psi. On We reLine Arrive On Locatio tor, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron E And Correlated To Short own To Depth, Perforate LayDown Gun, Verify All Location At 11:00 Hrs. d Secured. SDFD.	Com Pill. n, Hold Safety Meeting Gun, Rig Up To Well. I Perf. Gun Configured ms., .44 Dia. Holes. Pated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/ Shots Fired, WSI And Rig Up Equipment	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up I At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012 . CR-4 Zone, 8,391 - 8,696'. 48 I Secured.
3:45 3:45 3:45 3:45 3:45 3:45 3:45 3:45	1460000 g Dur (hr) 0.50 2.25 2.00 5.25 14.00 D-36 BTF 1460000 g Dur (hr)	End Time 06:30 08:45 10:45 16:00 06:00 R 9/2 End Time	Code LOCL SRIG PFRT SRIG LOCL SRIG LOCL SRIG CODE SRIG CODE	Category Lock Wellhead & Secure Rig Up/Down Perforating Rig Up/Down Lock Wellhead & Secure Rig Up/Down Cock Wellhead & Secure County DUCHESNE	Field Name Black Tail Ridge WSI An SLB Wi Lubrica' RIH Wit .36" Per Density, Found A Drop Do Holes. POOH. HES Or WSI An PI2 06:00 Field Name Black Tail Ridge	COMPLETION d Secured. 0 Psi. On We reLine Arrive On Locatio tor, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron Dand Correlated To Short own To Depth, Perforate LayDown Gun, Verify All Location At 11:00 Hrs. d Secured. SDFD.	Com Pill. n, Hold Safety Meeting Gun, Rig Up To Well. I Perf. Gun Configured ms., .44 Dia. Holes. Pated 09-05-2012 And Joint At 8,177 - 8,199' Stage 1 CR-5/CR-4A/ Shots Fired, WSI And Rig Up Equipment Total Depth (ftKB)	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up I At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2013 CR-4 Zone, 8,391 - 8,696'. 48 I Secured. Primary Job Type 8,860.0 Drilling & Completion
9:45 6:00 6:30 8:45	1460000 g Dur (hr) 0.50 2.25 2.00 5.25 14.00 D-36 BTF 1460000 g Dur (hr)	End Time 06:30 08:45 10:45 16:00 06:00 8 9/2	Code LOCL SRIG PFRT SRIG LOCL SRIG LOCL SRIG VICTORIAN CONTROL CONT	Category Lock Wellhead & Secure Rig Up/Down Perforating Rig Up/Down Lock Wellhead & Secure Rig Up/Down County Lock Wellhead & Secure County DUCHESNE	Field Name Black Tail Ridge WSI An SLB Wi Lubrica RIH Wit .36" Per Density, Found A Drop Do Holes. POOH. HES Or WSI An Pield Name Black Tail Ridge	COMPLETION d Secured. 0 Psi. On We reLine Arrive On Locatio tor, Test Lubricator, Arm h 3 1/8" PJ Omega 3104 netration Charges, 16 Gr / Dual Spaced Neutron Dand Correlated To Short own To Depth, Perforate LayDown Gun, Verify All Location At 11:00 Hrs. d Secured. SDFD.	Com Pell. In, Hold Safety Meeting Gun, Rig Up To Well. I Perf. Gun Configured ms., .44 Dia. Holes. Pated 09-05-2012 And Joint At 8,177 - 8,199 Stage 1 CR-5/CR-4A/ Shots Fired, WSI And Rig Up Equipment Total Depth (ftKB) Com Hrs., Prime Chemical	8,860.0 Drilling & Completion g. Rig Up Equipment. Pick Up I At 120 Degree Phasing, 3 Spf, Correlating To HES Spectral SLB CBL/CCL Dated 09/12/2012 . CR-4 Zone, 8,391 - 8,696'. 48 I Secured.



Time Log Start Time	Dur (hr)	End Time	Code	Category	Com
06:10		07:15	FRAC	Frac. Job	Frac Stage 1. Fluid System: Hybor G 16 Open Well, 592 Psi. ICP. BrokeDown At 9.1 Bpm And 2,830 Psi Pump 3900 Gals. 15% HCL And 96 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 69.1 Bpm And 4,044 Psi., Get ISIP, 2,204 Psi 0.70 Psi./Ft. F.G 33/48 Holes. Con't With SlickWater Pad, 48,431 Gals Stage Into Hybor Pad, 71.6 Bpm At 4,013 Psi On Perfs, 71.7 Bpm At 4,126 Psi., 12,140 Gals. Stage Into 2# 20/40 White Prop, 71.5 Bpm At 4,122 Psi On Perfs, 70.9 Bpm At 3,678 Psi., 9,483 Gals. Stage Into 3# 20/40 White Prop, 70.9 Bpm At 3,678 Psi On Perfs, 71.0 Bpm At 3,346 Psi., 19,081 Gals. Stage Into 3.5# 20/40 White Prop, 71.1 Bpm At 3,200 Psi On Perfs, 71.1 Bpm At 3,120 Psi., 10,462 Gals. Stage Into 4# 20/40 White Prop, 71.1 Bpm At 3,110 Psi On Perfs, 71.1 Bpm At 3,067 Psi., 10,869 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 2,327 Psi 0.71 Psi./Ft. F.G WSI And Secured. Total 20/40 White - 150,700# Total Clean - 132,760 Gals 3,161 Bbls 2% KCL - 62,035 Gals 1,477 Bbls Produced Water - 68,816 Gals 1,638 Bbls BWTR - 3,439 Bbls. Max. Rate - 71.7 Bpm Avg. Rate - 71.3 Bpm Max. Psi 4,130 Psi. Avg. Psi 3,489 Psi.
07:15	0.25	07:30	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize To Well Pressure.
07:30	1.17	08:40	PFRT	Perforating	RIH With 3 1/8" PJ Omega 3104 Perf. Gun Configured At 120 Degree Phasing, 3 Spf, .36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 8,177 - 8,199'. Drop Down To Depth, Set CBP At 8,382', 2,150 Psi Perforate Stage 2 CR-4/CR-3 Zone, 8,103 - 8,362'. 45 Holes. 2,150 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.
08:40	0.08	08:45	GOP	General Operations	Well Turned Over To HES. Pressure Test To 8500#. Equalize, Open To Well.
08:45		09:55	FRAC	Frac. Job	Frac Stage 2. Fluid System: Hybor G 16 Open Well, 2047 Psi. ICP. BrokeDown At 10.1 Bpm And 3,202 Psi Pump 3900 Gals. 15% HCL And 90 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 71.2 Bpm And 4,213 Psi., Get ISIP, 2,409 Psi 0.70 Psi./Ft. F.G 33/45 Holes. Con't With SlickWater Pad, 53,207 Gals Stage Into Hybor Pad, 71.4 Bpm At 3,995 Psi On Perfs, 71.3 Bpm At 4,195 Psi., 13,376 Gals. Stage Into 2# 20/40 White Prop, 71.3 Bpm At 4,218 Psi On Perfs, 71.0 Bpm At 3,851 Psi., 9,166 Gals. Stage Into 3# 20/40 White Prop, 71.0 Bpm At 3,801 Psi On Perfs, 71.1 Bpm At 3,522 Psi., 25,044 Gals. Stage Into 3.5# 20/40 White Prop, 71.0 Bpm At 3,490 Psi On Perfs, 71.0 Bpm At 3,425 Psi., 10,207 Gals. Stage Into 4# 20/40 White Prop, 71.0 Bpm At 3,422 Psi On Perfs, 71.1 Bpm At 3,067 Psi., 10,869 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 2,552 Psi 0.75 Psi./Ft. F.G WSI And Secured. Total 20/40 White - 165,500# Total 20/40 White - 165,500# Total Clean - 143,096 Gals 3,407 Bbls 2% KCL - 68,374 Gals 1,628 Bbls Produced Water - 72,744 Gals 1,732 Bbls BWTR - 3,560 Bbls. Max. Rate - 71.5 Bpm Avg. Rate - 71.5 Bpm Avg. Rate - 71.1 Bpm Max. Psi 4,218 Psi. Avg. Psi 3,684 Psi.
09:55	0.17	10:05	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize To Well Pressure.



Time Lo	g				
Start Time	Dur (hr)	End Time	Code	Category	Com
10:05		11:15	PFRT	Perforating	RIH With 3 1/8" PJ Omega 3104 Perf. Gun Configured At 120 Degree Phasing, 3 Spf, .36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 7,432 - 7,453'. Drop Down To Depth, Set CBP At 8,091', 2,200 Psi Perforate Stage 3 CR-3/CR-2 Zone, 7,788 - 8,071'. 45 Holes. 2,150 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.
11:15		11:25	GOP	General Operations	Well Turned Over To HES. Pressure Test To 8500#. Equalize, Open To Well.
11:25	1.08	12:30	FRAC	Frac. Job	Frac Stage 3. Fluid System: Hybor G 16 Open Well, 2053 Psi. ICP. BrokeDown At 10.0 Bpm And 2,331 Psi Pump 3900 Gals. 15% HCL And 90 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 71.3 Bpm And 3,899 Psi., Get ISIP, 2,261 Psi 0.73 Psi./Ft. F.G 35/45 Holes. Con't With SlickWater Pad, 50,891 Gals Stage Into Hybor Pad, 71.6 Bpm At 3,762 Psi On Perfs, 71.4 Bpm At 3,845 Psi., 12,536 Gals. Stage Into 2# 20/40 White Prop, 71.3 Bpm At 3,933 Psi On Perfs, 70.9 Bpm At 3,564 Psi., 8,893 Gals. Stage Into 3# 20/40 White Prop, 71.0 Bpm At 3,509 Psi On Perfs, 71.0 Bpm At 3,253 Psi., 22,691 Gals. Stage Into 3.5# 20/40 White Prop, 71.0 Bpm At 3,205 Psi On Perfs, 71.0 Bpm At 3,144 Psi., 9,835 Gals. Stage Into 4# 20/40 White Prop, 71.0 Bpm At 3,150 Psi On Perfs, 71.0 Bpm At 3,099 Psi., 10,625 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 2,395 Psi 0.74 Psi./Ft. F.G WSI And Secured. Total 20/40 White - 156,500# Total Clean - 136,418 Gals 3,248 Bbls 2% KCL - 64,580 Gals 1,538 Bbls Produced Water - 69,846 Gals 1,663 Bbls BWTR - 3,416 Bbls. Max. Rate - 71.6 Bpm Avg. Rate - 71.0 Bpm Max. Psi 3,933 Psi. Avg. Psi 3,393 Psi.
12:30	0.17	12:40	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize To Well Pressure.
12:40		13:45	PFRT	Perforating	RIH With 3 1/8" PJ Omega 3104 Perf. Gun Configured At 120 Degree Phasing, 3 Spf, .36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 7,432 - 7,453'. Drop Down To Depth, Set CBP At 7,769', 2,200 Psi Perforate Stage 4 CR-2/Wasatch Zone, 7,520 - 7,749'. 45 Holes. 2,000 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.
13:45	0.09	13:50	GOP	General Operations	Well Turned Over To HES. Pressure Test To 8500#. Equalize, Open To Well.

www.peloton.com Page 5/9 Report Printed: 10/2/2012



Time Lo					
Start Time	Dur (hr)	End Time		Category	Com
13:50	1.08	14:55	FRAC	Frac. Job	Frac Stage 4. Fluid System: Hybor G 16 Open Well, 1914 Psi. ICP. BrokeDown At 10.2 Bpm And 2,891 Psi Pump 3900 Gals. 15% HCL And 90 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 71.3 Bpm And 4,089 Psi., Get ISIP, 2,018 Psi 0.71 Psi./Ft. F.G 30/45 Holes. Con't With SlickWater Pad, 48,577 Gals Stage Into Hybor Pad, 71.7 Bpm At 3,581 Psi On Perfs, 71.6 Bpm At 3,714 Psi., 12,535 Gals. Stage Into 2# 20/40 White Prop, 71.5 Bpm At 3,795 Psi On Perfs, 70.9 Bpm At 3,446 Psi., 8,510 Gals. Stage Into 3# 20/40 White Prop, 70.9 Bpm At 3,418 Psi On Perfs, 70.9 Bpm At 3,081 Psi., 21,998 Gals. Stage Into 3.5# 20/40 White Prop, 70.9 Bpm At 3,020 Psi On Perfs, 70.9 Bpm At 3,005 Psi., 9,835 Gals. Stage Into 4# 20/40 White Prop, 71.0 Bpm At 3,150 Psi On Perfs, 71.0 Bpm At 3,099 Psi., 10,625 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 2,327 Psi 0.75 Psi./Ft. F.G WSI And Secured. Total 20/40 White - 150,400# Total Clean - 131,708 Gals 3,136 Bbls 2% KCL - 62,501 Gals 1,488 Bbls Produced Water - 67,307 Gals 1,603 Bbls BWTR - 3,294 Bbls. Max. Rate - 71.1 Bpm Avg. Rate - 71.1 Bpm Max. Psi 3,795 Psi. Avg. Psi 3,258 Psi.
14:55	0.25	15:10	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize To Well Pressure.
15:10	1.08	16:15	PFRT	Perforating	RIH With 3 1/8" PJ Omega 3104 Perf. Gun Configured At 120 Degree Phasing, 3 Spf, .36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 6,088 - 6,110'. Drop Down To Depth, Set CBP At 7,515', 2,000 Psi Perforate Stage 5 CR-1 Zone, 7,239 - 7,500'. 45 Holes. 1,900 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.
16:15	0.75	17:00	GOP	General Operations	ShutDown And Secure Equipment
17:00	13.00	06:00	LOCL	Lock Wellhead & Secure	WSI And Secured. SDFD.
5-31D	-36 BTR	9/2	5/2012	2 06:00 - 9/26/2012 0	06:00
API/UWI			state/Province		Name Well Status Total Depth (ftKB) Primary Job Type

API/UWI	State/Province	County	Field Name	Well Status	Total Depth (ftKB)	Primary Job Type
43013511460000	UT	DUCHESNE	Black Tail Ridge	COMPLETION	8,860.0	Drilling & Completion

Time Lo	g				
Start Time	Dur (hr)	End Time	Code	Category	Com
06:00	0.00	06:00	LOCL		HES Crew On Location At 0400 Hrs., Prime Chemical And Fluid Pumps, Pressure Test To 9000 Psi., Ran QC On Fluid, Looks Good.
06:00	0.00	06:00	SMTG	Safety Meeting	Safety Meeting. Talk About Smoking Area, PPE, Escape And Mustering Areas, Communication, And Red Zone.

www.peloton.com Page 6/9 Report Printed: 10/2/2012



Time Log		F . 1 T	I 6	2	2
Start Time 06:00	Dur (hr)	End Time 07:00	FRAC	Category Frac. Job	Frac Stage 5. Fluid System: Hybor G 16
					Open Well, 1274 Psi. ICP. BrokeDown At 10.3 Bpm And 2,120 Psi Pump 3900 Gals. 15% HCL And 90 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 71.5 Bpm And 4,070 Psi., Get ISIP, 1,835 Psi 0.69 Psi./Ft. F.G 28/45 Holes. Con't With SlickWater Pad, 51,646 Gals Stage Into .75# 100 Mesh, 71.4 Bpm At 3,707 Psi On Perfs, 71.4 Bpm At 3,768 Psi., 19,455 Gals. Stage Into 1# 20/40 White Prop, 71.3 Bpm At 3,513 Psi On Perfs, 71.2 Bpm At 3,355 Psi., 8,325 Gals. Stage Into 2# 20/40 White Prop, 71.2 Bpm At 3,333 Psi On Perfs, 70.9 Bpm At 3,144 Psi., 8,208 Gals. Stage Into 3# 20/40 White Prop, 70.9 Bpm At 3,118 Psi On Perfs, 70.9 Bpm At 2,956 Psi., 23,566 Gals. Stage Into 3.5# 20/40 White Prop, 70.9 Bpm At 2,902 Psi On Perfs, 70.9 Bpm At 2,889 Psi., 9,325 Gals. Stage Into 4# 20/40 White Prop, 70.8 Bpm At 2,903 Psi On Perfs, 71.0 Bpm At 2,926 Psi., 9,532 Gals. Stage Into 4# 20/40 White Prop, 70.8 Bpm At 2,903 Psi On Perfs, 71.0 Bpm At 2,926 Psi., 9,532 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 2,012 Psi 0.71 Psi./Ft. F.G WSI And Secured. Total 100 Mesh - 14,560# Total 20/40 White - 160,840# Total 20/40 White - 69,702 Gals 1,660 Bbls BWTR - 3,738 Bbls. Max. Rate - 71.6 Bpm Avg. Rate - 71.1 Bpm Max. Psi 3,776 Psi. Avg. Psi 3,198 Psi.
07:00	0.50	07:30	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize
07:30		08:40	PFRT	Perforating	To Well Pressure. RIH With 3 1/8" PJ Omega 3104 Perf. Gun Configured At 120 Degree Phasing, 3 Spf,
					.36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 6,088 - 6,110'. Drop Down To Depth, Set CBP At 7,234', 1,700 Psi Perforate Stage 6 UteLand Butte/Castle Peak Zone, 6,937 - 7,219'. 45 Holes. 1,500 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.
08:40		08:45	GOP	General Operations	Well Turned Over To HES. Pressure Test To 8500#. Equalize, Open To Well.
08:45	1.25	10:00	FRAC	Frac. Job	Frac Stage 6. Fluid System: Hybor G 16 Open Well, 1437 Psi. ICP. BrokeDown At 10.5 Bpm And 1,770 Psi Pump 3900 Gals. 15% HCL And 90 Bio Balls, Attempt BallOut. Let Balls Fall. Get Stabilized Injection Of 71.3 Bpm And 4,075 Psi., Get ISIP, 1,553 Psi 0.66 Psi./Ft. F.G 26/45 Holes. Con't With SlickWater Pad, 51,698 Gals Stage Into .75# 100 Mesh, 71.2 Bpm At 3,243 Psi On Perfs, 71.0 Bpm At 3,309 Psi., 19,503 Gals. Stage Into 1# 20/40 White Prop, 71.0 Bpm At 3,360 Psi On Perfs, 70.6 Bpm At 3,176 Psi., 8,039 Gals. Stage Into 2# 20/40 White Prop, 70.6 Bpm At 3,154 Psi On Perfs, 70.4 Bpm At 2,918 Psi., 8,226 Gals. Stage Into 3# 20/40 White Prop, 70.4 Bpm At 2,896 Psi On Perfs, 70.4 Bpm At 2,763 Psi., 24,207 Gals. Stage Into 3.5# 20/40 White Prop, 70.6 Bpm At 2,705 Psi On Perfs, 70.8 Bpm At 2,651 Psi., 9,809 Gals. Stage Into 4# 20/40 White Prop, 71.0 Bpm At 2,648 Psi On Perfs, 70.8 Bpm At 2,628 Psi., 8,535 Gals. Stage Into Flush, Flush 15 Bbls. Over Bottom Perf Get ISDP, 1,826 Psi 0.70 Psi./Ft. F.G WSI And Secured. Total 100 Mesh - 14,430# Total 20/40 White - 160,470# Total Clean - 149,506 Gals 3,560 Bbls 2% KCL - 78,319 Gals 1,865 Bbls Produced Water - 69,162 Gals 1,647 Bbls BWTR - 3,738 Bbls. Max. Rate - 71.3 Bpm Avg. Rate - 70.6 Bpm Max. Psi 3,365 Psi. Avg. Psi 2,942 Psi.
10:00	0.17	10:10	CTUW	W/L Operation	Well Turned Over To WireLine. Pick Up Gun String And CBP Plug Assembly. Equalize To Well Pressure.



Time Lo	g												
Start Time	Dur (hr)	End Time	Code	Category				Com erf. Gun Configured At 120 Degree Phasing, 3 Spf,					
10:10	1.08	11:15	PFRT	Perforating		.36" Penetration Charges, 16 Gms., .44 Dia. Holes. Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 6,088 - 6,110'. Drop Down To Depth, Set CBP At 6,930', 1,600 Psi Perforate Stage 7 Castle Peak/Black Shale Zone, 6,595 - 6,910'. 45 Holes. 1,200 Psi POOH. LayDown Gun, Verify All Shots Fired, WSI And Secured.							
11:15	0.17	11:25	GOP	General Operations		Well Turn	ed Over To HES. Pressure	e Test To 8500#. Equalize, Open To Well.					
11:25		12:40	FRAC	Frac. Job		Frac Stag Open We Pump 390 Get Stabil F.G 29/4 Con't With Stage Into On Perfs, Stage Into On On O	e 7. Fluid System: Hybor G I, 1098 Psi. ICP. BrokeDo IO Gals. 15% HCL And 90 ized Injection Of 68.1 Bpm 5 Holes. o .75# 100 Mesh, 70.2 Bpm 69.9 Bpm At 2,838 Psi., 1 o 1# 20/40 White Prop, 69. 69.8 Bpm At 2,844 Psi., 7 o 2# 20/40 White Prop, 69. 69.3 Bpm At 2,648 Psi., 7 o 3# 20/40 White Prop, 69. 69.3 Bpm At 2,505 Psi., 1 o 3.5# 20/40 White Prop, 69. 60.7 Bpm At 2,475 Psi., 8 o 4# 20/40 White Prop, 71. 70.8 Bpm At 2,628 Psi., 10 o 10.7 Bpm At 2,628 Psi., 10 o 10.7 Bpm At 2,628 Psi., 10 o 10.7 Bpm At 2,638 Psi., 10 o 10.7 Bpm At 2,63	G 16 Dwn At 10.4 Bpm And 1,464 Psi Bio Balls, Attempt BallOut. Let Balls Fall. In And 3,152 Psi., Get ISIP, 1,302 Psi 0.64 Psi./Ft. Gals In At 2,793 Psi 7,998 Gals. 8 Bpm At 2,874 Psi 667 Gals. 4 Bpm At 2,833 Psi 639 Gals. 3 Bpm At 2,632 Psi 9,502 Gals. 5.1 Bpm At 2,291 Psi 8,809 Gals. 0 Bpm At 2,648 Psi 8,866 Gals. er Bottom Perf Get ISDP, 1,569 Psi 0.67 Psi./Ft.					
12:40	0.33	13:00	CTUW	W/L Operation		Pressure.	ed Over 10 wireLine. Pick	Up CBP Plug Assembly. Equalize To Well					
13:00	1.00	14:00	PFRT	Perforating		RIH With 3 1/8" Sinker Bars And CBP Plug Assembly Correlating To HES Spectral Density/ Dual Spaced Neutron Dated 09-05-2012 And SLB CBL/CCL Dated 09/12/2012. Found And Correlated To Short Joint At 6,088 - 6,110'. Drop Down To Depth, Set CBP At 6,560', 1,300 Psi Bleed Pressure Off Well. POOH. LayDown Tools. WSI And Secured.							
14:00	4.00	18:00	SRIG	Rig Up/Down		RigDown	SLB And HES. MOL. Batcl	h Water.					
18:00	12.00	06:00	LOCL	Lock Wellhead & Secure		WSI And	Secured.						
5-31E)-36 BTR	8 9/2	6/2012	06:00 - 9/27/201	2 06:0	00							
API/UWI		S	tate/Provinc	e County	Field Name)	Well Status	Total Depth (ftKB) Primary Job Type					
	1460000	l	JT	DUCHESNE	Black Ta	ail Ridge	COMPLETION	8,860.0 Drilling & Completion					
Time Lo Start Time	g Dur (hr)	End Time	Code	Category				Com					
06:00	,	07:00	CTRL	Crew Travel		CREW TF	RAVEL. HOLD SAFETY MI						
07:00		09:00	RMOV	Rig Move			G F/ RU 24-13 TO LOACT						
09:00		10:00	SRIG	Rig Up/Down			REQUIPMENT.						
10:00		11:00	BOPI	Install BOP's			TREE. N/U BOP. R/U FL	OOR & FOLIIPMENT					
11:00		12:30	GOP	General Operations				LOAD 286 JTS OF 2-7/8 TBG ON RACKS.					
12:30		17:00	RUTB	Run Tubing		P/U 4-3/4	BIT, POBS, 1 JT 2-7/8 TB	BG & XN- NIPPLE. RIH W/ BHA P/U NEW 2-7/8 L-80 CIRC EQUIPMENT. SWIFN.					
17:00	1.00	18:00	CTRL	Crew Travel		CREW TE	RAVEL.						
18:00	12.00	06:00	LOCL	Lock Wellhead & Secure			UT IN & SECURE.						
5-31F			7/2013	2 06:00 - 9/28/201	2 06:0	00							
API/UWI	, 30 D I I		state/Provinc		Field Name		Well Status	Total Depth (ftKB) Primary Job Type					
	1460000		JT	DUCHESNE	Black Ta		COMPLETION	8,860.0 Drilling & Completion					

www.peloton.com Page 8/9 Report Printed: 10/2/2012



Time Log	9				
Start Time	Dur (hr)	End Time	Code	Category	Com
06:00	1.00	07:00	CTRL	Crew Travel	CREW TRAVEL. HOLD SAFETY MEETING.
07:00	0.50	07:30	RUTB	Run Tubing	SICP- 0. R/U POWER SWIVEL. BREAK CIRC.
07:30	7.00	14:30	DOPG	Drill Out Plugs	D/O KILL PLUG @ 6560'. CFP ON 32/64 CHOKE 200 PSI. SWIVEL IN HOLE, TAG SAND @ 6925'. C/O SAND & D/O CBP @ 6932'. CFP- 400.
					SWIVEL IN HOLE, TAG SAND @ 7205'. C/O SAND & D/O CBP @ 7236'. CFP- 450.
					SWIVEL IN HOLE, NO SAND. D/O CBP @ 7517'. CFP- 400.
					SWIVEL IN HOLE, TAG SAND @ 7760'. C/O SAND & D/O CBP @ 7771'. CFP- 400.
					SWIVEL IN HOLE, TAG SAND @ 8062'. C/O SAND & D/O CBP @ 8093'. CFP- 600.
					SWIVEL IN HOLE, TAG SAND @ 8288'. C/O SAND & D/O CBP @ 8384'. CFP- 700.
					SWIVEL IN HOLE, TAG SAND @ 8693'. C/O SAND TO F/C @ 8760', D/O F/C & C/O CMT TO 8820'. PBTD. CIRC WELL CLEAN FOR 1 HR. R/D SWIVEL.
	4.00	45.00	D		
14:30			PULT	Pull Tubing	POOH L/D TBG TO 6553' & LAND TBG. 206 JTS TOTAL IN HOLE.
15:30		17:00	IWHD	Install Wellhead	N/D BOP. N/U WELLHEAD. DROP BALL & PUMPED BIT OFF. R/U TO SALES LINE. TURN OVER TO PRODUCTION.
17:00	13.00	06:00	CTRL	Crew Travel	CREW TRAVEL.

5-31D-36 BTR 9/28/2012 06:00 - 9/29/2012 06:00

API/UWI	State/Province	County	Field Name	Well Status	Total Depth (ftKB)	Primary Job Type
43013511460000	UT	DUCHESNE	Black Tail Ridge	COMPLETION	8,860.0	Drilling & Completion

ıme	

Start Time	Dur (hr)	End Time	Code	Category	Com
06:00	1.00	07:00	CTRL	Crew Travel	CREW TRAVEL. HOLD SAFETY MEETING.
07:00	8.00	15:00	SRIG	3 -1.	R/D RIG & EQUIPMENT. CLEAN LOCATION. MOVE RIG & EQUIPMENT OFF LOCATION.
15:00	15.00	06:00	CTRL	Crew Travel	CREW TRAVEL.

www.peloton.com Page 9/9 Report Printed: 10/2/2012

	STATE OF UTAH			FORM 9		
	DEPARTMENT OF NATURAL RESOUR DIVISION OF OIL, GAS, AND MI			5.LEASE DESIGNATION AND SERIAL NUMBER: 1420H626405		
SUNDR	RY NOTICES AND REPORTS	ON V	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
	posals to drill new wells, significantly reenter plugged wells, or to drill horiz n for such proposals.			7.UNIT or CA AGREEMENT NAME:		
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: 5-31D-36 BTR		
2. NAME OF OPERATOR: BILL BARRETT CORP		9. API NUMBER: 43013511460000				
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	NE NUMBER: 12-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM				
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL			COUNTY: DUCHESNE			
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	HIP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W Me	U	STATE: UTAH			
11. CHEC	K APPROPRIATE BOXES TO INDICA	ATE NA	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA		
TYPE OF SUBMISSION			TYPE OF ACTION			
	ACIDIZE	Па	LTER CASING	CASING REPAIR		
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	С	HANGE TUBING	CHANGE WELL NAME		
Approximate date work will start.	CHANGE WELL STATUS	□ c	OMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE		
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	☐ FF	RACTURE TREAT	☐ NEW CONSTRUCTION		
10/3/2012	OPERATOR CHANGE	Пр	LUG AND ABANDON	PLUG BACK		
SPUD REPORT	✓ PRODUCTION START OR RESUME		ECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION		
Date of Spud:	REPERFORATE CURRENT FORMATION		IDETRACK TO REPAIR WELL	TEMPORARY ABANDON		
	TUBING REPAIR		ENT OR FLARE	WATER DISPOSAL		
DRILLING REPORT	WATER SHUTOFF		I TA STATUS EXTENSION	APD EXTENSION		
Report Date:			TIA STATUS EXTENSION			
	WILDCAT WELL DETERMINATION	o	THER	OTHER:		
l .	completed operations. Clearly shownst oil sales on 9/30/2012 a 10/3/2012.			Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY October 05, 2012		
NAME (PLEASE PRINT)	PHONE NUM	IBER	TITLE Social Parmit Analyst			
Venessa Langmacher SIGNATURE	303 312-8172		Senior Permit Analyst DATE			
N/A			10/3/2012			

	STATE OF UTAH			FORM 9
ı	DEPARTMENT OF NATURAL RESO DIVISION OF OIL, GAS, AND I			5.LEASE DESIGNATION AND SERIAL NUMBER: 1420H626405
SUNDR	Y NOTICES AND REPORT	TS ON V	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for procurrent bottom-hole depth, FOR PERMIT TO DRILL form	posals to drill new wells, significar reenter plugged wells, or to drill ho n for such proposals.	ntly deepe orizontal la	en existing wells below aterals. Use APPLICATION	7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: 5-31D-36 BTR
2. NAME OF OPERATOR: BILL BARRETT CORP	9. API NUMBER: 43013511460000			
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	NE NUMBER: 12-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL				COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH	HP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W	U	STATE: UTAH	
11. CHECI	K APPROPRIATE BOXES TO INDI	ICATE NA	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
	ACIDIZE	Па	LTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	☐ cı	HANGE TUBING	CHANGE WELL NAME
Approximate date work will start.	CHANGE WELL STATUS	□ c	OMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	☐ FF	RACTURE TREAT	☐ NEW CONSTRUCTION
·	OPERATOR CHANGE	□ рі	LUG AND ABANDON	PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME		ECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION		IDETRACK TO REPAIR WELL	TEMPORARY ABANDON
✓ DRILLING REPORT	L TUBING REPAIR		ENT OR FLARE	☐ WATER DISPOSAL
Report Date: 10/31/2012	WATER SHUTOFF	∟ sı	TA STATUS EXTENSION	APD EXTENSION
1070172012	WILDCAT WELL DETERMINATION	∐ o	THER	OTHER:
No Octob	completed operations. Clearly sher 2012 monthly drilling a	activity	to report.	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY November 07, 2012
NAME (PLEASE PRINT) Brady Riley	PHONE NU 303 312-8115	JMBER	TITLE Permit Analyst	
SIGNATURE N/A			DATE 11/7/2012	

Sundry Number: 32667 API Well Number: 43013511460000

	STATE OF UTAH			FORM 9
I	DEPARTMENT OF NATURAL RESOUF DIVISION OF OIL, GAS, AND M		3	5.LEASE DESIGNATION AND SERIAL NUMBER: 1420H626405
SUNDR	Y NOTICES AND REPORTS	ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	posals to drill new wells, significantl reenter plugged wells, or to drill horiz n for such proposals.			7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: 5-31D-36 BTR
2. NAME OF OPERATOR: BILL BARRETT CORP	9. API NUMBER: 43013511460000			
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300	DNE NUMBER: 312-8164 Ext	9. FIELD and POOL or WILDCAT: CEDAR RIM		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1982 FNL 0632 FWL				COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SWNW Section:	HP, RANGE, MERIDIAN: 31 Township: 03.0S Range: 06.0W M	eridian	n: U	STATE: UTAH
11. CHECI	K APPROPRIATE BOXES TO INDICA	ATE N	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
	ACIDIZE		ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS		CHANGE TUBING	CHANGE WELL NAME
- Approximate date work will old it.	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	□ F	FRACTURE TREAT	NEW CONSTRUCTION
	OPERATOR CHANGE	F	PLUG AND ABANDON	PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	□ F	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR		VENT OR FLARE	WATER DISPOSAL
✓ DRILLING REPORT Report Date:	WATER SHUTOFF		SI TA STATUS EXTENSION	APD EXTENSION
12/3/2012	WILDCAT WELL DETERMINATION		OTHER	OTHER:
12 DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show			<u>'</u>
	November monthly activity	-	_	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY December 03, 2012
NAME (DI EASE PRINT)	DLIONE NUM	IREP	Ттт	
NAME (PLEASE PRINT) Brady Riley	PHONE NUM 303 312-8115	IBER	TITLE Permit Analyst	
SIGNATURE N/A			DATE 12/3/2012	

Form 3160-4 (August 2007)

UNITED STATES

FORM APPROVED

(•		BUREA	U OF LA	ND M	ANAGI	EMENT			,					30 4- 0137 31,2010
	WELL	COMPL	ETION (OR REC	OMP	LETIO	N REP	ORT	AND LO	3			ease Serial N 420H6264		
1а. Турс о	_	Oil Well	☐ Gas	Well [D ry	Пo	ther		- 1			6. If	Indian, Allo	ttee or	Tribe Name
b. Type o	f Completion	Othe	cw Well	☐ Work	Over	De De	epen [] Plug	g Back 🔲	Diff. R	esvr.	7. Ü	nit or CA A	greeme	ent Name and No.
2. Name of BILL B	f Operator ARRETT Co	ORPORA	TION E	-Mail: jwe	Con ebb@bi	tact; JU	LIE WEB	B	·				case Name a -31D-36 B		il No.
3. Address	1099 18T DENVER	H STREE , CO 802	T SUITE 2				3a. Ph	one No	o. (include are 9-9949	a code)			PI Well No.		43-013-51146
	a of Well (Re						•)*			10. I	Field and Po EDAR RIN	ol, or I	
At surf			L 632FWL				12683 W	Lon				11. 5	Sec., T., R.,	M., or	Block and Survey 3S R6W Mer UBM
	prod interval depth SW	•			FNL 8 2	6HVVL						12. 0	County or Pa	rish	13. State
14. Date S 08/17/2	pudded	144 2001	15. D	atc T.D. R					Completed				DUCHESNE Elevations (I	OF, KE	UT 3, RT, GL)*
			<u> </u>	/05/2012					0/2012	dy to P				3 GL	
18. Total I		MD TVD	8860 8850	أ	•	Back T.		MD IVD	8761 8751				dge Plug Sc	7	MD I'VD
MUD, 6	lectric & Off CBL, BORE	ier Mechan HOLE	ical Logs R	un (Submi	it copy o	f each)			22	Was I	vell core OST run? ional Su		XINo F	⊒ Yes	(Submit analysis) (Submit analysis) (Submit analysis)
23. Casing a	nd Liner Rec	ord (Repor	rt all strings	set in wel	1)					Ditec	JOHAI SH	vey	1740 (N 1 es	(Submit analysis)
Hole Size	Size/G	irade	Wt. (#/ft.)	Top (MD)		ottom MD)	Stage Cer Dept		No. of Sk Type of Co		Slurry (BE		Cement T	'op*	Amount Pulled
26.000 12.250		0 COND	36.0	***************************************	0	90		90						0	
8.750		625 J-55 00 P-110	36.0 17.0	1	0	2710 8860		2706 8850		730 1370		318 467		0 2306	15000
										1070		407		2000	15000
	<u> </u>														
24. Tubing	Record			<u> </u>			L	***************************************			<u> </u>				
Size	Depth Set (N		cker Depth	(MD)	Size	Deptl	ı Set (MD)) P	acker Depth (MD)	Size	De	pth Set (MI))	Packer Depth (MD)
2.875 25. Produci	ng Intervals	6554			•	26.	Perforation	n Reco	ard	<u>_</u>		<u> </u>		上	
	ormation		Тор		Bottom				Interval	Т	Size	1	Vo. Holes		Perf. Status
_A)	GREEN R	IVER		6595	75	00			6595 TO 7	500	0.4			OPEN	
B)	WAS	ATCH		7520	86	96		·····	7520 TO 8	696	0.4	40	183	OPEN	٧
D).						+-						+			
27. Acid, F	racture, Treat	ment, Cem	ent Squeeze	Etc.											
	Depth Interve	····					•		nount and Ty	pe of M	aterial				
			00 GREEN 96 WASAT					5-7				····			
		20 10 00				<u> </u>	1020								
00 D 1															
Date First	ion - Interval	A. Hours	Test	Oil	Gas	T is	/ater .	Oil Gr	anida:	Gas		Des de ser	M.d1		
Produced 09/30/2012	Date 10/02/2012	Tested 24	Production	BBL	MCF	В	BL	Corr.	API	Gravity		Produci	ion Method		
Choke	Thg. Press.	Csg.	24 Hr.	423.0	Gas	1.0	461.0 Vater	Gas:O	52.0	Well St	ahs		FLOW	SFRC	M WELL
Size 26/64		Press. 1900.0	Rate	вві, 423	MCF 10	В	BL 461	Ratio	2460	1	OW				
	tion - Interve			1 720	1 10		701	1	2700	1 -	J##				i di min
Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF		/ater BL	Oil Gr		Gas		Producti	ion Method		
		t wordt		برسر	MCr	ľ	אמי	Côm.	wi	Gravity				Dr	
Choke Size	Tbg, Press. Flwg.	Csg, Press.	24 Hr. Rate	Oil BBL	Gas MCF		Vater BL	Gas:O Ratio	il	Well St	atus				CEIVED
	SI	<u></u>							_	1.				UF	T 0 4 2012

⁽See Instructions and spaces for additional data on reverse side)
ELECTRONIC SUBMISSION #161604 VERIFIED BY THE BLM WELL INFORMATION SYSTEM
** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

28h Produ	uction - Interv	ılC			·								
Date First	Test	Hours	Test	Oil	Gas	Water	Tong :			T'	·		
Produced	Date	Tested.	Production	BBL	MCF	BBL	Oil Gravity Corr. API	Gas Grav		Production Method			
Choke Size	Tbg. Press. Fiwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas:Oil Ratio	Well	Status				
	action - Interva	d D	· · · · · · · · · · · · · · · · · · ·										
Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Grav		Production Method			
Choke Size	Tog. Press. Flwg. Si	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas:Oil Ratio	Well	Il Status				
29. Dispos SOLD	ition of Gas(S	old, used f	or fuel, vent	ed, etc.)			<u> </u>			· · · · · · · · · · · · · · · · · · ·			
30. Summa	ary of Porous .	Zones (Inc	lude Aquife	rs):			***************************************		31. For	nation (Log) Mar	cers	· · · · · · · · · · · · · · · · · · ·	
iesis, H	all important z neluding depth coveries.	ones of po	rosity and co ested, cushio	ontents there in used, time	of: Cored in tool open,	itervals and flowing and	all drill-stem shut-in pressures						
]	Formation		Тор	Bottom		Descriptio	ns, Contents, etc.			Name		Top Meas Denth	
	32. Additional remarks (include plugging procedure): TOC calculated by CBL. CBL mailed due to file size. Conductor was cemented with grout. Treatment Data attached. This well had first oil sales on 9/30/2012 and first gas sales on 10/3/2012.												
I. Elec	enclosed attach trical/Mechani dry Notice for	ical Logs (. Geologic l	-		DST Rep	ort	4. Direction	al Survey	
34 The1	. aami C. 11 1	- fo		.11.0				·**					
34, 1 nereby	y centry that fr	ic icregoin	g and attach Electro	aic Sabmis	sion #1616(14 Verified	cct as determined by the BLM Wei RATION, sent t	l Inform	ation Sys	records (see attacl tem.	ed instruction	us);	
Name (p	olease print) <u>J</u>	ULIE WEI	ВВ				Title PE	RMIT AN	NALYST				
Signatur	те	ectionid	Solomistio	w)e	bk	<u> </u>	Date <u>12/</u>	04/2012					
Title 18 U.S of the Unite	S.C. Section IX	001 and Titalse, fictitie	tle 43 U.S.C ous or fradul	. Section 12 lent statemen	12, make it a	a crime for a	my person knowing to any matter with	ngly and hin its ju	willfully to	o make to any dep	artment or ag	gency	

5-31D-36 BTR Completion Report Continued*

	AMOUNT AND TYPE OF MATERIAL									
Stage .	BBLS Slurry	lbs 100 Mesh Sand	lbs 20/40 White Sand							
1	3,323		150,700							
2	3,585		165,500							
3	3,417		156,500							
4	3,300		150,400							
5	3,764	14,560	128,140							
6	3,717	14,430	131,370							
7	3,595	13,810	112,300							

^{*}Depth intervals for frac information same as perforation record intervals.

Bill Barrett Corp

Duchesne County, UT (NAD 1927) Sec. 31-T3S-R6W 5-31D-36 BTR

Plan A

Design: MWD Survey

Sperry Drilling ServicesFinal Survey Report

04 December, 2012

Well Coordinates: 673,174.73 N, 2,248,126.59 E (40° 10' 41.40" N, 110° 36' 43.10" W)

Ground Level: 6,613.00 ft

Local Coordinate Origin:

Centered on Well 5-31D-36 BTR

Viewing Datum:

KB=15' @ 6628.00ft (Patterson 506)

TVDs to System:

N

North Reference:

True

Unit System:

API - US Survey Feet - Custom

Geodetic Scale Factor Applied Version: 2003.16 Build: 43I

RECEIVED
DEC 0 4 2012

DIV. OF OIL, GAS & MINING

HALLIBURTON

Design Report for 5-31D-36 BTR - MWD Survey

Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Vertical Section	Dogleg Rate
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
133.00	0.89	211.22	132.99	-0.88	-0.54	-0.56	0.67
First MWD S	urvey						
197.00	1.19	227.04	196.98	-1.76	-1.28	-1.32	0.64
258.00	1.46	244.44	257.97	-2.53	-2.44	-2.50	0.79
320.00	1.17	258.90	319.95	-2.99	-3.78	-3.84	0.71
381.00	0.76	321.85	380.94	-2.79	-4.64	-4.70	1.75
442.00	1.16	2.81	441.94	-1.86	-4.86	-4.90	1.26
503.00	1.88	13.59	502.91	-0.27	-4.59	-4.60	1.26
564.00	1.93	14.60	563.88	1.70	-4.10	-4.06	0.10
625.00	1.87	11.70	624.85	3.67	-3.64	-3.56	0.19
686.00	1.73	10.57	685.82	5.55	-3.27	-3.14	0.24
748.00	1.59	15.27	747.79	7.30	-2.87	-2.70	0.31
809.00	1.06	38.55	808.78	8.55	-2.29	-2.10	1.22
870.00	1.42	58.52	869.76	9.39	-1.30	-1.09	0.91
930.00	2.29	57.52	929.73	10.42	0.35	0.58	1.45
993.00	2.21	59.12	992.68	11.72	2.45	2.71	0.16
1,057.00	1.90	57.01	1,056.64	12.93	4.40	4.69	0.50
1,120.00	1.78	52.52	1,119.61	14.10	6.05	6.37	0.30
1,184.00	1.71	50.08	1,183.58	15.31	7.57	7.92	0.16
1,248.00	1.69	47.73	1,247.55	16.56	9.00	9.37	0,11
1,311.00	1.52	47.30	1,310.52	17.75	10.31	10.70	0.27
1,374.00	1.38	39.38	1,373.50	18.91	11.40	11.82	0.39
1,438.00	1.36	40.17	1,437.49	20.08	12.38	12.83	0.04
1,501.00	1.30	40.65	1,500.47	21.20	13.33	13.80	0.10
1,564.00	1.21	45.91	1,563.45	22.20	14.27	14.77	0.23
1,628.00	1.09	48.68	1,627.44	23.07	15.21	15.73	0.21
1,691.00	1.25	48.97	1,690.43	23.92	16.18	16.71	0.25
1,754.00	1.90	47.76	1,753.40	25.07	17.47	18.03	1.03
. 1,818.00	1.86	50.54	1,817.37	26.45	19.06	19.65	0.16
1,881.00	1.55	49.94	1,880.34	27.64	20.50	21.12	0.49
1,945.00	1.35	50.40	1,944.32	28.68	21.75	22.38	0.31
2,008.00	1.23	53.25	2,007.30	29.56	22.86	23.52	0.22
□,072.00	1.02	56.74	2,071.29	30.28	23.89	24.56	0.35
2,135.00	1.00	58.92	2,134.28	30.87	24.83	25.51	0.07
2,199.00	1.42	57.22	2,198.27	31.59	25.97	26.67	0.66
2,262.00	1.40	61.05	2,261.25	32.39	27.30	28.02	0.15
2,326.00	1.16	66.36	2,325.23	33.03	28.58	29.31	0.42
2,389.00	1.10	72.72	2,388.22	33.46	29.74	30.48	0.22
2,453.00	1.56	73.93	2,452.20	33.88	31.16	31.92	0.72
2,516.00	1.51	78.61	2,515.18	34.29	32.80	33.56	0.21
2,579.00	1.10	86.34	2,578.16	34.49	34.22	34.98	0.71
2,642.00	0.83	100.01	2,641.16	34.45	35.27	36.04	0.56
2,740.00	0.84	93.69	2,739.15	34.28	36.69	37.45	0.09
2,803.00	0.89	124.16	2,802.14	33.97	37.55	38.31	0.73
2,866.00	1.16	107.69	2,865.13	33.50	38.57	39.31	0.63
2,930.00	1.31	109.71	2,929.11	33.06	39.87	40.60	0.24
2,993.00	1.12	109.46	2,992.10	32.61	41.13	41.85	0.30
3,057.00	1.06	52.63	3,056.09	32.76	42.19	42.91	1.62
3,120.00	1.11	43.70	3,119.08	33.56	43.07	43.82	0.28

Design Report for 5-31D-36 BTR - MWD Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)
3,184.00	0.57	145.69	3,183.07	33.74	43.68	44.43	2.11
3,247.00	1.33	165.78	3,246.06	32.78	44.04	44.76	1.30
3,311.00	1.84	80.99	3,310.05	32.22	45.24	45.95	3.39
3,374.00	2.59	65.11	3,373.00	32.97	47.53	48.25	1.53
3,437.00	2.45	81.21	3,435.94	33.78	50.15	50.89	1.14
3,501.00	3.42	84.34	3,499.86	34.18	53.40	54.15	1.54
3,564.00	4.20	81.90	3,562.72	34.69	57.55	58.32	1.26
3,628.00	4.59	87.41	3,626.53	35.13	62.43	63.21	0.90
3,691.00	4.41	89.14	3,689.33	35.28	67.37	68.15	0.36
3,755.00	4.46	84.96	3,753.14	35.54	72.31	73.09	0.51
3,818.00	5.17	86.23	3,815.92	35.94	77.58	78.37	1.14
3,882.00	6.46	87.52	3,879.59	36.29	84.06	84.85	2.03
3,945.00	6.20	92.92	3,942.21	36.27	91.00	91.79	1.03
4,009.00	5.83	92.45	4,005.85	35.95	97.70	98.48	0.58
4,072.00	6.65	91.92	4,068.48	35.69	104.54	105.31	1.30
4,136.00	7.38	93.99	4,132.00	35.28	112.34	113.11	1.21
4,199.00	7.59	94.62	4,194.46	34.67	120.53	121.27	0.36
4,262.00	8.35	91.29	4,256.85	34.23	129.25	129.98	1.41
4,326.00	7.79	93.32	4,320.22	33.87	138.22	138.95	0.98
4,390.00	7.14	90.93	4,383.68	33.56	146.53	147.25	1.13
4,453.00	7.00	82.67	4,446.20	33.98	154.25	154.98	1.63
4,517.00	6.74	82.39	4,509.74	34.98	161.84	162.59	0.41
4,580.00	6.00	88.82	4,572.35	35.53	168.80	169.55	1.63
4,643.00	5.33	85.35	4,635.04	35.84	175.01	175.77	1.19
4,707.00	5.24	79.61	4,698.77	36.61	180.85	181.62	0.84
4,770.00	4.88	84.63	4,761.53	37.38	186.34	187.13	0.91
4,830.16	4.26	95.16	4,821.50	37.42	191.12	191.91	1.73
4,897.00	3.63	107.45	4,888.18	36.56	195.61	196.38	1.57
4,960.00	3.18	114.02	4,951.07	35.25	199.11	199.85	0.94
5,024.00	2.43	123.46	5,014.99	33.78	201.86	202.57	1.37
5,087.00	1.80	144.60	5,077.95	32.23	203.55	204.22	1.58
5,151.00	1.28	167.93	5,141.93	30.72	204.28	204.92	1,26.
5,214.00	1.01	197.19	5,204.91	29.50	204.26	204.87	1.01
5,278.00	1.36	210.53	5,268.90	28.30	203.71	204.29	0.69
5,341.00	1.48	204.56	5,331.88	26.92	202.99	203.54	0.30
5,405.00	1.39	234.13	5,395.86	25.71	202.02	202.54	1.15
5,468.00	1.69	253.70	5,458.84	25.01	200.51	201.02	0.95
5,532.00	1.62	264.65	5,522.81	24.66	198,70	199.20	0.51
5,595.00	1.26	261.33	5,585.79	24.47	197.13	197.63	0.59
5,658.00	1.34	240.68	5,648.78	24.00	195.80	196.29	0.75
5,722.00	1.35	212.78	5,712.76	23.00	194.74	195.21	1.01
5,785.00	0.24	3.44	5,775.75	22.51	194.35	194.80	2.48
5,848.00	0.86	5.03	5,838.75	23.11	194.40	194.87	0.98
5,912.00	0.21	244.57	5,902.75	23.54	194.33	194.81	1.54
5,975.00	0.54	161.15	5,965.75	23.21	194.33	194.80	0.88
6,039.00	0.61	110.84	6,029.75	22.81	194.74	195.20	0.77
6,102.00	0.84	155.05	6,092.74	22.27	195.25	195.70	0.93
6,166.00	0.52	158.72	6,156.74	21.57	195.55	195.99	0.50
6,229.00	0.60	180.52	6,219.73	20.97	195.65	196.08	0.36
6,293.00	1.76	181.84	6,283.72	19.66	195.62	196.01	1.81

Design Report for 5-31D-36 BTR - MWD Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	
6,419.00	0.46	213.91	6,409.67	16.49	195.24	195.56	2.27	
6,483.00	0.69	305.60	6,473.67	16.50	194.78	195.11	1.31	
6,546.00	0.82	307.08	6,536.67	16.99	194.12	194.45	0.21	
6,610.00	1.14	350.22	6,600.66	17.90	193.64	194.00	1.22	
6,673.00	0.49	61.52	6,663.65	18.64	193.77	194.14	1.73	
6,737.00	0.69	116.30	6,727.65	18.60	194.36	194.73	0.89	
6,800.00	1.31	138.17	6,790.64	17.90	195.18	195.53	1.14	
6,863.00	1.23	142.83	6,853.62	16.82	196.07	196.40	0.21	
6,927.00	0.65	181.98	6,917.62	15.91	196.47	196.78	1.30	
6,990.00	0.63	160.17	6,980.61	15.23	196.58	196.87	0.39	
7,054.00	0.95	161.25	7,044.61	14.40	196.87	197.14	0.50	
7,117.00	1.12	177.47	7,107.60	13.29	197.06	197.31	0.53	
7,180.00	0.65	246.76	7,170.59	12.53	196.76	196,99	1.71	
7,243.00	0.86	263.73	7,233.58	12.34	195.96	196.19	0.48	
7,307.00	0.77	227.36	7,297.58	11.99	195.17	195.39	0.81	
7,371.00	1.15	201.72	7,361.57	11.11	194.61	194.81	0.88	
7,434.00	1.14	189.86	7,424.56	9.90	194.27	194.45	0.38	
7,497.00	0.29	150.78	7,487.55	9.15	194.24	194.40	1.48	
7,561.00	0.08	65.30	7,551.55	9.02	194.36	194.52	0.46	
7,624.00	0.61	159.06	7,614.55	8.73	194.52	194.67	0.98	
7,688.00	1.64	176.69	7,678.54	7.50	194.70	194.82	1.68	
7,751.00	1.43	162.48	7,741.51	5.85 ·	194,99	195.07	0.69	
7,815.00	1.07	111.45	7,805.50	4.87	195.78	195.84	1.76	
7,878.00	1.07	137.56	7,868.49	4.22	196.73	196.77	0.77	
7,941.00	1.74	152.36	7,931.47	2.93	197.57	197.58	1.20	
8,005.00	1.18	168.69	7,995.45	1.43	198.15	198.13	1.08	
8,068.00	1.46	214.60	8,058.44	0.13	197.82	197.77	1.68	
8,132.00	1.28	219.20	8,122.42	-1.09	196.90	196.83	0.33	
8,195.00	0.62	237.89	8,185.41	-1.82	196.17	196.08	1.14	4
8,259.00	1.54	203.29	8,249.40	-2.79	195.54	195.43	1.70	
8,322.00	1.56	195.25	8,312.37	-4.40	194.98	194.83	0.35	
8,385.00	1.12	203.42	8,375.36	-5.79	194.51	194.33	0.76	
8,449.00	1.09	203.59	8,439.34	-6.92	194.01	193.81	0.05	
8,512.00	1.62	195.17	8,502.33	-8.33	193.54	193.31	0.90	
8,576.00	2.46	184.49	8,566.29	-10.57	193.20	192.91	1.44	
8,639.00	2.00	180.21	8,629.24	-13.02	193.09	192.75	0.78	
8,703.00	1.31	153.64	8,693.21	-14.79	193.41	193.03	1.59	
8,766.00	1.66	158.96	8,756.19	-16.29	194.06	193.64	0.60	
8,800.00	2.02	156.38	8,790.17	-17.30	194.47	194.04	1.09	
Final MWD S	•							
8,860.00	2.02	156.38	8,850.14	-19.24	195.32	194.84	0.00	
Survey Proje	ection to TD							

Design Report for 5-31D-36 BTR - MWD Survey

Angle Origin Origin Start Type Azimuth Type TVD Target +N/_S +E/-W (°) (ft) (ft) (ft) 0.00

Target 5-31D-36 88.71 Slot 0.00 0.00 BTR_PlanA - Rev0 BHL Tgt

Survey tool program

From Survey/Plan **Survey Tool** (ft) (ft)

133.00 8.860.00 Sperry MWD Surveys MWD

Targets

Target Name Dip Dip - hit/miss TVD +N/-S Northing Easting Dir. +E/-W Angle target (ft) (ft) (ft) (°) (°) (ft) (ft) Latitude Longitude Shano 5-31D-36 0.00 0.00 8,835.00 4.01 178.56 673,180.51 2,248,305.09 40° 10' 41.441 N 110° 36' 40.799 W - actual wellpath misses target center by 28.12ft at 8843.89ft MD (8834.03 TVD, -18.72 N, 195.09 E) - Point 0.00 6,210.00 0.00 4.01 178.56 673,180.51 2,248,305.09 40° 10' 41.441 N 110° 36' 40.799 W - actual wellpath misses target center by 24.15ft at 6219.40ft MD (6210.13 TVD, 21.07 N, 195.65 E) - Rectangle (sides W200.00 H200.00 D2,625.00) 5-31D-36 0.00 0.00 0.00 673,174.73 2.248.126.59 40° 10' 41.401 N 110° 36' 43.099 W - actual wellpath hits target center - Polygon Point 1 28.00 200.00 673,374.99 2,248,152.60 Point 2 28.00 -200.00 672,975.04 2,248,156.57 Point 3

673,374.99

2,248,152.60

200.00

28.00

North Reference Sheet for Sec. 31-T3S-R6W - 5-31D-36 BTR - Plan A

All data is in US Feet unless otherwise stated. Directions and Coordinates are relative to True North Reference.

Vertical Depths are relative to KB=15' @ 6628.00ft (Patterson 506). Northing and Easting are relative to 5-31D-36 BTR

Coordinate System is US State Plane 1927 (Exact solution), Utah Central 4302 using datum NAD 1927 (NADCON CONUS), ellipsoid Clarke 1866

Projection method is Lambert Conformal Conic (2 parallel)


Central Meridian is 111° 30' 0.000 W°, Longitude Origin:0° 0' 0.000 E°, Latitude Origin:40° 39' 0.000 N°

False Easting: 2,000,000.00ft, False Northing: 0.00ft, Scale Reduction: 0.99991672

Grid Coordinates of Well: 673,174.73 ft N, 2,248,126.59 ft E Geographical Coordinates of Well: 40° 10' 41.40" N, 110° 36' 43.10" W Grid Convergence at Surface is: 0.57°

Based upon Minimum Curvature type calculations, at a Measured Depth of 8,860.00ft the Bottom Hole Displacement is 196.27ft in the Direction of 95.63° (True).

Magnetic Convergence at surface is: -10.87° (25 August 2012, , BGGM2012)



Magnetic Model: BGGM2012 Date: 25-Aug-12

Declination: 11.44° Inclination/Dip: 65.75° Field Strength: 52082

Grid North is 0.57° East of True North (Grid Convergence)
Magnetic North is 11.44° East of True North (Magnetic Declination)
lagnetic North is 10.87° East of Grid North (Magnetic Convergence)


To convert a True Direction to a Grid Direction, Subtract 0.57° to convert a Magnetic Direction to a True Direction, Add 11.44° East To convert a Magnetic Direction to a Grid Direction, Add 10.87°

Project: Duchesne County, UT (NAD 1927) Site: Sec. 31-T3S-R6W Well: 5-31D-36 BTR

Bill Barrett Corp



Sperry Drilling




Project: Duchesne County, UT (NAD 1927) Site: Sec. 31-T3S-R6W

Well: 5-31D-36 BTR

Bill Barrett Corp



Sperry Drilling



Division of Oil, Gas and Mining

Operator Change/Name Change Worksheet-for State use only

Effective Date:

11/1/2016

FORMER OPERATOR:	NEW OPERATOR:
Bill Barrett Corporation	Rig II, LLC
1099 18th Street, Suite 2300	1582 West 2600 South
Denver, CO 80202	Woods Cross, UT 84087
CA Number(s):	Unit(s):

WELL INFORMATION:

Well Name	Sec	TWN	RNG	API	Entity	Mineral	Surface	Type	Status
See Attached List									

OPERATOR CHANGES DOCUMENTATION:

1. Sundry or legal documentation was received from the **FORMER** operator on:

10/21/2016

2. Sundry or legal documentation was received from the NEW operator on:

10/21/2016

3. New operator Division of Corporations Business Number:

8256968-0160

REVIEW:

1. Surface Agreement Sundry from NEW operator on Fee Surface wells received on:

N/A

2. Receipt of Acceptance of Drilling Procedures for APD on:

10/21/2016

3. Reports current for Production/Disposition & Sundries:

11/2/2016

4. OPS/SI/TA well(s) reviewed for full cost bonding:

11/3/2016

5. UIC5 on all disposal/injection/storage well(s) approved on:

11/3/2016

6. Surface Facility(s) included in operator change:

None

7. Inspections of PA state/fee well sites complete on (only upon operators request):

11/3/2016

NEW OPERATOR BOND VERIFICATION:

1. Federal well(s) covered by Bond Number:

UTB000712

2. Indian well(s) covered by Bond Number:

LPM 922467

3.State/fee well(s) covered by Bond Number(s):

9219529

DATA ENTRY:

1. Well(s) update in the OGIS on:

11/7/2016

2. Entity Number(s) updated in OGIS on:

11/7/2016

3. Unit(s) operator number update in OGIS on:

N/A

4. Surface Facilities update in OGIS on:

N/A

5. State/Fee well(s) attached to bond(s) in RBDMS on:

11/7/2016

6. Surface Facilities update in RBDMS on:

N/A

COMMENTS:

Well Name	Sec	TWN	RNG	API Number	Entity	Mineral	Surface	Туре	Status
SWD 9-36 BTR	9	030S	060W	4301350646	18077	Indian	Fee	WD	Α
16-6D-46 BTR SWD	6	040S	060W	4301350781	18327	Indian	Fee	WD	Α
6-32-36 BTR SWD	32	030S	060W	4301350921	18329	Indian	Fee	WD	Α
LC TRIBAL 8-26D-47	26	040S	070W	4301334024		Indian	Indian	OW	APD
16-21D-37 BTR	21	030S	070W	4301350758		Indian	Fee	OW	APD
14-11D-37 BTR	11	030S	070W	4301350862		Indian	Fee	OW	APD
7-17D-46 BTR	17	040S	060W	4301350883		Indian	Indian	OW	APD
14-12D-37 BTR	12	030S	070W	4301350894		Indian	Fee	ow	APD
1-18D-36 BTR	18	030S	060W	4301350922		Indian	Fee	OW	APD
13-2D-45 BTR	2	040S	050W	4301350931		Indian	Indian	OW	APD
5H-16-46 BTR	16	040S	060W	4301350992		Indian	Indian	OW	APD
9H-17-45 BTR	17	040S	050W	4301351098		Indian	Indian	OW	APD
13H-8-46 BTR UB	8	040S	060W	4301351124		Indian	Indian	OW	APD
8H-9-46 BTR	9	040S	060W	4301351140		Indian	Indian	ow	APD
LC TRIBAL 7-31D-37	31	030S	070W	4301351147		Indian	Fee	ow	APD
14-16D-45 BTR	16	040S	050W	4301351178	İ	Indian	Indian	ow	APD
16-19D-37 BTR	19	030S	070W	4301351179		Indian	Fee	OW	APD
6-2D-45 BTR	2	040S	050W	4301351234		Indian	Indian	ow	APD
2-2D-45 BTR	2	040S	050W	4301351235		Indian	Indian	OW	APD
10-26-35 BTR	26	030S	050W	4301351248		Indian	Fee	OW	APD
LC TRIBAL 1H-33-46	33	040S	060W	4301351257		Indian	Fee	OW	APD
LC TRIBAL 9-25D-46	25	040S	060W	4301351276		Indian	Indian	OW	APD
LC TRIBAL 8H-30-45	30	040S	050W	4301351277		Indian	Indian	OW	APD
LC TRIBAL 16H-30-45	30	040S	050W	4301351279		Indian	Indian	OW	APD
LC TRIBAL 13-30D-45	30	040S	050W	4301351282		Indian	Indian	OW	APD
LC TRIBAL 16H-36-46	36	040S	060W	4301351291		Indian	Indian	OW	APD
LC TRIBAL 13H-30-46	30	040S	060W	4301351321		Indian	Indian	OW	APD
LC TRIBAL 13H-31-46	31	040S	060W	4301351326		Indian	Indian	OW	APD
LC TRIBAL 16-31D-46	31	040S	060W	4301351328		Indian	Indian	OW	APD
LC TRIBAL 5H-26-47	26	040S	070W	4301351337		Indian	Indian	OW	APD
LC TRIBAL 5H-19-45	20	040S	050W	4301351349		Indian	Indian	OW	APD
LC TRIBAL 16-36D-47	36	040S	070W	4301351363		Indian	Indian	OW	APD
15-4D-47 BTR	4	040S	070W	4301351377		Indian	Fee	OW	APD
16-23D-46 LC TRIBAL	23	040S	060W	4301351396		Indian	Fee	OW	APD
15-2D-36 BTR	2	030S	060W	4301351419		Indian	Fee	OW	APD
16-23D-37 BTR	23	030S	070W	4301351420	1	Indian	Fee	ow	APD
11-9D-47 BTR	9	040S	070W	4301351422		Indian	Fee	OW	APD
15-13D-47 BTR	13	040S	070W	4301351424		Indian	Indian	OW	APD
LC TRIBAL 15-19D-46	19	040S	060W	4301351426	<u> </u>	Indian	Indian	ow	APD
16-13D-45 BTR	13	040\$	050W	4301351428		Indian	Indian	OW	APD

14-12D-45 BTR	12	040S	050W	4301351444	Indian	Indian	OW	APD
16-14D-45 BTR	14	040S	050W	4301351445	Indian	Indian	OW	APD
5-13D-45 BTR	13	040S	050W	4301351446	Indian	Indian	OW	APD
LC TRIBAL 16-26D-46	26	040S	060W	4301351450	Indian	State	OW	APD
LC TRIBAL 10-20D-40	34	0408	060W	4301351451				
16-12D-45 BTR	12	040S	050W	4301351451	Indian Indian	State Indian	OW	APD
8-12D-45 BTR	12	040S	050W	4301351452			OW	APD
LC TRIBAL 1-35D-46	35	040S	060W		Indian	Indian	OW	APD
16-25D-37 BTR		0405	070W	4301351454	Indian	Fee	OW	APD
LC TRIBAL 13H-29-46	25			4301351455	Indian	Fee	OW	APD
	28	0408	060W	4301351462	Indian	Fee	OW	APD
LC TRIBAL 14-30D-37	30	0308	070W	4301351494	Indian	Fee	OW	APD
7-13D-45 BTR	13	0408	050W	4301351497	Indian	Indian	OW	APD
LC TRIBAL 4H-35-46	35	0408	060W	4301351515	Indian	Fee	OW	APD
LC TRIBAL 13H-19-46	19	040\$	060W	4301351543	Indian	Indian	OW	APD
16-26D-37 BTR	26	030S	070W	4301351598	Indian	Fee	OW	APD
LC TRIBAL 16-31D-37	31	030\$	070W	4301351610	Indian	Fee	OW	APD
5-4-35 BTR	4	030S	050W	4301351613	Indian	Fee	OW	APD
LC TRIBAL 16-31D-47	31	040S	070W	4301351616	Indian	Indian	OW	APD
LC TRIBAL 13H-31-47	31	040S	070W	4301351617	Indian	Indian	OW	APD
LC TRIBAL 13-32D-47	32	040S	070W	4301351619	Indian	Indian	OW	APD
LC TRIBAL 16H-32-47	32	040S	070W	4301351620	Indian	Indian	OW	APD
LC TRIBAL 1-32D-47	32	040S	070W	4301351624	Indian	Indian	OW	APD
LC TRIBAL 4H-32-47	32	040S	070W	4301351625	Indian	Indian	OW	APD
LC TRIBAL 13-28D-47	28	040S	070W	4301351627	Indian	Indian	OW	APD
LC TRIBAL 13H-29-47	28	040S	070W	4301351628	Indian	Indian	OW	APD
LC TRIBAL 16H-28-47	28	040S	070W	4301351629	Indian	Indian	OW	APD
LC TRIBAL 1-28D-47	28	040S	070W	4301351639	Indian	Indian	OW	APD
LC TRIBAL 1H-27-47	28	040S	070W	4301351640	Indian	Indian	OW	APD
LC TRIBAL 4H-28-47	28	040S	070W	4301351641	Indian	Indian	OW	APD
LC TRIBAL 7-25D-58	25	050S	W080	4301351643	Indian	Indian	OW	APD
LC TRIBAL 6-25D-58	25	050S	080W	4301351644	Indian	Indian	OW	APD
LC TRIBAL 13H-24-58	24	050S	W080	4301351645	Indian	Indian	OW	APD
LC TRIBAL 16-24D-58	24	050S	080W	4301351646	Indian	Indian	OW	APD
LC Tribal 8-23D-46	23	040S	060W	4301351654	Indian	Fee	OW	APD
LC Tribal 16-35D-45	35	040S	050W	4301351656	Indian	Fee	OW	APD
LC Tribal 13H-35-45	35	040S	050W	4301351657	Indian	Fee	ow	APD
LC Tribal 16-36D-45	36	040S	050W	4301351658	Indian	Fee	ow	APD
LC Tribal 13H-36-45	36	040S	050W	4301351659	Indian	Fee	OW	APD
LC Tribal 5-36D-45	36	0408	050W	4301351661	Indian	Fee	OW	APD
LC Tribal 8-26D-46	26	040\$	060W	4301351663	Indian	Fee	OW	APD
3-29D-36 BTR	29	0308	060W	4301351665	Indian	Fee	OW	APD

LC Tribal 5-35D-45	35	040S	050W	4301351666	Indian	Fee	OW	APD
_C Tribal 5-24D-46	24	0408	060W	4301351668	Indian	Indian	ow	APD
_C TRIBAL 6-12D-58	12	0508	080W	4301351696	Indian	Indian	OW	APD
LC TRIBAL 8-12D-58	12	050S	080W	4301351697	Indian	Indian	OW	APD
.C TRIBAL 16H-22-47	21	040S	070W	4301351700	Indian	Indian	OW	APD
5-25D-37 BTR	25	030S	070W	4301351803	Indian	Fee	OW	APD
8-3D-36 BTR	3	0308	060W	4301351804	Indian	Fee	OW	APD
14-26D-37 BTR	26	0308	070W	4301351805	Indian	Fee	OW	APD
9-4-35 BTR	4	0308	050W	4301351806	Indian	Fee	ow	APD
11-4D-35 BTR	4	030S	050W	4301351807	Indian	Fee	OW	APD
16-27D-37 BTR	27	0308	070W	4301351808	Indian	Fee	OW	APD
14-27D-37 BTR	27	0308	070W	4301351809	Indian	Fee	OW	APD
14-16D-46 BTR	16	040S	060W	4301351812	Indian	Indian	OW	APD
_C Tribal 16-35D-48	35	040S	080W	4301351847	Indian	Indian	OW	APD
LC Tribal 13H-35-48	35	040S	080W	4301351848	Indian	Indian	OW	APD
_C Tribal 13-2D-58	11	050S	080W	4301351850	Indian	Indian	OW	APD
5-13D-36 BTR	13	0308	060W	4301351862	Indian	Fee	OW	APD
5-8D-36 BTR	8	0308	060W	4301351871	Indian	Fee	OW	APD
16-1D-36 BTR	1	0308	060W	4301351872	Indian	Fee	ow	APD
3-18D-46 BTR	18	040S	060W	4301351897	Indian	Fee	OW	APD
_C Tribal 5-36D-46	36	0408	060W	4301351905	Indian	Indian	OW	APD
LC Tribal 5-26D-45	26	040S	050W	4301351907	Indian	Indian	OW	APD
14-13D-45 BTR	13	040S	050W	4301351974	Indian	Indian	OW	APD
14-34D-46 DLB	34	040S	060W	4301351975	Indian	Fee	OW	APD
LC Tribal 5-21D-45	21	0408	050W	4301352001	Indian	Indian	OW	APD
_C Tribal 8-22D-45	22	0408	050W	4301352002	Indian	Indian	OW	APD
_C Tribal 8-25D-45	25	0408	050W	4301352007	Indian	Indian	OW	APD
LC Tribal 16-25D-45	25	040S	050W	4301352008	Indian	Indian	OW	APD
LC Tribal 16-22D-45	22	040S	050W	4301352009	Indian	Indian	OW	APD
LC Tribal 16-26D-45	26	040S	050W	4301352010	Indian	Indian	OW	APD
LC Tribal 14-31D-37	31	0308	070W	4301352016	Indian	Fee	OW	APD
5-12D-45 BTR	12	040S	050W	4301352030	Indian	Indian	ow	APD
LC Tribal 9-20D-45	20	040S	050W	4301352031	Indian	Indian	OW	APD
LC Tribal 13-35D-47	35	0408	070W	4301352055	Indian	Indian	ow	APD
C Tribal 1-23D-47	23	040S	070W	4301352057	Indian	Indian	ow =	APD
9-17D-46 BTR	17	040S	060W	4301352059	Indian	Indian	OW	APD
11-18D-46 BTR	18	040S	060W	4301352060	Indian	Indian	OW	APD
9-10D-47 BTR	10	0408	070W	4301352092	Indian	Fee	OW	APD
LC Tribal 1-17D-47	17	0408	070W	4301352096	Indian	Fee	OW	APD
7-35D-37 BTR	35	0308	070W	4301352115	Indian	Fee	OW	APD
14-25D-37 BTR	25	0308	070W	4301352116	Indian	Fee	OW	APD

LC Tribal 5-25-46	25	040S	060W	4301352126	Indian	Indian	OW	APD
3-33D-35 BTR	33	030S	050W	4301352161	Indian	Fee	OW	APD
5-4D-36 BTR	4	030S	060W	4301352175	Indian	Fee	OW	APD
7-4D-36 BTR	4	030S	060W	4301352176	Indian	Fee	OW	APD
_C Tribal 4-36D-47	36	040S	070W	4301352186	Indian	Indian	OW	APD
LC Tribal 4-22D-46	22	040S	060W	4301352944	Indian	Indian	OW	APD
LC Tribal 16-22D-46	22	040S	060W	4301352945	Indian	Indian	OW	APD
LC Tribal 11-19D-46	19	040S	060W	4301352946	Indian	Indian	OW	APD
LC Tribal 7-20D-45	20	040S	050W	4301352947	Indian	Indian	OW	APD
15-11D-35 BTR	11	030S	050W	4301353056	Indian	Fee	OW	APD
13-11D-35 BTR	11	030S	050W	4301353057	Indian	Fee	OW	APD
3TR 16-36D-37	36	030S	070W	4301353059	Indian	Fee	OW	APD
4-29D-35 BTR	30	030\$	050W	4301353060	Indian	Fee	OW	APD
1-30D-35 BTR	30	0308	050W	4301353061	Fee	Fee	OW	APD
_C TRIBAL 3-23D-46	23	040S	060W	4301353066	Indian	State	OW	APD
_C Tribal 14-23D-46	23	040S	060W	4301353067	Indian	State	OW	APD
_C Tribal 13-25D-46	25	040S	060W	4301353068	Indian	Indian	OW	APD
_C Tribal 14-26D-46	26	040S	060W	4301353069	Indian	State	OW	APD
_C Tribal 5-26D-46	26	040S	060W	4301353070	Indian	State	OW	APD
_C Tribal 11-35D-45	35	040S	050W	4301353071	Indian	State	OW	APD
_C Tribal 7-35D-45	35	040\$	050W	4301353072	Indian	State	OW	APD
_C Tribal 3-35D-45	35	040S	050W	4301353075	Indian	State	OW	APD
_C Tribal 14-36D-45	36	040S	050W	4301353076	Indian	State	OW	APD
_C Tribal 13-36D-45	36	040S	050W	4301353077	Indian	State	OW	APD
_C Tribal 10-36D-45	36	0408	050W	4301353078	Indian	State	OW	APD
_C Tribal 8-36D-45	36	040S	050W	4301353079	Indian	State	OW	APD
LC Tribal 6-36D-45	36	040S	050W	4301353080	Indian	State	OW	APD
LC Tribal 1-34D-46	34	040S	060W	4301353081	Indian	State	OW	APD
_C Tribal 9-27D-46	27	040S	060W	4301353082	Indian	State	OW	APD
_C Tribal 13-35D-45	35	040S	050W	4301353083	Indian	State	OW	APD
_C Tribal 8-35D-45	35	040S	050W	4301353084	Indian	State	OW	APD
_C Tribal 15-35D-45	35	040S	050W	4301353085	Indian	State	OW	APD
LC Tribal 12-25D-45	25	040S	050W	4301353122	Indian	Indian	OW	APD
LC Tribal 14-25D-45	25	040\$	050W	4301353123	Indian	Indian	OW	APD
_C Tribal 10-25D-45	25	040S	050W	4301353124	Indian	Indian	OW	APD
_C Tribal 11-26-45	26	040S	050W	4301353125	Indian	Indian	OW	APD
_C Tribal 13-26D-45	26	040S	050W	4301353126	Indian	Indian	OW	APD
C Tribal 7-31D-46	31	040S	060W	4301353127	Indian	Indian	OW	APD
C Tribal 7-19D-45	19	040S	050W	4301353128	Indian	Indian	OW	APD
_C Tribal 5-19D-45	19	040S	050W	4301353130	Indian	Indian	OW	APD
LC Tribal 7-25D-46	25	040S	060W	4301353132	Indian	Indian	OW	APD

	15.	1							
_C Tribal 7-24D-46	24	0408	060W	4301353134		Indian	Indian	OW	APD
.C Tribal 14-31D-46	31	040S	060W	4301353135		Indian	Indian	OW	APD
C Tribal 14-30D-46	30	040S	060W	4301353136		Indian	Indian	OW	APD
13-4-35 BTR SWD	4	030S	050W	4301353293		Fee	Fee	OW	APD
.C FEE 14-26D-47	26	040S	070W	4301353294	1	Fee	Indian	OW	APD
C Fee 5-25D-47	25	040S	070W	4301353295		Fee	Indian	OW	APD
7-35-46 LC SWD	35	040S	060W	4301353296		Fee	Fee	OW	APD
.C Fee 1H-33-47	32	040S	070 W	4301353309		Fee	Indian	ow	APD
_C FEE 14-2D-58	2	050S	W080	4301353312		Fee	Indian	OW	APD
C FEE 13H-21-47	21	040S	070W	4301353313		Fee	Indian	OW	APD
C Fee 16-21D-47	21	040S	070W	4301353326		Fee	Indian	OW	APD
6-7D-46 BTR	7	040S	060W	4301353328		Fee	Indian	OW	APD
C Fee 15-26D-47	26	040S	070W	4301353331		Fee	Indian	OW	APD
.C Fee 4-24D-47	23	040S	070W	4301353332		Fee	Indian	OW	APD
.C Fee 5-34D-47	34	040S	070W	4301353333		Fee	Indian	OW	APD
.C Fee 5-35D-47	35	040S	070W	4301353334	:	Fee	Indian	OW	APD
3-34D-47 LC Fee	34	040S	070W	4301353337		Fee	Indian	OW	APD
4-35D-35 BTR	35	030S	050W	4301352120		Fee	Fee	OW	DRL
-17D-46 BTR	17	040S	060W	4301351078		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301351187		Indian	Fee	OW	OPS
5-10D-45 BTR	10	040S	050W	4301351221		Indian	Indian	OW	OPS
-3D-45 BTR	3	040S	050W	4301351810		Indian	Indian	OW	OPS
-34D-35 BTR	34	030S	050W	4301352117		Fee	Fee	OW	OPS
-35D-35 BTR	35	030S	050W	4301352118		Fee	Fee	OW	OPS
-2D-46 BTR	2	040S	060W	4301353086		Indian	Fee	OW	OPS
'-21-46 DLB	21	040S	060W	4301333567	16526	Indian	Indian	OW	P
.C TRIBAL 1H-27-46	27	040S	060W	4301333568	18175	Indian	Fee	GW	P
'-29-46 DLB	29	040S	060W	4301333584	17603	Indian	Fee	GW	P
C TRIBAL 12H-28-46	28	0408	060W	4301333631	18132	Indian	Indian	GW	P
.C TRIBAL 13H-21-46	21	0408	060W	4301333632	18107	Indian	Indian	GW	 P
2-36-36 BTR	36	030S	060W	4301333638	16336	Indian	Fee	GW	P
i-5-46 BTR	5	0408	060W	4301333639	16542	Indian	Fee	OW	P
5-23-36 BTR	23	0308	060W	4301333642	16675	Indian	Fee	GW	P
4-29-36 BTR	29	030S	060W	4301333643	16725	Indian	Fee	ow	P
4-30-36 BTR	30	0308	060W	4301333644	16701	Indian	Fee	GW	<u>'</u>
'-20-46 DLB	20	040S	060W	4301333657	16584	Indian	Indian	OW	'P
.C TRIBAL 5-21D-46	21	0408	060W	4301333658	18887	Indian	Indian	OW	P
-20-46 DLB	20	0408	060W	4301333659	18750	Indian	Indian	GW	P
.C TRIBAL 13H-20-46	20	0408	060W	4301333678	17979	Indian	Indian	GW	P
14-7-46 BTR	7	0408	060W	4301333806	16890	Indian	Indian	GW	P
	1.	0.00	100011	TOO OOOOOO	10000	HIMIAII	HIMIAH	UVV	1 1-1

1-5-45 BTR	5	040S	050W	4301333868	16931	Indian	Indian	OW	Р
5-16-36 BTR	16	030S	060W	4301333970	17195	Indian	Fee	ow	P
5-29-36 BTR	29	0308	060W	4301333972	17557	Indian	Fee	OW	P
4-30-36 BTR	30	030S	060W	4301333973	17249	Indian	Fee	OW	P
7-19-46 DLB	19	040S	060W	4301334004	19018	Indian	Indian	OW	Р
5-25-36 BTR	25	0308	060W	4301334021	17126	Fee	Fee	OW	P
5-4-45 BTR	4	0408	050W	4301334089	17507	Indian	Indian	oW	Р
13-2-46 BTR	2	040S	060W	4301334090	18618	Indian	Indian	ow	Р
2-3-45 BTR	3	040S	050W	4301334099	17932	Indian	Indian	OW	Р
7-6-45 BTR	6	040S	050W	4301334100	17653	Indian	Indian	OW	Р
1-9-45 BTR	9	0408	050W	4301334101	17910	Indian	Indian	OW	Р
8-10-45 BTR	10	040S	050W	4301334102	17530	Indian	Indian	ow	Р
7-17-45 BTR	17	040S	050W	4301334104	17933	Indian	Indian	OW	Р
16-7-45 BTR	7	040S	050W	4301334111	17665	Indian	Indian	OW	Р
15-18-45 BTR	18	040S	050W	4301334112	17832	Indian	Indian	ow	P
6-12-46 BTR	12	040S	060W	4301334114	17964	Indian	Indian	ow	P
5-13-46 BTR	13	040S	060W	4301334115	17833	Indian	Indian	OW	Р
16-26-36 BTR	26	030S	060W	4301334132	18028	Indian	Fee	ow	Р
1-23-36 BTR	23	030S	060W	4301334136	17722	Indian	Fee	OW	Р
15-10-36 BTR	10	030S	060W	4301334277	17419	Indian	Fee	ow	Р
14-5-46 BTR	5	040S	060W	4301350307	17624	Fee	Fee	ow	Р
14X-22-46 DLB	22	040S	060W	4301350351	17604	Indian	Indian	ow	Р
16-13-36 BTR	13	030S	060W	4301350372	17853	Indian	Fee	ow	Р
5-33-46 DLB	33	040S	060W	4301350397	17765	Indian	Fee	OW	Р
5-34-46 DLB	34	040S	060W	4301350415	17801	Indian	State	GW	Р
LC FEE 12H-32-46	32	040S	060W	4301350431	18003	Fee	Fee	OW	Р
1-13D-47 BTR	13	040S	070W	4301350445	18205	Indian	Fee	OW	Р
16-8D-45 BTR	8	040S	050W	4301350466	18799	Indian	Indian	OW	Р
7-13D-46 BTR	13	040S	060W	4301350470	18076	Indian	Indian	OW	Р
14-8D-45 BTR	8	040S	050W	4301350567	18207	Indian	Indian	OW	Р
14-5D-45 BTR	5	040S	050W	4301350568	18108	Indian	Indian	OW	Р
16-31D-36 BTR	31	030S	060W	4301350573	18004	Indian	Fee	OW	P
5-7D-46 BTR	7	040S	060W	4301350574	18176	Indian	Indian	OW	Р
LC TRIBAL 13H-33-46	34	040S	060W	4301350575	18223	Indian	State	OW	Р
5-8-45 BTR	8	040S	050W	4301350607	18279	Indian	Indian	OW	Р
16-6D-45 BTR	6	040S	050W	4301350610	18177	Indian	Indian	OW	P
5-18D-45 BTR	18	040S	050W	4301350611	18300	Indian	Indian	OW	Р
7-26-37 BTR	26	030\$	070W	4301350641	18131	Indian	Fee	OW	Р
3-11D-36 BTR	11	030S	060W	4301350642	18299	Indian	Fee	OW	Р
16-1D-46 BTR	1	040S	060W	4301350675	18525	Indian	Indian	ow	Р
14-3-45 BTR	3	040S	050W	4301350676	18363	Indian	Indian	ow	Р

4-17D-45 BTR	17	040S	050W	4301350687	18517	Indian	Indian	OW	Р
5-6D-45 BTR	6	040S	050W	4301350688	18726	Indian	Indian	OW	P
7-7D-45 BTR	7	040S	050W	4301350689	18380	Indian	Indian	OW	P
14-10D-45 BTR	10	040S	050W	4301350754	18447	Indian	Indian	OW	P
14-9D-45 BTR	9	040S	050W	4301350755	18379	Indian	Indian	OW	P
13-16D-36 BTR	16	030S	060W	4301350757	18206	Indian	State	OW	Р
5-9D-36 BTR	9	030S	060W	4301350843	18381	Indian	Fee	OW	P
16-5D-46 BTR	5	040S	060W	4301350844	18280	Fee	Fee	OW	Р
5-27D-37 BTR	27	030S	070W	4301350847	18526	Indian	Fee	OW	Р
7-4D-45 BTR	4	040S	050W	4301350884	18562	Indian	Indian	OW	Р
2-16D-45 BTR	16	040S	050W	4301350899	18619	Indian	Indian	OW	Р
16-10D-45 BTR	10	040S	050W	4301350902	18725	Indian	Indian	OW	P
5-2D-36 BTR	2	030S	060W	4301350913	18886	Indian	Fee	ow	Р
13H-27-36 BTR	27	030S	060W	4301350918	18445	Indian	State	ow	Р
8-16D-46 BTR	16	040S	060W	4301350953	19027	Indian	Indian	OW	Р
16-16D-46 BTR	16	040S	060W	4301350956	19028	Indian	Indian	OW	Р
16-9D-45 BTR	9	040S	050W	4301350962	18662	Indian	Indian	OW	Р
14-31D-36 BTR	31	030S	060W	4301350973	18524	Indian	Fee	OW	Р
5-10D-36 BTR	10	030S	060W	4301350978	18989	Indian	Fee	OW	Р
1-32D-36 BTR	32	030S	060W	4301350979	18648	Indian	Fee	OW	Р
16-12D-36 BTR	12	030S	060W	4301350980	18748	Indian	Fee	ow	Р
2-18D-45 BTR	18	040S	050W	4301350991	18776	Indian	Indian	OW	Р
3-1-46 BTR	1	040S	060W	4301351017	18777	Indian	Fee	ow	Р
10-5-45 BTR	5	040S	050W	4301351062	18724	Indian	Indian	OW	Р
12-4D-45 BTR	4	040S	050W	4301351063	18813	Indian	Indian	ow	Р
1-10D-45 BTR	10	040S	050W	4301351064	18966	Indian	Indian	ow	Р
16-2D-46 BTR	2	040S	060W	4301351079	18830	Indian	Indian	OW	Р
9H-4-45 BTR	4	040S	050W	4301351092	18814	Indian	Indian	OW	Р
12-17-45 BTR	17	040S	050W	4301351097	18984	Indian	Indian	OW	Р
5-9D-46 BTR	9	040S	060W	4301351109	19313	Indian	Fee	OW	Р
14-9D-36 BTR	9	030S	060W	4301351144	19004	Indian	Fee	OW	Р
5-31D-36 BTR	31	030S	060W	4301351146	18691	Indian	Fee	OW	Р
4-9D-45 BTR	9	040S	050W	4301351157	18883	Indian	Indian	OW	Р
8-12D-46 BTR	12	040S	060W	4301351159	18911	Indian	Indian	OW	Р
LC TRIBAL 16-23D-47	23	040S	070W	4301351180	18617	Indian	Indian	OW	Р
14-7D-45 BTR	7	040S	050W	4301351222	18949	Indian	Indian	OW	Р
5-16D-45 BTR	16	040S	050W	4301351223	18987	Indian	Indian	OW	Р
4-5D-45 BTR	5	040S	050W	4301351242	18882	Indian	Indian	OW	P
LC TRIBAL 16H-19-45	19	0408	050W	4301351278	18627	Indian	Indian	OW	Р
LC TRIBAL 13-19D-45	19	040S	050W	4301351280	18628	Indian	Indian	OW	Р
LC TRIBAL 5-30D-45	30	040S	050W	4301351281	19448	Indian	Indian	OW	Р

LC TRIBAL 15-24D-46	24	040S	060W	4301351283	18626	Indian	Indian	OW	Р
LC TRIBAL 13H-24-46	19	040S	050W	4301351289	18629	Indian	Indian	ow	Р
7-16-47 BTR	16	040S	070W	4301351296	18950	Indian	Fee	ow	P
14-18D-45 BTR	18	040S	050W	4301351313	19005	Indian	Indian	ow	Р
LC TRIBAL 16-30D-46	30	040S	060W	4301351320	19006	Indian	Indian	ow	Р
LC TRIBAL 5-20D-45	20	040S	050W	4301351331	19449	Indian	Indian	ow	Р
11-8D-46 BTR	8	040S	060W	4301351336	19314	Indian	Indian	OW	Р
5-7D-45 BTR	7	040S	050W	4301351350	18951	Indian	Indian	ow	Р
7-5-35 BTR	5	030S	050W	4301351599	19078	Indian	Fee	OW	P
13-5D-35 BTR	5	030S	050W	4301351600	18996	Indian	Fee	ow	Р
11-5D-35 BTR	5	030S	050W	4301351601	19061	Fee	Fee	OW	Р
15-5D-35 BTR	5	030S	050W	4301351602	19062	Fee	Fee	OW	Р
9-5D-35 BTR	5	030S	050W	4301351609	19029	Indian	Fee	ow	Р
3-5D-35 BTR	5	030S	050W	4301351638	19079	Indian	Fee	OW	Р
7-8-46 BTR	8	040S	060W	4301351702	19315	Indian	Indian	ow	Р
7-30-46 DLB	30	040S	060W	4301351703	18997	Fee	Indian	OW	Р
3-13D-46 BTR	13	040S	060W	4301351718	18881	Indian	Indian	ow	Р
2-13D-46 BTR	13	040S	060W	4301351719	18885	Indian	Indian	OW	Р
12-12D-46 BTR	12	040S	060W	4301351720	18867	Indian	Indian	OW	P
10-12D-46 BTR	12	040S	060W	4301351721	18856	Indian	Indian	ow	Р
11-11D-47 BTR	11	040S	070W	4301352091	19633	Fee	Fee	ow	P
7-12D-47 BTR	12	040S	070W	4301352094	19600	Indian	Fee	ow	Р
5-12D-47 BTR	12	040S	070W	4301352095	19634	Indian	Fee	ow	Р
14-33D-35 BTR	33	030S	050W	4301352162	19450	Indian	Fee	ow	Р
16-33D-35 BTR	33	030S	050W	4301352163	19451	Indian	Fee	ow	Р
14-22-46 DLB	22	040S	060W	4301333660	17604	Indian	Indian	D	PA
13H-31-36 BTR	31	0308	060W	4301350465	18485	Indian	Fee	OW	PA
16X-23D-36 BTR	23	030S	060W	4301350623	18007	Indian	State	OW	PA
8-6-45 BTR	6	040S	050W	4301350900	18561	Indian	Indian	ow	PA
13-13-36 BTR	13	030S	060W	4301350919	18364	Indian	Fee	OW	PA
7-28-46 DLB	28	040S	060W	4301333569	16460	Indian	Indian	OW	S
5-21-36 BTR	21	030S	060W	4301333641	16674	Indian	Fee	GW	S
13-26-36 BTR	26	030S	060W	4301333980	17569	Indian	Fee	OW	S
14-1-46 BTR	1	040S	060W	4301334113	18516	Indian	Indian	OW	S
16-21-36 BTR	21	030S	060W	4301334130	17721	Indian	Fee	OW	S
14-21-36 BTR	21	030S	060W	4301334131	18006	Indian	Fee	OW	S
7-16-36 BTR	16	030\$	060W	4301334133	17834	Indian	Fee	OW	s
1-30-36 BTR	30	0308	060W	4301334134	17905	Indian	Fee	OW	S
16-30-36 BTR	30	0308	060W	4301334135	18005	Indian	Fee	OW	S
3-23-36 BTR	23	0308	060W	4301334137	17860	Indian	Fee	OW	S
16-16-36 BTR	16	0308	060W	4301334138	17666	Indian	Fee	OW	S

4-26-36 BTR	26	030S	060W	4301334139	17620	Fee	Fee	OW	S
9-11-36 BTR	11	030S	060W	4301334276	17451	Indian	Fee	OW	S
3-36-36 BTR	36	030S	060W	4301350398	17955	Indian	Fee	OW	S
7-10-36 BTR	10	030S	060W	4301350437	18052	Indian	Fee	OW	S
16-12D-46 BTR	12	040S	060W	4301350467	18051	Indian	Indian	OW	S
13H-13-46 BTR	13	040S	060W	4301350468	18208	Indian	Indian	OW	S
13-12-46 BTR	12	040S	060W	4301350469	18233	Indian	Indian	OW	S
14-8D-36 BTR	8	030S	060W	4301350612	18163	Indian	Fee	OW	S
14-7D-36 BTR	7	030S	060W	4301350613	18330	Indian	Fee	OW	S
16-9-36 BTR	9	030S	060W	4301350645	18078	Indian	Fee	ow	S
7-27-37 BTR	27	030S	070W	4301350647	18090	Indian	Fee	OW	S
16-12D-37 BTR	12	030S	070W	4301350785	18446	Indian	Fee	OW	S
14-21D-37 BTR	21	030S	070W	4301350859	18548	Indian	Fee	OW	S
10-18D-36 BTR	18	030S	060W	4301350915	18884	Indian	Fee	ow	S
5-27D-36	27	030S	060W	4301350917	18482	Indian	State	ow	S
10-36D-36 BTR	36	030S	060W	4301351005	18523	Indian	Fee	OW	S
14-6D-45 BTR	6	040S	050W	4301351158	18967	Indian	Indian	ow	S
5H-1-46 BTR UTELAND BUTTE	6	040S	050W	4301351215	18728	Indian	Indian	OW	S
5H-1-46 BTR WASATCH	6	040S	050W	4301351216	18727	Indian	Indian	OW	S
1-25D-36 BTR	25	030S	060W	4301351294	18798	Indian	Fee	OW	S
5-5D-35 BTR	5	030S	050W	4301351605	19055	Indian	Fee	ow	S
16-23-36 BTR	23	030S	060W	4301333971	17182	Indian	Fee	ow	TA
LC TRIBAL 14-23D-47	23	040S	070W	4301334022	18616	Indian	Indian	OW	TA
5-32D-36 BTR	32	030S	060W	4301350756	18328	Indian	Fee	ow	TA



October 20, 2016

RECEIVED

OCT 21 2016

Re: Bill Barrett Corporation Transfer to New Operator

DIV. OF OIL, GAS & MINING

Dear Ms. Medina:

Attached please find the change of operation Form 9, Form 5's and Request to Transfer APD formchanging the operator from Bill Barrett Corporation to RIG II, LLC, effective 11/1/2016. Badlands Energy – Utah, LLC will be a sub-operator.

New Operator Contact information:

RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 Telephone:(801) 683-4245 Fax:(801) 298-9889

Upon reviewing the attached, please contact myself with any questions at 303-312-8115.

Sincerely,

Bill Barrett Corporation

Brady Riley Permit Analyst

STATE OF UTAH FORM 9 **DEPARTMENT OF NATURAL RESOURCES** 5. LEASE DESIGNATION AND SERIAL NUMBER: DIVISION OF OIL, GAS AND MINING (see attached well list) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME: SUNDRY NOTICES AND REPORTS ON WELLS N/A 7, UNIT or CA AGREEMENT NAME: Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. 1. TYPE OF WELL 8. WELL NAME and NUMBER OIL WELL 🔽 GAS WELL (see attached well list) 2. NAME OF OPERATOR: 9. API NUMBER RIG II, LLC 3. ADDRESS OF OPERATOR PHONE NUMBER: 10. FIELD AND POOL, OR WILDCAT: 1582 West 2600 South (801) 683-4245 STATE UT ZIP 84087 Wood Cross 4. LOCATION OF WELL FOOTAGES AT SURFACE: (see attached well list) COUNTY: QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: STATE: UTAH CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 11. TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE REPERFORATE CURRENT FORMATION NOTICE OF INTENT (Submit in Duplicate) ALTER CASING FRACTURE TREAT SIDETRACK TO REPAIR WELL Approximate date work will start; CASING REPAIR **NEW CONSTRUCTION** TEMPORARILY ABANDON 11/1/2016 CHANGE TO PREVIOUS PLANS OPERATOR CHANGE TUBING REPAIR CHANGE TUBING PLUG AND ABANDON VENT OR FLARE SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK WATER DISPOSÁL (Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME) WATER SHUT-OFF Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE OTHER: CONVERT WELL TYPE **RECOMPLETE - DIFFERENT FORMATION** 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. RIG II, LLC IS SUBMITTING THIS SUNDRY AS NOTIFICATION THAT THE WELLS LISTED ON THE ATTACHED LIST HAVE BEEN SOLD TO-Rig II, LLC BY BILL BILL BARRETT CORPORATION EFFECTIVE 11/1/2016. PLEASE REFER ALL FUTURE CORRESPONDENCE TO THE ADDRESS BELOW. RIG II, LLC 1582 West 2600 South Woods Cross, Utah 84087-0298 801-683-4245 (STATE/FEE BOND # 9219529/ BLM BOND # UTB000712/ BIA BOND # LPM9224670) BILL BARRETT CORPORATION NOILS RIG II, LLC MAME (PLEASE PRINT) _ NAME (PLEASE PRINT) SIGNATURE SIGNATURE EH&S, Government and Regulatory Affairs Jesse McSwain Manager NAME (PLEASE PRINT) 1012016

APPROVED

NOV 0 7 2016

(This space for State use only)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

Request to Transfer Application or Permit to Drill

	(This form should ac	ccompany a Sundr	y Notice, Form 9, reque	esting APD transfer)		
Well	name:	(See attached li	st)			
API ı	number:					
Loca	ation:	Qtr-Qtr:	Section:	Township: Range:		
Com	pany that filed original application:	Bill Barrett Corp	oration			
Date	original permit was issued:					
Com	pany that permit was issued to:	Bill Barrett Cor	poration			
Check one		Des	ired Action:			
	Transfer pending (unapproved) App					
	The undersigned as owner with legal r submitted in the pending Application for owner of the application accepts and a	or Permit to Dril	l, remains valid ar	nd does not require revision. The	new	
✓	Transfer approved Application for F	ermit to Drill t	o new operator			
	The undersigned as owner with legal r information as submitted in the previous revision.				re	
Folio	owing is a checklist of some items rel	ated to the ap	plication, which s	should be verified.	Yes	No
If loc	ated on private land, has the ownership	changed?			√	
	if so, has the surface agreement been	updated?				✓
	e any wells been drilled in the vicinity of tirements for this location?	the proposed w	rell which would af	fect the spacing or siting		✓
	e there been any unit or other agreemen osed well?	ts put in place t	hat could affect th	e permitting or operation of this		✓
	there been any changes to the access osed location?	route including	ownership or righ	t-of-way, which could affect the		✓
Has t	the approved source of water for drilling	changed?				✓
	e there been any physical changes to the s from what was discussed at the onsite		on or access route	which will require a change in		✓
Is bo	nding still in place, which covers this pro	posed well? B	ond No. 9219529-UDOGM/U	JTB000712-BLM / LPM9224670-BIA	1	
shou nece	desired or necessary changes to either a ld be filed on a Sundry Notice, Form 9, o ssary supporting information as required	or amended Ap	plication for Permi			red,
	e (please print) Jesse McSwain		Title Manager	2110		
_	esenting (company name) RIG II, LLC		Date 10 0	<u> 114 </u>		
rtepi	cooming (company name)			· · · · · · · · · · · · · · · · · · ·		

The person signing this form must have legal authority to represent the company or individual(s) to be listed as the new operator on the Application for Permit to Drill.

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL, GAS AND MINING

•	TRAI	NSFE	R OF	AUTHORITY TO INJECT	•
Well Name and Number 6-32-36 BTR SWD		4			API Number 4301350921
Location of Well				DUQUENOE	Field or Unit Name CEDAR RIM
Footage: 1628 FNL 1553 FWL QQ, Section, Township, Range: SENW	32	3S	6W	County : DUCHENSE State : UTAH	Lease Designation and Number 2OG0005608

EFFECTIVE DATE OF TRANSFER: 11/1/2016

CURRENT OP	PERATOR	
Company:	BILL BARRETT CORPORATION	Name: Duane Zavadil
Address:	1099 18th Street Ste 2300	Signature: 2nCd
	city DENVER state CO zip 80202	Senior Vice President - Title: EH&S, Government and Regulatory Affairs
Phone:	(303) 293-9100	Date: 10 20 16
Comments	· · · · · · · · · · · · · · · · · · ·	

Address: 1582 West 2600 South Signature: Signature: Manager	Company: RIG II, LLC Name: Jesse McSwain	
10/2 . 111	1593 West 2000 Courts	R:
(004) 002 4045	city Wood Cross state UT zip 84087 Title: Manager	
Phone: (801) 683-4245 Date: 10 LC 10	Phone: (801) 683-4245 Date: 10 20 10	

(This space for State use only)

Transfer approved by:

Approval Date: ///3//L

Comments:

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	JTHORITY TO INJECT	Γ
Well Name and 16-6D-46 BT			API Number 4301350781
ocation of Well		:	Field or Unit Name
Footage: 0200 FSL 0099 FEL		County : DUCHESNE	ALTAMONT Lease Designation and Number
QQ, Section,	Township, Range: SESE 6 4S 6W	State: UTAH	20G0005608
	11/1/2016		
EFFECTIVE L	DATE OF TRANSFER: 11/1/2016		
CURRENT OP	PERATOR		
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil
Address:	1099 18th Street Ste 2300	Signature:	m Zinal
	city DENVER state CO zip 80202	SeniorV	ice President - Government and Regulatory Affairs
Phone:	(303) 293-9100	Date:	20/16
Comments:			
oommonto.	•		
NEW OPERAT			
VEW OF LINA	iok		
Company:	RIG II, LLC	Name: Jesse	McSwain ⁽
Address:	1582 West 2600 South	Signature:	Leve MG:
, , , , , , , , , , , , , , , , , , , ,	city Wood Cross state UT zip 84087	Title: Mana	
Phone:	(801) 683-4245	Date:	120/16
Comments:	:		
This space for S	state use only)	· ·	1
Transfer ap	oproved by:	Approval Date:	11/3/16
	Title: VIC		•

Comments:

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

	TRANSFER OF AL	JTHORITY TO INJEC	Γ
ell Name and SWD 9-36 B	TR		API Number 4301350646
cation of Well			Field or Unit Name CEDAR RIM
Footage: 0	539 FSL 0704 FEL	County : DUCHESNE	Lease Designation and Number
QQ, Section,	Township, Range: SESE 9 3S 6W	State: UTAH	2OG0005608
FFECTIVE	DATE OF TRANSFER: 11/1/2016		
URRENT OP	PERATOR		
	DV L DADDETT CODDODATION	_	
Company:	BILL BARRETT CORPORATION	Name: Duane	e Zavadil
Address:	1099 18th Street Ste 2300	Signature: Senior V	rice President -
	city DENVER state CO zip 80202	Title: EH&S, G	Government and Regulatory Affairs
Phone:	(303) 293-9100	Date: <u>\</u>	2014
Comments:			
EW OPERAT	FOR		
Company:	RIG II, LLC	Name: Jesse	McSwain
Address:	1582 West 2600 South	Signature:	ENE MEG-
	city Wood Cross state UT zip 84087	Title: Mana	ger
Phone:	(801) 683-4245	Date:	20/16
Comments:			
is space for S	tate use only)		
Transfer ap	proved by:	Approval Date:	
	Title:		
	This well was own	rived by USE.	PH.
Comr	ments: This well was approved with	Il be required.	
	EPH approved to.		